


Universidade do Minho
Escola de Engenharia

João Carlos Amaro Ferreira

**Mobi-System: Towards an Information System to
Support Sustainable Mobility with Electric Vehicle Integration**

December 2013



Universidade do Minho
Escola de Engenharia



João Carlos Amaro Ferreira

**Mobi-System: Towards an Information System to Support
Sustainable Mobility with Electric Vehicle
Integration**

Programa MIT-Portugal – Área EDAM

Programa Doutoral em Líderes para as Indústrias Tecnológicas

Trabalho efetuado sob a orientação de:

Professor Doutor João Luiz Afonso

Professor Doutor Alberto Manuel Rodrigues da Silva

December 2013

DECLARAÇÃO

Nome

João Carlos Amaro Ferreira

Título dissertação □/tese x

Mobi-System: Towards an Information System to Support Sustainable Mobility with Electric Vehicle Integration

Orientador(es):

Professor Doutor João Luiz Afonso

Professor Doutor Alberto Manuel Rodrigues da Silva

Ano de conclusão: 2011

Designação do Mestrado ou do Ramo de Conhecimento do Doutoramento:

Programa Doutoral em Líderes para as Indústrias Tecnológicas

É AUTORIZADA A REPRODUÇÃO INTEGRAL DESTA TESE/TRABALHO APENAS PARA EFEITOS DE INVESTIGAÇÃO, MEDIANTE DECLARAÇÃO ESCRITA DO INTERESSADO, QUE A TAL SE COMPROMETE;

Universidade do Minho, 06 de Dezembro, 2013¹

¹ This dissertation was updated with minor changes and improvements on October 2013 and December 2013, namely with the a general revision of Chapter 1 and Chapter 2 due to some significant suggestions sent by members of the Jury Committee. Furthermore, the dissertation was also updated by including the most relevant and recent references to the papers authored in the context of this research work.

ACKNOWLEDGEMENTS

It is a pleasure to thank those who made this Thesis possible: my students, colleges at ISEL, Vítor Monteiro, Luís Reis and Helena Silva.

Also a special thanks to Professor António Cunha for initial advice on Electric Vehicle topic.

Foremost, I would like to express my sincere gratitude to my advisors Professor João Afonso and Professor Alberto Silva for the continuous support of my Ph.D study and research.

My final words go to my family. In this type of work the relatives are always mistreated.

ABSTRACT

The current Thesis proposes the conceptual aspects and the preliminary prototype of a mobile information system to support information integration and manipulation towards the Electric Vehicle (EV) introduction, and the support of mobility process in urban environments, giving recommendations to drivers about EV range autonomy, charging stations, electricity market, and also as route planner taking into account public transportation, car or bike sharing systems.

The main work objective is the creation of an Information and Communication Technology (ICT) platform based on successful approaches developed in the Computer Science Area, recommender systems, cooperative systems and mobile devices, to help the driver of EV by giving real time information related with EV charging process, range autonomy, electricity market participation, and also smart mobility process in cities by giving guidance towards best route options, taking into account time travel and CO₂ emissions.

Based on the analysis of the problem a conceptual system and a prototype application were created under the designation “Mobi-System”, designed to mobile devices, with relevant information oriented to: (1) EV charging process; (2) EV range autonomy; (3) electricity market participation; and (4) mobility process in smart cities of the future. In this work it was developed an application to store data related with EV charging/discharging process, for further intelligent analysis and remote interaction with the charging system, determining a smart charging procedure, taking into account the distribution electrical system limitations, and the creation of communities with participation in the electricity market. A range estimation and representation process is introduced as part of the help process to assist EV drivers. An Aggregator system and a collaborative broker for distributed energy sources are proposed, taking into account the electricity market. A proposal for data integration of different transportation sources and a multimodal best route path are proposed based on CO₂ emissions and time travel.

Keywords: Sustainable Transportation System, Electric Vehicle, Smart Grid System, Electricity Market, Users Collaboration, Sustainable Mobility Process, User Profile, V2G (Vehicle-to-Grid) System, Range Anxiety Problem, Mobile Device, Geographic Information System, Electromobility.

RESUMO

O presente trabalho consiste na concepção e discussão do sistema Mobi-System, que disponibiliza informação relevante para condutores de veículos elétricos (VE), tendo em conta os problemas dos carregamentos dos VE, a gestão da ansiedade de autonomia (range anxiety) dos condutores, a participação no mercado de energia elétrica, a integração das fontes de energia renováveis, bem como a integração de informação de transportes públicos e a criação de sistemas para gerir o problema da mobilidade sustentável em cidades inteligentes (smart cities).

O objetivo principal do trabalho é o uso apropriado de Tecnologia da Informação e Comunicação (TIC) baseada em abordagens bem-sucedidas desenvolvidas na área da informática, como os sistemas de recomendação, sistemas cooperativos e dispositivos móveis para ajudar o condutor de VE, dando informações relevantes em tempo real, orientando o condutor para os pontos de carregamento públicos, ou para o melhor caminho tendo em conta o tempo e as políticas ambientais, nomeadamente as emissões de CO₂.

Com base na análise do problema, um sistema conceitual e uma aplicação protótipo foram criadas sob a designação de Mobi-System, projetada para dispositivos móveis com informações relevantes orientadas a: (1) processo de carregamento do VE feito num local público com a orientação e a reserva de slots de carregamento, ou em casa com a programação do processo de carregamento lento, tendo em conta limitações de potência; (2) gestão assistida da autonomia dos VE; (3) participação no mercado de energia, pela criação de comunidades de condutores com capacidade de participar no mercado de energia, dado o VE poder atuar como um armazenador de energia; e (4) processo de mobilidade em cidades inteligentes do futuro, com a proposta de integração de dados de diferentes tipos de transporte, com indicação do trajeto de melhor rota multimodal, proposto com base nas emissões de CO₂ e no tempo das viagens.

Palavras-Chave: Sistema de Transporte Sustentável, Veículo Elétrico, Rede Elétrica Inteligente (Smart Grid), Mercado de Eletricidade, Colaboração entre Utilizadores, Mobilidade Sustentável, Perfil do Utilizador, Sistema Veículo-Rede (Vehicle-to-Grid System), Problema de Ansiedade de Autonomia, Dispositivo Móvel, Sistema de Informação Geográfica, Mobilidade Elétrica.

INDEX

AKNOWLEDGEMENTS	III
ABSTRACT	III
RESUMO	IV
INDEX	V
INDEX OF FIGURES.....	VIII
1. INTRODUCTION	1
1.1. Context	5
1.2. Research Problems and Goals	9
1.3. Research Methodology	13
1.4. Main Contributions.....	14
1.5. Outline of the Thesis	20
2. LITERATURE REVIEW	21
2.1. Smart Cities	21
2.2. Vehicles	21
2.3. Electricity Market.....	27
2.4. Electromobility	35
2.5. Projects related with Mobi-System	43
2.6. Related European Projects.....	44
2.7. Conclusions	46
3. MOBI-SYSTEM: EV RELATED FUNCTIONS	47
3.1. Information Extraction from EV and Charging Device	47
3.2. Information Repository	50
3.3. Driver Profile.....	50
3.4. Public Charging Station.....	51
3.5. Tracking System in ‘Offline’ Mode Drive	54
3.6. Weather Module	56

3.7. Geo-Reference Graph for the Electrical Distribution Network	58
3.8. Home Consumption Simulation	60
3.9. Smart Charging Strategy	65
3.10. Range Prediction Functions	68
3.11. Recommendation Engine and System.....	74
3.12. Conclusions	77
4. MOBI-SYSTEM: ELECTRICITY MARKET FUNCTIONS	79
4.1. EV Aggregations	79
4.2. Microgeneration and Distributed Energy Resources	90
4.3. Collaborative Aggregator Broker for DER	94
4.4. Conclusions	101
5. MOBI-SYSTEM: SUSTAINABLE MOBILITY FUNCTIONS	103
5.1. Real Time Information and Best Path	105
5.2. Car Pooling System.....	110
5.3. Car Sharing System.....	119
5.4. Bike Sharing System	121
5.5. Public Transportation Information Integration	124
5.6. Transportation Best Advice and Green Route Planer	128
5.7. Conclusions	133
6. MOBI-SYSTEM: USER APPLICATION AND CASE STUDY	135
6.1. V2G Smart System (Web Application).....	136
6.2. SiREV Application.....	140
6.3. IRecommendit: Windows Mobile Application	145
6.4. Mobile Application Usage Results (Case Study).....	148
6.5. SITP Application.....	161
6.6. Conclusion.....	164
7. CONCLUSION	165

7.1. Future Work.....	169
7.2. Expected Impacts of Current Work.....	169
ANNEX	173
A.1 Ontology for Public Transportation (OPT).....	173
A.2 Search Public Transportation Routes.....	176
A.3 Best Path Implementation	177
A.4 Calculate the Price of the Trip	178
BIBLIOGRAPHY AND REFERENCES	181

INDEX OF FIGURES

Figure 1-1: EV sales and charging infrastructure available in 2012 from [IEA, 2013].	2
Figure 1-2: Main challenge to achieve between EV and Renewable Energy Resources, with Portuguese data from [Pinho, 2008].	3
Figure 1-3: Current situation (on the start of this research project in 2008).	6
Figure 1-4: Future tendencies for current research area work.	7
Figure 1-5: Main research goal and related areas.	8
Figure 1-6: Purpose of current research work: mobile information system design, with focus in the driver's information needs adapted to the new reality of EV introduction and cooperation with transportation infrastructures.	10
Figure 1-7: Mobi-System Chapter organization.	13
Figure 2-1: Main vehicle types.	24
Figure 2-2: Global Green house gasses emissions [Rosmarino, 2009].	25
Figure 2-3: Greenhouse emissions emissions for different types of small vehicles [Argone, 2009].	26
Figure 2-4: EV battery charge and Low Voltage (LV) typical consumption in a day, [ERSE, 2009].	29
Figure 2-5: Current reality of electricity market, from [EPRI, 2010].	29
Figure 2-6: Illustrative diagram of the EVs mode of V2G (discharging process) and G2V (charging process).	33
Figure 2-7: General layout of an electrical network. A transmission grid is usually defined for voltages higher than 110 kV, and a distribution grid for voltages lower than [Mbizon, 2010].	34
Figure 2-8: Main methods of charging EV batteries.	37
Figure 2-9: Number of Public EV Charging Stations by countries (status June 2011).	39
Figure 2-10: Evolution of the SoC of an EV battery pack for a typical day.	42
Figure 2-11: Personal Context of current research work.	44
Figure 3-1: EV functions main modules.	47
Figure 3-2: Main information to extract and commands to perform on charging device.	48
Figure 3-3: Visualization of VEECO extracted information in an external laptop [Gead, 2011].	49
Figure 3-4: User Profile Operations.	51
Figure 3-5: Fields of KML file for information exchange with charging station.	52
Figure 3-6: Image of a Public charging infrastructure.	53
Figure 3-7: SGR penalty points to avoid user reservation failures.	54
Figure 3-8: Main module of driver's tracking system in a mobile device with GPS, and information created from drivers movements database.	55
Figure 3-9: Menu de Opções da Aplicação GPS Tracker.	55
Figure 3-10: Menu Principal da Aplicação GPS Tracker.	56

Figure 3-11: Electricity demand in the CalISO area as function of average daily temperatures: 2004 [Crowley, 2003].	57
Figure 3-12: Electrical distribution network, transformed in a graph.	59
Figure 3-13: Geo-reference electrical distribution network with power limitations.	59
Figure 3-14: Simulation approach methodology.	62
Figure 3-15: Simulation application on Netlog.	62
Figure 3-16: Smart Charging approach and goals.	66
Figure 3-17: Power Consumption Distribution (all types of family).	67
Figure 3-18: Large family consumption simulation results.	67
Figure 3-19: Main parameters for range prediction.	69
Figure 3-20: Range representation process using Google Maps API.	71
Figure 3-21: Range estimation of a Lisbon trip to north. Four different cases are showed.	72
Figure 3-22: Representation of charging range for different SoC levels at a charging process.	73
Figure 3-23: Range estimation with a low SoC level.	73
Figure 3-24: Range estimation based on the uncertainty factors showed at Figure 3-19.	74
Figure 3-25: Recommender System.	75
Figure 3-26: Nearest Neighbour Algorithm used to calculate the function u .	77
Figure 4-1: The EV community may act as a controllable load or as a generation/storage Device.	80
Figure 4-2: Main modules and interfaces of the V2G Aggregation system.	84
Figure 4-3: Aggregation hierarchy.	84
Figure 4-4: Proposed credits mechanisms.	85
Figure 4-5: Electrical power available during day for 500 EVs of 15kWh of energy stored in batteries.	88
Figure 4-6: Main modules of the Collaborative Aggregator Broker system.	95
Figure 4-7: Wind effect and weather information.	96
Figure 4-8: Integration of microgeneration, EVs and ESSs in an electrical distribution network controlled by a broker.	99
Figure 4-9: Energy flux in an electrical distribution network with microgeneration, EVs and ESS.	101
Figure 5-1: Main Sustainable Mobility System objectives and sub-systems.	105
Figure 5-2: Semi-automatic creation of a XML file with road information to be used for graph creation.	106
Figure 5-3: Graph node weight calculation based on traffic information from web sites (traffic information in Portuguese language).	107
Figure 5-4: Application of the best path taking into account no traffic information (trip estimation time is around 12 minutes).	109
Figure 5-5: Application of the best path taking into account traffic information (trip estimation time is around 20 minutes).	109
Figure 5-6: Application of the best path taking into account a serious traffic problem in 25 de Abril Bridge.	109

Figure 5-7: Car Pooling system main modules.....	112
Figure 5-8: Use Case for car pooling driver profile.....	112
Figure 5-9: Use Case for car pooling passenger profile.....	113
Figure 5-10: Lisbon Metropolitan Area (LMA) traffic distribution from 2001 census.....	117
Figure 5-11: Lisbon Metropolitan Area (LMA) people movements from 2001 census.....	118
Figure 5-12: User match ride, with user preferences on a graph tool visualization, in a java prototype.....	119
Figure 5-13: Car Sharing parking places available in Lisbon, status July 2011.....	120
Figure 5-14: Use case for car sharing system.....	121
Figure 5-15: Main Bike Sharing system functionalities.....	122
Figure 5-16: Google Web Service Elevation.....	123
Figure 5-17: Example of a bike path with the elevation in meters (top of figure).....	124
Figure 5-18: Different sources of public transportation data integration approach.....	127
Figure 5-19: Platform D2RQ used at wrapper components [Bizer, 2009].....	127
Figure 5-20: Mobi Transportation best advice.....	128
Figure 5-21: Mobi-System transportation related system.....	129
Figure 5-22: Green Route application (application in Portuguese language).....	130
Figure 5-23: Administration application menu: weight configuration (in Portuguese language).....	131
Figure 5-24: Weights used on current example.....	131
Figure 5-25: Green Route application results with all transportation weights equal (application in Portuguese language).....	132
Figure 5-26: CO2 emissions route calculation (application in Portuguese language).....	133
Figure 6-1: Mobi-System main developed applications. In brackets are the Sections where the applications are described.....	135
Figure 6-2: V2G Smart System Mobile Application (in Portuguese language).....	138
Figure 6-3: V2G Smart System - menu for charging profile creation (in Portuguese language).....	138
Figure 6-4: Driver profile visualization (in Portuguese language).....	139
Figure 6-5: Small example of collective smart charging taking into account electrical distribution power limitation and user profile. At 3 am systems checks that user C needs more power, so V2G smart system limits user B charging.....	139
Figure 6-6: Main SiREV system platform layers.....	140
Figure 6-7: SiREV system architecture.....	141
Figure 6-8: Components Models of SiREV application.....	142
Figure 6-9: Screens of SiREV Application.....	143
Figure 6-10: Main modules of IRecommendit (Windows Mobile Application).....	146

Figure 6-11: SiREV- Charging indication (SoC); EV estimated autonomy	150
Figure 6-12: SiREV- Login menu with driver identification (in Portuguese language)	150
Figure 6-13: SiREV- Operation mode (in Portuguese language).	151
Figure 6-14: SiREV, destination identification, usually destinations are highlighted (in Portuguese language).	151
Figure 6-15: Showing recommendation, regarding charging points that fits drivers' choices (in Portuguese language)	153
Figure 6-16: Recommendation of charging places nearby (in Portuguese language).	154
Figure 6-17: Recommendation generated because SiREV detects that EV range is below 30% of initial range	155
Figure 6-18: Recommendation, because SiREV detects that range is below the configured limit of 30 km.	156
Figure 6-19: Recommendation for fast charging station.....	157
Figure 6-20: Main application screen and search for POI (Points of Interest).	158
Figure 6-21: Screen for POI (Points of Interest)	158
Figure 6-22: Visualization and classification of POI (Points of Interest).....	159
Figure 6-23: Get POI (Points of Interest) and get directions.	159
Figure 6-24: Availability and reservation of slots for charging stations.....	160
Figure 6-25: Reverse and submission forms on Mobi-System	160
Figure 6-26: Use case for SITP application	161
Figure 6-27: SITP - Web Client Application Menu	161
Figure 6-28: SITP - available menu for users	162
Figure 6-29: SITP - available menu for public transportation operators	162
Figure 6-30: Search result of a user query for a PT stop in a radius of 50m from his current position in Lisbon (Cais do Sodré)	163
Figure 6-31: Search result of a user price query for CP public transportation operator (description in Portuguese Language)	163
Figure 6-32: SITP mobile device interface	163
Figure 6-33: Menu for public transportation operator that introduces a stop on SITP system	164
Figure 7-1: Mobi-System related areas and the achieved research goals	166
Figure 7-2: Developed Functions and System for Mobi-System for EV related and electricity market related functions	167

INDEX OF TABLES

Table 2-1: Different pure EV and PHEV (data from different company's websites in November 2011).....	27
Table 2-2: Technical features of each charging level defined by EPRI	37
Table 2-3: Pilot tests performed with EV charging processes (June 2011 Status).....	38
Table 3-1: User Profile of an EV	50
Table 3-2: Information about distribution network, used for our case study	60
Table 3-3: Power consumption of conventional home equipment. Data taken from [ESRE, 2010]	64
Table 3-4: Questionnaire table to users about home energy consumption.....	65
Table 4-1: Annual Revenue of EV and PHEV in the Electricity Market [Tomić, 2007].....	92
Table 4-2: NB (Naïve Bayes) classifier approach for a small example	97
Table 6-1: Data used in the case study of Section 6.4	148

1. INTRODUCTION

With the electric mobility paradigm in smart grids environment [Wencong, 2012], mainly through the Electric Vehicles (EVs) and Plug-in Hybrid Electric Vehicles integration around the world [Hajimiragha, 2010], the open electricity market, the advances in the production and integration of renewable energy [Cochran, 2012] with the associated emission reductions [Saber, 2011], new research challenges are being opened. Thereby, it is necessary to establish a set of technologies to allow the integration of these areas [Gungor, 2011]. In [Gungor, 2010] are presented some opportunities and challenges to the wireless sensor area in smart grids scenario. In [Kennel, 2012] is proposed an energy management system for smart grids with EVs, and in [Moreno-Muñoz, 2013] is presented an embedding synchronized measurement technology for smart grids development. In this scenario, Information and Communication Technology (ICT) represents a fundamental area in the growth and performance of smart grids [Gungor, 2013]. ICT can also play an important role from the point of view of integration system information [Timbus, 2009], as well as from the point of view of the EV drivers, as shown in [Haghbin, 2013]. This upcoming reality will force to provide relevant information to the drivers, e.g., information related with electricity market, public transportation systems, EV performance, battery State-of-Charge (SoC), and drivers guidance. Moreover, considering the integration of EVs with bidirectional operation capabilities Grid-to-Vehicle (G2V) and Vehicle-to-Grid (V2G) [Tuttle, 2012], will strengthen the electricity market participation.

Nowadays, several projects related with smart grids are under development around the world [Sabin, 2012]. In this context, smart homes with energy management and efficient solutions, smart appliances, and smart meters [Benzi, 2011], will be the first steps to the smart grids evolution [Palensky, 2011]. However, the main principles of micro grids [Dasgupta, 2012], the guidelines of smart cities initiatives, the upcoming reality of energy markets, and the electric mobility integration, are also key areas of smart grids. Nevertheless, it is important to highlight that the combination of the information available in these systems represents a very complex scenario of data, which must be wisely coordinated.

In transportation systems a new reality is being introduced: the Electric Vehicle (EV), with several manufacturers investing in the production of this type of vehicle (e.g., Daimler AG, Toyota Motor Corp., General Motors Corp., Renault SA, Peugeot-Citroen, Volkswagen, Mitsubishi Corporation). EV sales from main automotive manufactures started in 2009 with IMiEV² and Nissan Leaf³ in 2010 and grow to 180000 in 2012 [IEA, 2013], as shown in Figure 1-1. Simultaneously, the share of renewable energy production is increasing. The combining of these two new scenarios is likely to be the first opportunity to harvest the synergies emerging from a co-evolution of vehicles and energy systems. Also for the Portuguese case this is an important opportunity, since we have a great energy dependency from the exterior, and in the last decade there was a great development on energy resources [Pinho, 2008]. This is illustrated in Figure 1-2, where is highlighted an important challenge for Portugal: the creation of a policy and system integration for Electric Vehicles based on new developments on Information Communication Technology (ICT).




Figure 1-1: EV sales and charging infrastructure available in 2012 from [IEA, 2013].

² Mitsubishi innovative Electric Vehicle is a five-door hatchback electric car produced by Mitsubishi Motors, and is the electric version of the Mitsubishi i. Market introduction was July 2009.

³ Nissan Leaf is a compact five-door hatchback electric car manufactured by Nissan and introduced in Japan and the United States in December 2010.



However...



The Challenge:

- In Portugal Road Transportation emissions contributes with 30%
- Congestions have an impact of 2% GDP
- Transportation energy consumption is 38% of all consumption

- Renewable represents around 43% of total electricity generation

-Technology allows explore new energy models

-Digital environments allow new thinking models for mobility

Figure 1-2: Main challenge to achieve between EVs and Renewable Energy Resources (Portuguese data from [Pinho, 2008]).

Environmental concerns on affordability of energy services and supply security have pushed Europe to develop and pursue policies to increase the share of renewable energy in the electricity generation mix, to promote energy efficiency, to consider the electrification of part of the vehicle fleet, and to move towards a smart electricity grid [COM, 2007]. This strategy positions Europe at the forefront in fighting climate change, in promoting a green economy and in creating green jobs. It is a cornerstone of the EU 2020 strategy for smart, sustainable and inclusive growth. And it is a vital part of the European Union (EU) 2020 flagship initiatives: a “Digital Agenda for Europe”, the “Innovation Union”, and a “Resource Efficient Europe”.

Currently, the transport sector is responsible for about a quarter of the EU carbon dioxide (CO₂) emissions. Car usage alone accounts for about 12% of all the EU CO₂ emissions, and road transport is responsible for 27% of energy consumption [Milkovits, 2010], [COM,

2007]. Even though modern transportation systems are becoming more fuel-efficient, they have not yet reached the level of efficiency that could substantially reduce the increasing share of the transportation sector in greenhouse gases (GHG) emissions and energy consumption.

The EU has launched a set of initiatives to address these issues. The most relevant in relation to this research topic are the:

- EU 20:20:20 Climate and Energy Initiative⁴;
- European Green Cars Initiative⁵;
- EU Transport White Paper [EU, 2011].

The first aims at reducing GHG emissions in 20% by 2020 relative to 1990, at improving energy efficiency in 20% by 2020, also relative to 1990, and at increasing the share of renewable energy to 20% by 2020 [COM, 2007]. The second supports R&D on technologies and infrastructures that are essential for promoting the use of renewable and non-polluting energy sources, and it has a clear focus on the electrification of road transport. And the third recommends an ambitious target of 60% reduction of GHG emissions from transport by 2050, relative to 1990.

Portugal and Spain intend to create the first “green car” in Iberia, hoping to generate 150 million euro worth of investment and 800 new jobs in the region's struggling automotive industry. The “Mobi-Green Car”, as the vehicle is named, is being developed by two automotive research centres in Portugal and Spain, using funds from both the public and private sectors [Almeida, 2008].

Under directive 2009/28/EC of the European Parliament and the Council [EC, 2009], Portugal has committed itself to a target of 31% of gross final energy consumption coming from renewable sources by 2020. In its National Energy Strategy 2020 [ENE, 2009],

⁴ Information available at <ec.europa.eu/clima/policies/package>.

⁵ Information available at <www.green-cars-initiative.eu>.

Portugal also sets the objectives of having 60% of electricity production and 10% of energy consumption in transport coming from renewable energy sources by 2020.

The Portuguese Electric Mobility Initiative started in early 2008 with the creation of the MOBI.E Program⁶. This ambitious Program is based on cooperation among the different stakeholders. It aims at setting a nationwide integrated network with the focus on users and opened to every vehicle manufacturer, energy retailer and private operator. The full interoperability of services and electricity provision is ensured by a settlement system that is entrusted to a management entity, responsible for all the energy and financial flows from electric mobility network operations. With MOBI.E, any user is able to charge the batteries of the EV at any charging point of the network, regardless his or her mobility electric subscription with any retailer of electricity. The system results in transparency, low entry barriers, and competition along the value chain, and the supporting business model takes into consideration the “type” of the energy used to produce electricity, generating stimuli for the use of greener energy. This Program completed its first phase in June 2011, with the installation of 1300 public normal charging points and 50 fast charging points in primary roads and highways, connecting 25 of the largest Portuguese municipalities⁷. Currently, there are over 300 electric cars on the road throughout the country, and the number is projected to rise to 200000 by 2020, in view of wide user adoption fostered by strong commitment and investments provided by the government; the public charging infrastructure may count 25000 charging points by that time [Mobieuropa, 2011].

1.1. Context

The research work of this Thesis is conceived to the creation of a system for mobility process oriented to the user (driver), taking into account new future realities, such as the EV integration with smart cities, resulting in a timely information system to assist driver with relevant information in order to address the following issues: EV charging, electricity market participation and sustainable mobility functions.

⁶ Information available at <<http://www.mobie.pt/>>.

⁷ Information available at <<http://www.mobie.pt/>>.

At the start of this research, an indication of success for this approach was the navigation systems applied on transportation systems. This situation is pointed out in Figure 1-2, where is highlighted the main problems on transportation systems, e.g., increased demand of vehicles and the limited resources on fossil fuels with increasing prices (in Europe average fuel price is around 1.5 €/liter⁸, which means around 0.12 €/km, and taking an average daily trip of 60 km, we have around 200 €/month for fuel expenses). Also CO₂ emissions are an important issue from the transportation activity. On the other hand, in computer science the success of the utilization of mobile applications, integrated in social networks and geographic information systems, represents a huge potential for applications on these areas of transportation and electricity.




Figure 1-3: Current situation (on the start of this research project in 2008).

From this reality, Figure 1-3 shows a new scenario that is emerging in 2008, with the EV introduction, the open electricity market and the advances in renewable energy production

⁸ Prices of December 2011.

and integration, new research challenges are being opened, where ICT (e.g., mobile devices with available GPS capacity, and usage proliferation with decreasing prices on mobile communications) and information systems can play an important role from the system information integration point of view, as well as from the point of view of driver, as shown in Figure 1-3.

This upcoming reality (suggested in Figure 1-4) will create needs for driver's relevant information (e.g., information related with transportation systems, EV charging status, electricity market and driver's guidance). This research has the goal to define a model and a prototype system to give drivers real time relevant information to promote the reduction of private energy consumption and costs, to promote EV integration and acceptance by reducing the anxiety range problem [Schott, 2009], to assist the renewable energy integration by V2G (Vehicle-to-Grid) and G2V (Grid-to Vehicle) approaches and the consequent electricity market participation. These related concepts are further discussed in the next subsection.




Figure 1-4: Future tendencies for current research area work.

Figure 1-5 suggests the research context of this work, involving three new emerging paradigms: smart cities, electricity new challenges and the EV integration. This research project is located on the intersections of these emergent tendencies, where ICT, with mobile communications and information systems play an important role to support the integration and real time information access. These upcoming realities raise drivers' information needs similar to current internet users' information needs, due to information overload. Based on the author background and the potential of application of these emergent realities, the current research is oriented towards the definition of information system architecture to support the information integration on a mobile device that can feed the need of drivers' relevant real time information.




Figure 1-5: Main research goal and related areas.

1.2. Research Problems and Goals

Taking the main principles and guidelines of smart cities initiatives and the upcoming reality of energy markets and EV integration, this information gives us a complex scenario where this research intends to contribute with a model to data integration among EV data, charging data, electricity market participation and the cooperation with existing transportation infrastructures. This cooperation can be achieved if it is possible to provide information regarding routes, schedules and pricing of public transportation, information about availability of parking places, or even bike and car sharing systems.

Also the minimization of the driver range anxiety problem is an interesting research work with the follow necessities: (1) an accurate EV range prediction based on past driver behavior and external parameters, like road traffic and weather; (2) representation on a map of the distance possible to reach, associated with an uncertainty associated with driver behavior; and (3) guidance and reservation of charging slots on Public Charging Station (PCS).

Taking into account the current development and proliferation of mobile devices, associated with the increasing communication connectivity in mobile communication (higher speed rates and coverage), the proposed system should run in a mobile device.

1.2.1. Research Problems

From the referred areas overview the author identifies several problems related with the integration of EV and the cooperation with public transportation infrastructures. The main problems related with the EV integration are: guidance and reservation of charging slots in public charging stations; the smart charging needed to be performed at home charging devices to overcome electrical distribution power limitations; the support to drivers towards the range anxiety problem; the electricity market participation to increase drivers profits, and consequently increase the EV attractiveness; and even the support to the integration of local renewable resources (microgeneration) by storing the excess of energy production. Cooperation among transportation infrastructure can be achieved by public transportation data integration, access to car and bike sharing system, or even by carpooling. Real time traffic information together with all these transportation options could incentive drivers to use vehicles where public transportation is poor or do not meet their needs, using public

transportation only when their requirements are fulfilled. Also this can be achieved, or at least partially, with all the information described in Figure 1-6, available in a mobile device.




Figure 1-6: Purpose of current research work: mobile information system design, with focus in the driver's information needs adapted to the new reality of EV introduction and cooperation with transportation infrastructures.

1.2.2. Research Goals

Considering the scope and the problems identified above, the research goal is the design of a system to give drivers relevant information in real time, taking into account emergent future realities, such as the EV integration, smart cities, cooperation among transportation infrastructures, services integration, and participation in the electrical energy market. **The main challenge addressed in this research is the definition and discussion of a model for that system and the development of a prototype** in order to address the following issues:

- The problem of EV charging at public places (route guidance based on current vehicle position and reservation of time at charging slots) and at home, with the transactions account, and considering smart charging to deal with possible electrical grid power limitation on electricity distribution due to simultaneous charging processes;
- Mitigate the drivers range anxiety problem;
- Integrate EV in electricity market participation through the V2G and G2V modules and the creation of EV communities based on a collaborative approach. These communities can constitute market players, taking into account that several EVs constitute a large capacity storage device;
- Smart integration of local microgeneration resources, taking locally the excess of energy produced by microgeneration;
- Support driver's mobility in smart cities, providing integrated information related to transportation systems and other systems, such as carpooling, car and bike sharing systems.

The objective of this work is to define a model for an integrated information system, which can make possible to accomplish the following Research Goals (RG):

- RG-1: Mitigate the EV charging problem;
- RG-2: Minimize the driver range anxiety;
- RG-3: Create and manage EV communities for electricity market participation and microgeneration integration;
- RG-4: Integrate the EV in cooperative transport infrastructures, with different operators transportation data integration, and interaction with carpooling, car sharing and bike sharing systems;
- RG-5: Provide route guidance, taking into account traffic information, transportation available data, or even public charging station locations.

Due to the diversity of topics involved in this research work, this thesis is organized under four topics (see Figure 1-7), each one described in a separated Chapter, namely:

- **EV related functions** (see Chapter 3), where it is proposed a process to extract relevant information for charging process, to deal with the present distribution power limitations, without a Smart Grid infrastructure, and to help the driver to overcome the range anxiety problem by range prediction, representation features and guidance to the nearest public charging station;
- **Electricity market related functions** (see Chapter 4), where it is proposed the creation of EV communities for electricity market participation, with the integration of local renewable energy resources;
- **Sustainability Mobility functions** (see Chapter 5), where a diversity of data integration is proposed, and a diversity of environment friendly systems are suggested (carpooling, car sharing and bike sharing), towards possible advices for the best path, taking into account the travel time. In spite of the lack of real world testing scenarios, this integrated view with traffic information is a new approach that can help in a near future the reduction of vehicles in the city, without great penalty for drivers;
- **Mobi-System** (see Chapter 6), set of prototypes created for user interaction with previous functions. This system is based on a web application called V2G Smart System (see Section 6.1), on a mobile application developed for Android operating system designated by SiREV (see Section 6.2), and on an application called IRecommendit developed for Windows Mobile operating systems (see Section 6.3) and SITP application for public transportation interaction (see Section 6.5).




Figure 1-7: Mobi-System Chapter organization.

1.3. Research Methodology

The research developed in this thesis addresses the questions enumerated in Section 1.2.2, following the Action Research Method [Lewin, 1946], considering the set of problems identified in Section 1.2.1.

The issues raised shall be approached from an engineering perspective, using available technology to build a prototype that allows the development and validation of models. The research makes use of the following techniques: state of the art analysis, identification of

the relevant features in the research context, and a prototype construction, providing means for model development based on a domain specific language.

To validate the research's results a set of case-studies were used, during a first phase reproducing reference models described in scientific literature, and on a second phase addressing “real-life” problems with scientific relevance on their own. The results of this research have been submitted in peer reviewed international conferences and book chapters seeking validation from the scientific community.

1.4. Main Contributions

The result of this research work has already produced the following technical Papers:

Books Chapters

- BC1. João Ferreira. Green Route Planner. Nonlinear Maps and their Applications, Selected Contributions from the NOMA 2011 International Workshop. Series: Springer Proceedings in Mathematics & Statistics, Vol. 71. Grácio, C.; Fournier-Prunaret, D.; Ueta, T.; Nishio, Y. (Eds.), ISBN 978-1-4614-9160-6, December 2013.
- BC2. Vítor Monteiro, João C. Ferreira, Andrés Meléndez, João L. Afonso, Electric Vehicles On-Board Battery Charger for the Future Smart Grids, L.M. Camarinha-Matos, S. Tomić, and P. Graça (Eds.): DoCEIS 2013, IFIP AICT 394, pp. 351–358, 2013.
- BC3. João Carlos Ferreira, Alberto Rodrigues da Silva, Vítor Monteiro and João L. Afonso. Collaborative Broker for Distributed Energy Resources. in Computational Intelligence and Decision Making - Trends and Applications, ISBN 978-94-007-4722-7, Springer, 2013.
- BC4. Vítor Monteiro, Henrique Gonçalves, João C. Ferreira, João L. Afonso. “Batteries Charging Systems for Electric and Plug-In Hybrid Electric Vehicles,” in Automotive Engineering, João Paulo Carmo, InTech. 2012. ISBN 979-953-307-838-9.
- BC5. João C. Ferreira, Paulo Trigo, Alberto Silva, Helder Coelho, João L. Afonso. Simulation of Electrical Distributed Energy Resources for Electrical Vehicles Charging Process Strategy, IEEE computer magazine dedicated to the Second Brazilian Workshop on Social Simulation (BWSS 2010), 24-25 Oct. 2010, São Bernardo do

Campo, São Paulo, Brazil, pp. 82-89, IEEEExplore Digital Object Identifier: 10.1109/BWSS.2010.15, ISBN: 978-1-4577-0895-4.

BC6. João C. Ferreira, Alberto Silva and João L. Afonso. Ferreira. EV-Cockpit – Mobile Personal Travel Assistance for Electric Vehicles. *Microsystems for Automotive Applications 2011. Smart Systems for Electric, Safe and Networked Mobility*. Springer, 2011, ISBN 978-3-642-21380-9.

BC7. João C. Ferreira, João L. Afonso, “Electric Vehicle Communities for Electric Market”, *World Electric Vehicle Journal*, 2010 WEVA, Vol. 4, pp. 683-692, ISSN 2032-6653.

Proceedings of Internationals Conferences

IC1. João C. Ferreira, Porfírio Filipe, Paulo Martins. Cooperative Transportation Infrastructure in proceedings of the International Conference on IT and Intelligent Systems (ICITIS'2013), 28 - 29 August, Malaysia.

IC2. Joao Ferreira; Vítor Monteiro; Joao Afonso. Moby.Cockpit Project for EV Seamless Integration in the Cooperative Transport Infrastructure in proceedings of the International Conference on IT and Intelligent Systems (ICITIS'2013), 28 - 29 August, Malaysia.

IC3. Joao Ferreira; Rui Santos; Vítor Monteiro; Joao Afonso. Broker Colaborativo Na Cloud in proceedings of the 8th Iberian Conference on Information Systems and Technologies (CISTI2013), 19-22 June 2013, Lisbon.

IC4. José Almeida; João Ferreira. BUS Public Transportation System Fuel Efficiency Patterns in proceedings of the 2nd International Conference on Machine Learning and Computer Science (IMLCS'2013) 24-25 August, Malaysia.

IC5. João Carlos Ferreira, Vítor Monteiro and João L. Afonso. Dynamic Range Prediction for an Electric Vehicle in proceedings of the 27th Electric Vehicle Symposium (EVS27)⁹, 17-20 November 2013 in Barcelona.

⁹ Conference Web page <<http://www.evs27.org/pt/home>>.

- IC6. João C. Ferreira, Porfírio Filipe, Paulo Martins. Integra System, in proceedings of WEBIST 2013 – 9th International Conference on Web Information Systems and Technologies, 8-10 May, Aachen-Germany.
- IC7. Vítor Monteiro, J. G. Pinto, Bruno Exposto, João C. Ferreira, João L. Afonso. Assessment of a Battery Charger for Electric Vehicles with Reactive Power Control in proceedings of IECON 2012, the 38th Annual Conference of the IEEE Industrial Electronics Society in Montreal Canada from 25 to 28 October 2012.
- IC8. João C. Ferreira, Vítor Monteiro, João L. Afonso. Real Time Information Extraction of an Electric Vehicle, in proceedings of the Annual Seminar on Automation, Industrial Electronics and Instrumentation (SAAEI'12), in its nineteenth edition, will be held at the Escola de Engenharia of the Universidade do Minho, in Guimarães, Portugal, 11-13 July 2012.
- IC9. João C. Ferreira, Vítor Monteiro, João L. Afonso. Cooperative Transportation System for Electric Vehicles, in proceedings of the Annual Seminar on Automation, Industrial Electronics and Instrumentation (SAAEI'12), in its nineteenth edition, Escola de Engenharia of the Universidade do Minho, in Guimarães, Portugal, 11-13 July 2012.
- IC10. Vítor Monteiro, J. G. Pinto, João C. Ferreira, Henrique Gonçalves, João L. Afonso. Bidirectional Multilevel Converter for Electric Vehicles, in proceedings of the Annual Seminar on Automation, Industrial Electronics and Instrumentation (SAAEI'12), in its nineteenth edition, Escola de Engenharia of the Universidade do Minho, in Guimarães, Portugal, 11-13 July 2012.
- IC11. Vítor Monteiro, João C. Ferreira, J. G. Pinto, Bruno Exposto, Delfim Pedrosa, João L. Afonso. Comparison of Charging Systems for Electric Vehicles and Their Impact on Electrical Grid, in proceedings of the Annual Seminar on Automation, Industrial Electronics and Instrumentation (SAAEI'12), in its nineteenth edition, Escola de Engenharia of the Universidade do Minho, in Guimarães, Portugal, 11-13 July 2012.
- IC12. Vítor Monteiro, Delfim Pedrosa, Bruno Exposto, João C. Ferreira, João L. Afonso. Smart Charging System of the Electric vehicle CEPIUM, in proceedings of the Annual Seminar on Automation, Industrial Electronics and Instrumentation (SAAEI'12), in its nineteenth edition, Escola de Engenharia of the Universidade do Minho, in Guimarães, Portugal, 11-13 July 2012.

- IC13. João C. Ferreira, Vítor Monteiro, João L. Afonso, Electric Vehicle Route Recommender System, 1st International Conference on Smart Greens, Porto-Portugal, April 2012.
- IC14. Vítor Monteiro, João C. Ferreira, , João L. Afonso, Smart Battery Charger for Electric Mobility in Smart Grids, 1st International Conference on Smart Greens, Porto-Portugal, April 2012.
- IC15. Joao C. Ferreira, Vitor Monteiro and João Afonso Data Mining Approach for Range Prediction of Electric Vehicle. Conference on Future Automotive Technology Focus Electromobility, from March 26-27, 2012, Garching – Germany.
- IC16. Joao C. Ferreira, Vitor Monteiro and João Afonso. Mobile Geographic Range Prediction for Electric Vehicles in proceedings of the First Conference in Electronics, Telecommunications, and Computer Engineering (ISBN: 978-989-97531-0-5), 24th to 25th November, 2011, at Instituto Superior de Engenharia de Lisboa – ISEL, Lisbon- Portugal.
- IC17. Joao C. Ferreira. MultiModal Best Path in proceedings of the First Conference in Electronics, Telecommunications, and Computer Engineering (ISBN: 978-989-97531-0-5), 24th to the 25th November, 2011, at Instituto Superior de Engenharia de Lisboa – ISEL, Lisbon- Portugal.
- IC18. Joao C Ferreira, Vitor Monteiro, Alberto Silva and Joao Luiz Afonso. Collaborative Broker for Distributed Energy Resources in proceedings of the International Symposium on Computational Intelligence for Engineering Systems (ISCIES 2011), from 16 to 18 November 2011, Coimbra, Portugal.
- IC19. João C. Ferreira, Alberto Silva, Vítor Monteiro, João L. Afonso. Smart Electric Vehicle Charging System in proceedings of IEEE Intelligent Vehicles Symposium (IV 2011), June 5-9, 2011, in Baden-Baden, Germany.
- IC20. João C. Ferreira, P. Filipe, Alberto Silva. Multi-Modal Transportation Advisor System in proceedings of the First IEEE FISTS Forum on June 29 - July 1, 2011 in Vienna Austria.
- IC21. João C. Ferreira and João L. Afonso. Mobi-System: A Personal Travel Assistance for Electrical Vehicles in Smart Cities in proceedings of the 20th IEEE International

Symposium on Industrial Electronics (ISIES 2011), 27-30 June 2011, Gdansk University of Technology, Poland.

IC22. João C. Ferreira, Alberto Silva and João L. Afonso. Agent based approaches for Smart charging strategy for Electric Vehicle in proceedings of the EVTEC 11 (1st International Electric Vehicle Technology Conference), 17-19 May 2011, in Yokohama, Japan.

IC23. João C. Ferreira, João L. Afonso, Towards a Collective Knowledge for a Smart Electric Vehicle Charging Strategy in proceedings of the International Conference on Industrial and Intelligent Information (ICIII 2011) de 1 Abril a 3 de Abril de 2011 na ilha do Bali.

IC24. João C. Ferreira, Pedro Pereira, Porfírio Filipe; João Afonso. Recommender System for Drivers of Electric Vehicles in proceedings of the IEEE 3rd International Conference on Electronics Computer Technology (ICECT 2011), 8-10 April 2011, Kanyakumari, India, pp. 244-248, IEEEXplore Digital Object Identifier: 10.1109/ICECTECH.2011.5941995, ISBN: 978-1-4244-8678-6.

IC25. Vítor Monteiro, João C. Ferreira, Gabriel Pinto, Delfim Pedrosa, João L. Afonso, iV2G Charging Platform, in proceedings of the IEEE-ITSC, 13th International IEEE Conference on Intelligent Transportation Systems, 19-22 September 2010, Madeira, Portugal. IEEE Catalog Number: CFP10ITS-CDR, ISBN: 978-1-4244-7658-9, ISSN: 2153-0009, Pag 337.

IC26. João C. Ferreira, João L. Afonso. A Conceptual V2G Aggregation Platform in proceedings of the EVS-25 -The 25th World Battery, Hybrid and Fuel Cell Electric Vehicle Symposium & Exhibition, 5-9 Nov. 2010, Shenzhen, China.

IC27. Joao C. Ferreira, Vitor Monteiro and João Afonso. Mobile Geographic Range Prediction for Electric Vehicles. Proceedings of the 1st Conference in Electronics, Telecommunications, and Computer Engineering, from 24th to the 25th November, 2011, at Instituto Superior de Engenharia de Lisboa – ISEL, Lisbon- Portugal.

The author supervised the following academic projects in the context of this research work:

1. “Análise de eficiência energética em frota de transportes”, José de Almeida, nº 14937, MSc dissertation, ADEETC-ISEL, 2013.

2. “Determinação Dinâmica da Autonomia de um Veículo Eléctrico”, Rui Filipe Frias do Nascimento, nº 25657, MSc dissertation, ADEETC-ISEL, 2012.
3. “Broker colaborativo: Gestão de recursos energéticos distribuídos”, Rui Daniel Batista Santos, MSc dissertation, ADEETC-ISEL, 2012.
4. “Visualização de dados geográficos em dispositivos móveis”, Paulo Sousa, MSc dissertation, ADEETC-ISEL, 2009.
5. “Sistema de Recomendação para Condutores de Veículos Eléctricos”, Pedro Romão Pereira, MSc dissertation, ADEETC-ISEL, 2010.
6. “Determinação do melhor caminho em sistemas de transporte terrestre (BPath – Best Path)”. Tiago Fernandes and Miguel Fontes, Final Year Project, ADEETC-ISEL, 2009.
7. “Vehicle-2-Grid, Sistema de Carregamento Controlado à Distância”. Xênia Beatriz Henning and Andreia Sofia Reis Mouta, Final Year Project, ADEETC-ISEL, 2010.
8. “MyTracking: Sistema de Tracking de Movimentos de Condutores de Veículos em modo off-line”. João António Gomes de Sousa and Pedro Nuno Pereira dos Santos, Final Year Project, ADEETC-ISEL, 2010.
9. “V2G - Modelo de Simulação”. Ana Rita Gonçalves Ramada, Final Year Project, ADEETC-ISEL, 2010.
10. “V2G SMART SYSTEM: Sistema inteligente para gestão de carregamentos de veículos eléctricos”. Cláudio Russo and Nuno Bento, Final Year Project, ADEETC-ISEL, 2100.
11. “IRecommendIt: Sistema de recomendação para veículos eléctricos”. Luís Filipe Valente Borges and Miguel Ângelo Valente Borges, Final Year Project, ADEETC-ISEL, 2010.
12. “Forget about Traffic - Sistema cooperativo para gestão de incidência de tráfego”. Fernando Vaz and Vítor Viana, Final Year Project, ADEETC-ISEL, 2011.
13. “CarSharing”. Alberto Xavier and Nuno Lourenço, Final Year Project, ADEETC-ISEL, 2011.
14. “Green Route-Assistente ‘verde’ em viagens na cidade”. Miguel Marques and Raul Jesus, Final Year Project, ADEETC-ISEL, 2011.

15. “Assistente pessoal de viagem”. Daniel Costa, MSc dissertation, ADEETC-ISEL, 2011.

1.5. Outline of the Thesis

This thesis is divided in 7 Chapters: (1) Chapter 1 presents the introduction, motivation, scope, and main goals of this thesis; (2) Chapter 2 describes the literature review related to the topics of mobility processes in smart cities, EV and electricity market; (3) Chapter 3 presents the proposal towards the EV function modules and shared modules of tracking system, home consumption simulator and weather module; (4) Chapter 4 presents the Electricity Market functions, taking into account EV market participation, and the integration of local renewable energy resources; (5) Chapter 5 describes the sustainable mobility functions, with the proposal of carpooling, car sharing and bike sharing systems, and a system for public transportation data integration in the European space. A supporting decision system informs the user about the best path and public transportation, taking into account traffic information; (6) Chapter 6 describes the driver’s mobile application for portable devices, like PDA or mobile phones, and also a web application. Also some used cases of applications are showed; and (7) Finally, Chapter 7 summarizes the main conclusions of the work, and presents future work aspects to be considered.

2. LITERATURE REVIEW

Due to the diversity of Electrical Vehicle (EV) topics, the present literature review focuses on: (1) Smart Cities; (2) Vehicle; (3) The energy market with the study of electricity distribution network; (4) Electromobility, where is studied the EV charging process, and related process; (5) Projects related with Mobi-system; and (6) The identification of main related European scenarios.

Also Telematics using ICT (Information and Communications Technology) became a hot research topic since the automobile manufactures started working in this direction. The application of telematics typically integrates the usage of telecommunications and informatics to exchange information with external applications by receiving and storing information via telecommunication. Also the integration of GPS navigation, hands-free cell phones, wireless safety communications and automatic driving assistance systems are important investigation topics. In EVs the driver information needs are higher than in conventional vehicles, due to the limited range autonomy of EVs. Also, the charging stations for EVs are not heavily disseminated anywhere, like occurs with conventional petrol stations.

All these topics are considered as being of high urgency, and thus, they have to be considered at the earliest possible instance.

2.1. Smart Cities

The “Smart Cities” concept is a paradigm that has been quite fashionable in the policy arena in recent years. Its main focus seems to be on the role of ICT infrastructure, although much research has also been carried out on the role of human capital/education, social and relational capital, and environmental interest, as important drivers of urban growth [Caragliu, 2009].

Smart Cities concept is based on the application of ICT to the several city processes, like transportation and energy management, where is important to highlight the information integration towards the users’ needs. This approach benefits from recent developments on mobile communication and devices.

The European Union has performed efforts in the development of a plan for an urban growth in a 'smart' sense for its metropolitan areas. The "Smart Cities Initiative" was born under the SET-Plan¹⁰ (Strategic Energy Technology Plan) of the European Commission, with the mission of encouraging cities and regions to adopt approaches that could reduce the CO₂ emissions by a percentage around 40%. Part of these measures deals with the reduction of emissions of greenhouse gases, through less combustion engines in the cities, achieved with the use of more EVs or public transportation. For this work, the main input from the Smart Cities Initiative is the support for the usage of information systems sustained by ICT infrastructures, which support data integration among different players, and promotes a collective knowledge maintained by the usage of cooperative systems and social networks.

Also, smart cities initiate deals with the upcoming reality of decentralized power generation in buildings, which can change from energy consumers to energy producers. Thus, it is important the intelligent management of energy systems and transportation systems, where information and communication systems play an important role.

The smart cities concept implementation requires a considerable effort in team building, in order to bring together diverse actors - like the energy, transportation and ICT - in both the public and private sectors.

Several European projects under FP7 calls were performed. A detailed information can be found at European FP7 web site. Also this topic is considered an important research subject in the next H2020 program, with a European investment around €200m¹¹.

2.2. Vehicles

As suggested in Figure 2-1, there are different types of vehicles that depend on different types of energy power supply. The main types of vehicles are the following:

1. Internal Combustion Engines (ICE) are the conventional vehicles which have been associated with the problem of high emissions of CO₂. The ICE still dominates the

¹⁰ <<http://setis.ec.europa.eu/implementation/technology-roadmap/european-initiative-on-smart-cities>>.

¹¹ See information at European web Site <http://europa.eu/rapid/press-release_MEMO-13-884_en.htm>.

automobile market, but due to the continuous increase of fossil fuels prices and their limited resources, alternatives start to be considered. The ICE has low energy efficiency (around 20 %);

2. Hybrid electric vehicles. These types of vehicles were first introduced in 1997 in Japan with the introduction of Toyota Prius [Toyota, 2007]. The main specification of this type of vehicle is the operation of the ICE on its efficient interval by means of a regenerative braking system;
3. Latest generation of the vehicle the PHEV (Plug-in Hybrid Electric Vehicles) with additional capability to be charged from the grid. This vehicle can use fossil fuel and electric;
4. Electrical Vehicle (EV), only operates in the electric mode based electric motors or traction motors for propulsion. This EV is described in the next sections and is the subject of study of current work;
5. Fuel Cell Electric Vehicles (FCEV), is a type of hydrogen vehicle which uses a fuel cell to produce electricity, powering its on-board electric motor. Fuel cells in vehicles create electricity to power an electric motor using hydrogen (produced in one of several ways) and oxygen from the air.




Figure 2-1: Main vehicles types.

2.2.1. Why Electrical Vehicles?

ICE vehicles in big cities are also the major contributors of air pollution. Reducing emissions production is a big challenge for the world (both for developed and developing countries) and several initiatives are being taken into account to solve this problem. On the other hand, another major challenge in today's world is the high consumption of fossil

fuels, with increasing prices and diminishing number of resources. ICE vehicles are one of the major agents of fossil fuels consumption.

Global greenhouse gases emissions from different sectors are shown graphically in Figure 2-2. Transportation sector is the third factor of pollution after power stations and industries. The introduction of EV can be even more interesting when there are no emissions from power stations, in the case electricity is generated from renewable resources. The high intermittency of the electricity from renewable resources can be synchronized with the intermittency of consumption of electric cars, providing stability and avoiding load flow problems in the power systems.




Figure 2-2: Global Green house gasses emissions [Rosmarino, 2009].

In Figure 2-3 it is compared the CO₂ emissions for different vehicle types, taking into account that electricity is produced based on 20% of renewable sources. *In the 1990s the European Automobile Manufacturers Association entered into a voluntary agreement with the European Commission to reduce CO₂ emissions per kilometer. The target was 140 g CO₂/km by 2008, down from an average of 187 g CO₂/km in 1995. By 2005, it was apparent that the target was not going to be reached (World Resources Institute, 2005). In response the European Commission has, after much push-back from European automakers, extended the time of compliance to 2012, but reduced the target to 130 g CO₂/km [Barkenbus, 2010].*




Figure 2-3: Greenhouse emissions¹² emissions for different types of small vehicles¹³ [Argone, 2009]¹⁴.

2.2.2. EV Market Introduction

In the last years, major automobile companies started the development of EVs, and the products started to arrive at the market in 2009¹⁵. The main problem in this market introduction is the excessive price of EVs due to battery costs (approximately, the battery pack is half the price of the car). In spite of considerable saving on price per kilometer, the initial investment and the limited life time of the battery system is a major problem for EVs acceptance. To overcome this problem some companies sell EVs in a leasing model plan, or even sell the vehicle without the batteries and then go through a leasing plan for the battery pack. The limited range autonomy and the time necessary for the battery charging process are other problems associated to the EVs. The announcement of the Nissan Leaf in 2010¹⁶, with range autonomy of 160 km, was a major breakthrough of the year.

¹² Greenhouse gases are gases in the atmosphere that absorb and emit radiation within the thermal infrared range.

¹³ MRET 20% is the mandatory renewable energy target. Increase renewable power will reduce CO₂ emissions associated with energy production.

¹⁴ A complete report produced by the Researchers at Argonne National Laboratory [Argone, 2009].

¹⁵ Mitsubishi i, was introduction to the market in July 2009.

¹⁶ Nissan Leaf was introduced to the market in the end 2010.

Table 2-1 shows the most relevant characteristics of different PHEVs and EVs:

Table 2-1: Different pure EV and PHEV (data from different company's websites in November 2011).

Vehicle Type	Battery Capacity (kWh)	Electric Range (km)	Full Charging Time (hour)	Battery Type
 Toyota Prius	10	48	8	<i>Lithium-ion</i>
 Nissan Leaf	24	160	8	<i>Lithium-ion</i>
 Chevrolet Volt	16	64	10	<i>Lithium-ion</i>
 Mitsubishi iMiev	16	160	7 - 14	<i>Lithium-ion</i>
 Volvo C30	24	150	8	<i>Lithium-ion</i>

Battery Manufactures are mainly in China, BYD Auto¹⁷ is a Chinese company which basically produces 65% of the world's nickel cadmium batteries and 30% of the world's lithium-ion mobile phone batteries, and that has also focused on PHEV and EV manufacturing [Kassatly, 2010].

2.3. Electricity Market

The electricity industry faces new challenges, namely related to electricity renewable market, microgeneration and the deregulated electricity market.

¹⁷ <www.byd.com.cn>

Energy Renewable Market is the energy produced and sold based on energy sources, like wind, solar photovoltaic and waves. These resources have two main problems: (1) initial high investments and (2) the intermittent behavior, which can cause problems in the distribution process due to excess or insufficient production. Wind production power has experienced the fastest growth in renewable electricity source over the past 17 years (1995-2011) in Europe and accounted for about 15,6% of the total European electricity demand in 2007 [EWEA, 2012]. In 2012, installed wind power capacity in the European Union is around 7% of the EU's electricity production [EWEA, 2013].

Microgeneration is the small-scale generation of electricity by individuals, small businesses and communities to meet their own needs, as alternatives or supplements to traditional centralized grid-connected power, and this is a new important growing market [Jones, 2010]. It is expected a fast growing in microgeneration, and by 2025 it is projected 20% of energy produced from these resources [Jones, 2010]. A significant synergy is expected between microgeneration and EVs (see Section 4.2 and also a proposal for this subject in section 4.3), with the possibility of microgeneration production excess to be stored locally by EVs. A system and a business model are needed to control these transactions.

Deregulated Electricity Market is based on an open market, where we can have several suppliers of electricity, in opposition to the monopoly. In contrast to the experience in transportation and telecommunications industries, electricity deregulation has experienced many difficulties, due to the complexity of the electricity market [ERSE, 2009]. At the same time of this liberalization process a new reality arrives with the EV introduction and with renewables and microgeneration integration. EU directive created a single integrated European electricity market in 2007. Main output from this fact in the research context is that EV can play a role of producer, if conveniently aggregated in communities, creating a 'large storage device' (see Chapter 4, for further analysis). Figure 2-4 illustrates EV usage driving profile and its implication on EV battery charging, and also a typical consumption curve for Low Voltage (LV) power in Portugal, where in the late night period, when home energy consumption is low, EV battery charging process can occur, and when demand is high (e.g., around 12 and 21 o'clock) energy stored in EV can be sold back to the electrical grid.




Figure 2-4: EV battery charging and Low Voltage (LV) typical consumption in a day [ERSE, 2009].

Figure 2-5 shows current electricity market reality where distribution network remains regulated.




Figure 2-5: Current reality of electricity market, from [EPRI, 2010].

This paradigm has changed to an open market where market forces drive the price of electricity and reduce the net cost through increased competition. This electricity market has a centralized mechanism that facilitates electrical energy trading between buyers and

sellers. The electricity market's prices are reliable prices indicators, not only for market participants but for other financial markets and consumers of electricity as well. The main stakeholders, adapted from [Shahidehpour, 2002] are:

1. **ISO (Independent System Operator)** - The ISO is the leading entity in an electricity market and its functions determine market rules;
2. **GENCOs (GENERating COmpanies)** - This concept represents the energy producers. A GENCO operates and maintains existing generating plants;
3. **TRANSCOs (TRANSmition COmpanies)** are responsible for the distribution networks. The transmission network system is the most crucial element in electricity markets. TRANSCOs are regulated to provide non-discriminatory connections and comparable service for cost recovery;
4. **DISCOs (DIStribution COmpanies)** - A DISCO distributes the electricity, through its facilities, to customers in a certain geographical region. A DISCO is a regulated (by state regulatory agencies) electric utility that constructs and maintains distribution wires connecting the transmission grid to end-use customers;
5. **RETAILCOs (RETAIL COmpanies)** - A RETAILCO is a newly created entity in this competitive industry. It obtains legal approval to sell retail electricity. A RETAILCO takes title to the available electric power and re-sells it in the retail customer market. A retailer may deal indirectly with end-use customers through Aggregators;
6. **Aggregators** - An Aggregator is an entity or a firm that combines customers into a buying group. The group buys large blocks of electricity and other services at cheaper prices. The Aggregator may act as an agent (broker) between customers and retailers. When an Aggregator purchases electricity and re-sells it to customers, it acts as a retailer and should initially qualify as a retailer. This concept and the broker are used on chapter 4;
7. **Brokers** - A broker of electrical energy services is an entity or firm that acts as a middleman in a marketplace in which those services are priced, purchased, and traded. A broker does not take title on available transactions, and does not generate, purchase, or sell electrical energy but facilitates transactions between buyers and sellers;

8. **Marketers** - A marketer is an entity or a firm that buys and re-sells electricity but does not own generating facilities. A marketer takes title, and is approved by Federal Energy Regulatory Commission (FERC), to market electrical energy services. A marketer performs as a wholesaler and acquires transmission services. A marketer may handle both marketing and retailing functions;
9. **Customers.** A customer is the end-user of electricity with certain facilities connected to the distribution system, in the case of small customers, and connected to transmission system, in the case of bulk customers.

This work is oriented for a near future electricity market, in which the storage of energy produced from renewable energy sources in microgeneration has to be considered, as well as the impact of the utilization of Electric Vehicles (EVs). This future electricity market can be approximated as combinations of the existing markets, and taking into account this goal we discuss four of them — baseload power, peak power, spinning reserves, and regulation — which differ in control method, response time, duration of the power dispatch, contract terms, and price. The work will focus particularly on spinning reserves and regulation, which must deliver power within minutes or seconds of a request.

Baseload power is the electricity provided just in time and the energy is mainly produced through large nuclear or coal-fired plants that have low costs per kWh. This market is mainly for GENCOs. Several studies [Kempton, 1997], [Kempton, 2000], [Hawkins, 2001] and [Tomić, 2007], shows that EVs cannot provide baseload power at a competitive price.

Peak Power Market - Peak power is generated or purchased at times of day when high levels of power consumption are expected — for example, on hot summer afternoons, coal nights in winter. Again this is a market for GENCOs. Earlier studies have shown that V2G peak power may be economic under some circumstances [Kempton, 1997], [Kempton, 2000], [Kempton, 2001] and [Nagata, 2005], but nowadays car manufactures considerer that this behavior could affect seriously the battery life time.

Spinning Reserves is the market concept related with the power available capacity but unloaded, usually to cover an operator failure. This service is paid by the time that predefined power is available. For example, a 1 MW generator kept “spinning” and ready during a 24 hours period would be sold as 1 MW-day, even though no energy was actually

produced, [Kempton, 2005]. Based in this fact, and taking into account that EVs stay plugged in average 80%-90% of day time, creates a potential market for EVs if we aggregate them (see section 4.1). Since the possibility of taking an excessive amount of energy from an EV is low, the probability of reducing EV life time is minimized. Contracts for spinning reserves limit the number and duration of calls, with 20 calls per year and 1 hour per call typical maxima [Kirby, 2003]. Ancillary services account for 5–10% of electricity cost, with 80% of that cost going to regulation [Brooks, 2001].

Regulation are the actions to matching generation to load demand and can be divided in: (1) regulation up where we have an increase of electricity output in response to automatic generation control¹⁸ (AGC); and (2) regulation down (an decrease of electricity output to AGC). “Regulation must be under direct real-time control of the grid operator, with the generating unit capable of receiving signals from the grid operator’s computer and responding within a minute or less by increasing or decreasing the output of the generator. Depending on the electricity market and grid operator, regulation may overlap or be supplemented by slower adjustments, including “balancing service” (intra-hour and hourly) and/or “load following.” [Kempton, 2005].

2.3.1. EV and Energy Market

Other interesting problem on EV research is the potential of EV for the energy market, since it has energy storage capacity. This is the logic behind the concept of V2G (Vehicle-to-Grid), where EV provides electricity to the distribution grid, and G2V (Grid-to-Vehicle), where EV is charged with electricity from the grid, Figure 2-6 illustrates this concept. V2G provides a means by which exploit parked EVs to generate electricity for the grid, creating additional value. That is, V2G enables EV to both act as Distributed Energy Resources (DERs) and provide mobility services, bringing the transportation and the electricity systems together.

Distributed Energy Resources (DERs) have become the focus of considerable research and investigation, as well as commercial interest in the EU, USA and around the world. There is a substantial volume of research on the subject of DERs and their potential to provide

¹⁸ Is a system for adjusting the power output of multiple generators at different power plants, in response to changes in the load. Since a power grid requires that generation and load closely balance moment by moment, frequent adjustments to the output of generators are necessary.

various benefits to individual customers, to the utilities, and to society. In this scenario energy prices will change based on market law of demand versus production available.




Figure 2-6: Illustrative diagram of the EVs mode of V2G (discharging process) and G2V (charging process).

In this scenario Electric Vehicles (EVs) play an important role (as it is discussed in the following sections). EVs can help the integration of renewable energy resources, because EVs can store the excess of energy production, since renewable sources are intermittent, and then EVs can supply energy when production from renewables is low. However, as the main drawback of this approach, and as mentioned before, EV's batteries can have their life time reduced.

The EV must possess three elements to operate in V2G and G2V configuration: (1) a power connection to the electrical grid; (2) a control and/or communication device that allows the grid operators access to the energy stored in the EV batteries; and (3) precision metering on board the vehicle to track energy flows [Kempton, 2005].

This intelligent, two-way communication between the electrical grid and the vehicle enables utilities to manage electricity resources better, and it empowers vehicle owners to earn money by selling electrical energy back to the grid and participate in the electricity market.

2.3.2. Distribution Network

The electrical power distribution network connects producers to consumers, and its topology changes from country to country and according to the situation to be considered. The network illustrated in Figure 2-7 is at high voltage in transmission from big production centers to main cities, and then at medium-voltage and low-voltage (less than 1 kV) in the

distribution for final consumers. To this work and for the EV introduction we will look only on low voltage distribution (last part of distribution system) (see section 3.7 to 3.8). In Section 3.7 a new approach is proposed based on a geo-reference graph topology to represent and visualize the electrical network.




Figure 2-7: General layout of an electrical network. A transmission grid is usually defined for voltages higher than 110 kV, and a distribution grid for voltages lower than [Mbizon, 2010].

2.4. Electromobility

Electromobility refers to the use of electric vehicles for various transport needs and is a new growing area, where it is given a small overview on: the Storage Technology (e.g., the Batteries and associated control mechanisms) (Section 2.4.1), the EV Charging Process (Section 2.4.2), and the EV Utilization Characteristics (Section 2.4.3).

2.4.1. Storage Technology

In this section are described the main components of an energy storage technology system: The battery and the Battery Management System (BMS) to handle the operation of the battery integrated in the EV.

Batteries employed in EV operate under arduous conditions, being subjected to both large dynamic transients in current and power demand over a wide temperature range. Some of these transients are better handled by ultracapacitors, as they can absorb and provide high peaks of current and power. The future trend is to provide a tandem of batteries and ultracapacitors to achieve a high performance of energy storage. The accommodation of such operating conditions requires that the management system has accurate knowledge of the State of Charge (SoC) to facilitate safe and efficient utilization of the batteries, by preventing under or over-charging conditions, thereby extending the lifetime and preventing progressive permanent damage to the batteries. The electrical protection of the batteries during the charging and discharging process and the real-time monitoring of the cell, allows an accurate prediction of failures and will increase the batteries lifetime. These features are implemented with a Battery Management Systems (BMS).

The battery state, in terms of stored energy, is mainly based on the SoC, and the capability to store and deliver energy is influenced by the State of Health (SoH). The State of Health reflects the general condition of a battery and its ability to deliver the specified performance compared with a fresh battery. It takes into account such factors as charge acceptance, internal resistance, voltage, self-discharge and temperature during charge, discharge and storage (e.g., when the EV is parked during long periods). The knowledge of the battery state gives the possibility to adjust the control loop for the electrical management, by using the battery state and the driver decisions. In this task algorithms and devices have to be developed to forecast the State of Charge of the vehicle batteries, mainly taking into account the voltage levels of each individual cell, currents along the time and temperature.

Also, it has to be forecasted the vehicle batteries State of Health by two ways: the analysis of the historical of the charge/discharge cycles and/or by doing a test to the batteries.

2.4.2. EV Charging Process

EV Charging Process is associated with the G2V process, where energy is taken from the grid to the EV battery in a process that takes much more time than a conventional ICE vehicle fills up. The EV charging process can be performed: (1) at public places, in charging stations; or (2) at users' home, using charging devices. This processes use ICT approach to manage and control the electricity flow (transactions, electrical network distribution limitations, renewable integration). We divide this Section in: (1) Charging Methods; (2) Charging Infrastructures; and (3) Information System for EV Charging Process.

Charging Methods

The charging mode describes the method by which the electric vehicle is charged. There are five main methods of charging EV batteries (see Figure 2-8): (1) constant voltage; (2) constant current; (3) taper current (where the charging is performed from a crude unregulated constant voltage source, and the current diminishes as the cell voltage builds up); (4) pulsed charge (where pulsed chargers feed the charge current to the battery in pulses - the charging rate, based on the average current, can be precisely controlled by varying the width of the pulses, typically of about one second); (5) a combination of the previous methods of charging the batteries.

Most EV charging systems use a constant voltage for the initial portion of the charging process, followed by a constant current for the finish. Most of the battery capacity is restored during the constant voltage portion of the charging cycle. Temperature should be controlled (in all the charging methods), and thus it is preferable to have a temperature compensated charger (the coefficient of the temperature compensation should be about ± 18 mV/battery/ $^{\circ}$ C variation, from 25° C) [Jana, 1998]. The charging voltage must be reduced for ambient temperatures in excess of 25° C and increased for temperatures lower than 25° C [Jana, 1998].




Figure 2-8: Main methods of charging EV batteries.

Three possible methods can be implemented to recharge the battery. In a charge infrastructure review, [Morrow, 2008] describes three charging "levels" defined by the US Electric Power Research Institute (EPRI):

- The level 1 method uses the US standard 120 VAC, 15 A or 20 A branch circuit, used in the residential and commercial buildings. It delivers a 1.44 kW maximum power. This method would require for the user to install a new dedicated circuit to avoid overload.
- The level 2 method is based on a 240 VAC, single phase, and branch circuit with up to 40A. Under 15A, the maximum charging power would be 3.3 kW. This method could be implemented for both residential and public charging.
- The level 3 is the method suitable for fast charging through public facilities, based on 480 VAC, three-phase circuit, and enabling 60 kW to 150 kW charging power. This option implies a number of specific safety precautions.

Level 2 method would be enough to ensure a "rich" charging infrastructure. Table 2-2 summarizes the technical features, infrastructure requirement:

Table 2-2: Technical features of each charging level defined by EPRI.

	Level 1	Level 2	Level 3
Voltage/Current	US: 120 VAC / 15 A; EU: 220 VAC	US: 240 VAC / 40 A; EU: 240 VAC	480 VAC
Charging power	1.44 kW in US, higher	3.3 kW (15 A)	60-150 kW

	value in EU		
Charging time for a 10 kWh battery	~5-8 hours, even faster in EU	~1-2 hours	< 10 minutes
Vehicle equipment requirement	Higher battery capacity Required. On-board charger.	High battery capacity Required. On-board charger.	Low battery capacity required
Infrastructure requirement	Cable from electricity outlet to the vehicle. New dedicated circuit.	Stationary charger. Cable from electricity outlet to the vehicle. New dedicated circuit.	Stationary charger Three-phase

The creation of a charging infrastructure is essential for EV market introduction. The electrical energy sector, with the help of government initiatives, car manufactures and private companies are the main stakeholders of this complex process. An encouraging framework, with clear targets for market penetration and standards for battery chargers and billing systems, are required to build-up an infrastructure and several pilot tests have been performed, most of them with governments funding's. Table 2-3: Pilot tests performed with EV charging processes, show some of these initiatives, and Figure 2-9 illustrates current public charging station implementations and forecasts for the most active countries on this business.

Table 2-3: Pilot tests performed with EV charging processes (June 2011 Status).

City/Country	Description
London / UK	“Electric Vehicle Delivery Plan for London” – Mayor of London – May 2009 – building of infrastructure, EV procurement, incentives & marketing.
Singapore, Singapore	“Electric Vehicle Test Bed program” – CEO, Energy Market Authority – May 2009.
Los Angeles / USA	“Southern California Regional Plug-In Electric Vehicle (PEV) Plan” – Mayor of Los Angeles – Dec 2009 - Investment in charging infrastructure, streamlining permitting, fleet acquisition.
San Francisco / USA	9-step plan to make Bay Area “EV Capital of US” – Mayors of San Francisco, San Jose & Oakland – Feb 2009.
Portland / USA	Mayor of Sam Adams - announcement with Nissan for electric vehicle pilot Project.
Paris / France	Mayor of Delanoe announces “Autolib” ¹⁵ , a 4,000 EV rental program – Oct 2009.




Figure 2-9: Number of Public EV Charging Stations by countries (status June 2011).

Charging Infrastructure

An appropriate infrastructure provides the availability and necessary density of recharging possibilities. In a first phase, recharging places should be installed in parallel at strategic locations – including homes, workplaces and truck or bus depots – as well as on main roads: (1) identification of the early adopter hotspots and build capacity there; (2) public recharging stations (parking garage, shopping mall, Park & Ride, dedicated); (3) parking spots along streets; (4) home/depot recharging; and (5) workplace recharging. Standardization and business models play an important role on this starting process.

There are also several federal government initiatives or projects funded by federal governments across the world. In Portugal, Renault and Nissan have signed a contract with MOBIE.Tech in 2008. The MOBIE¹⁹ network has installed 100 charging stations and it is deploying 1300 charging stations as well as 50 fast-charging stations in 25 cities up to June 2011. The MOBIE stations work with magnetic stripe card and bills are sent to the cell phones of the users²⁰. In Singapore, a US \$ 99.8 Million stimulus grant was awarded. In

¹⁹ Information available at <<http://www.mobie.pt>>.

²⁰ Information available at <<http://www.mobie.pt>>.

the USA, the government of Arizona launched the ECOTality program, for an EV test pilot across 5 USA states, involving the deployment of up to 4700 Nissan LEAF EV and 11210 charging stations, [Philip, 2010]. In September 2009, China & the USA announced the launch of the US-China EV Initiative under which both countries would work together on standards development, demonstrations, a technical roadmap, as well as public awareness and engagement, [Philip, 2010]. Governments are not alone in showing increasingly high levels of activity in what regard to EV. Almost all large OEMs have by now announced EV prototypes, models, or even concrete dates for launching EV models in the market. Nissan launched its LEAF electric car in 2010. Even consulting companies seem to believe that EV is a defining topic for the future of the car industry – both McKinsey and the Boston Consulting Group have recently released extensive studies on the EV market²¹.

Infrastructure providers companies start to emerge providing charging stations, products and works related to EVs. Examples are:

- In the USA: Coulomb Technologies, Better Place, EV-Charge America;
- In Europe: Park & Charge, Circontrol, POD Point, Efacec, Magnum Cap, Cabelt.

A uniform worldwide charging infrastructure is necessary (interoperability), where should be possible to charge electric vehicles everywhere, at any times. User interests must have priority over the interests of individual companies.

Information System for EV Charging Process

EV charging process (remote interactions, power limitations of home consumer or electrical distribution network), integration of renewable energy resources, and electricity market, raise a complex environment where mobile information systems can play an important role. In the author's opinion this is a rich scenario, similar to the Internet. This information system can play an important role by automatically managing the charging process, maximizing the use of renewable energy, such as wind energy, which is generally stronger at night when demand is low, which can enable customers to schedule charging based on price signals. Initial information systems will focus on collecting data and

²¹Information available at <<http://www.bcg.com/documents/file36615.pdf>> and also <http://online.wsj.com/public/resources/documents/mckinsey_electric_vehicle_0113.pdf>.

presenting it to consumers, but once charging infrastructures are growing, and communication standards between EV and external systems are defined, a diversity of applications could be created to help EV drivers. Greater knowledge of the lifetime value of EV IT (Information Technology) systems, including the financial benefits from reducing carbon emissions, would make it easier for utilities to justify the investments [Pikeresearch, 2010]. Also, a study [Pikeresearch, 2010] shows that this market has a huge growing potential. EU opens a tender call (May 2011) for the study of “The impact of ICT R&D in the large-scale deployment of the electric vehicle SMART 2011/0065”. A preparatory study to EU is open (May 2011) [Tender, 2011] for future definition of new FP7 calls on this new topic.

The implementation of information systems for EV will be slowed down by the lack of standards for sharing information between utilities and external systems [CENELEC, 2011].

2.4.3. EV Utilization Characteristics

This section describes the characteristics of the EV batteries and the utilization of the EV. Automobile plays an important role in transportation and new challenges have appeared with the introduction of the EV with the limited range autonomy²². Drivers of EV will have to cope with a new problem: the fear of being stranded in an EV due to inadequate battery capacity: the range anxiety problem [Schott, 2009; Nilsson 2011]. This problem gains more relevance during this startup phase due to the lack of charging stations. The success of EV in part is going to depend on how comfortable people are, so that they can get where they want to go, without running out of charge, and without having to go through some process that will take them a long time and impact their ability to use the vehicle. So, taking out real time EV information, such as SoC (State of Charge), energy transactions, and other vehicle events, plays an important role. This information, taking into account recent progresses in mobile devices, geographic information systems and communication processes, can bring added value to drivers.

²² For example de Nissan Leaf has an autonomy of less than 160 km.

SoC (State of Charge)

The State of Charge (SoC) is an important parameter that defines the percentage of energy stored (from zero to one) in the battery. One means the battery is with the full charge, and it decreases when energy is withdrawn from the battery. Figure 2-10 shows the evolution of SoC level during a day, in which the EV owner goes to work in the morning, parks the EV, goes back home in the late afternoon, and then plugs-in the EV for charging during the night. Figure 2-4 also shows an example of EV charging for a typical day.

Batteries release energy more easily when their SoC is high, or more precisely, above a certain tolerance level. When the SoC is lower than 60%, a more appropriate utilization of the battery is for energy absorption (recharging of the batteries) [Guille, 2009]. Also, overall battery performance for either absorption or release is much higher in a band around this tolerance level [Yamane, 2002]. The width of this band is not well understood, and so, it is still a topic of research. If the battery releases energy, then the EV acts as a supply-side resource. If it absorbs energy, the EV acts as a demand-side resource [Guille, 2009].




Figure 2-10: Evolution of the SoC of an EV battery pack for a typical day.

Range Anxiety Problem

Range anxiety is a term mostly associated with EVs in the context of their limited range and underdeveloped infrastructures of charging opportunities [Wellings, 2011]. In general terms, range anxiety can be explained as the fear of a possible negative future event. It is believed that range anxiety was first reported in the press in 1997. Range anxiety is, in many ways, an intuitive term which are most often defined as perceptions or the experience of drivers regarding the fear of not reaching your destination when you are in an EV. Some definitions refer to the problem of recharging the EV, that is, the phenomenon may not only

relate to the occurrence of the particular situation but also to the available actions needing to be performed when in a situation in which the destination can no longer be reached.

2.5. Projects Related with Mobi-System

Figure 2-11, shows the main work interfaces to related projects in the electro-mobility area:

1. From ISEL we refer three main projects: (1) VEECO, where ISEL participated on the development of a Portuguese electric vehicle²³. The author participated on the definition of the vehicle interface with the battery system, as well as in the infotainment system (VEECO computer navigation system); (2) START²⁴ (INTERREG IVB) – Chapter 5 were based on author's contribution; and (3) MIBEL EDP project, where ISEL participated on the development of a trade platform for the open market energy in Portugal and Spain.
2. From Universidade do Minho, the Professor João Afonso's group participated in the development of home charging devices [Monteiro, 2010], charging and discharging processes [Monteiro, 2012], and also in the integration of renewable energy resources [Ferreira, 2013].
3. From INESC-ID, the Professor Alberto Silva's group, it was used the experience of mobile system [Ribeiro, 2012] and the project of Iniciativa eXcitingTrails [Belchior, 2011] and MobileTrails²⁵.
4. From INTELI²⁶ it was used the Mobi.E project and the charging infrastructure developed and implemented in Portugal. INTELI submitted a tender call to FP7 in May 2011 [Tender 2011]: SMART 2011/0065 "The impact of ICT R&D in the large scale deployment of the electric vehicle". This proposal reached the final decision phase, although it was not selected. Mobi-Guimaraes²⁷ was a POVT-09-0142-FEDER-000017 project approved in 2009, for the event Guimarães capital Europeia da Cultura in 2012. In 2009 was foreseen to use it in the demo events, however due financial constraints it was canceled;

²³ . For more information see public VEECO web site <www.veeco.pt>.

²⁴ <<http://www.start-project.eu/en/Home.aspx>>.

²⁵ for details see <<http://www.siquant.pt>>.

²⁶ <www.inteli.pt>.

²⁷ <<http://politicadecidades.dgotdu.pt/polis/projectos/Lists/Projectos/DispForm.aspx?ID=8>>.

- From CEIIA the participation in EV projects and the preparation of a FP7 proposal, the Electro-Mobility Cockpit Systems and Applications for FEV Range Optimisation and Seamless Integration in the Cooperative Transport Infrastructure (MOBI.Cockpit).




Figure 2-11: Personal Context of current research work.

2.6. Related European Projects

2.6.1. Public Transport Information Integration

Public transport information integration is one specific area, for which there is still lack of EU level data integration among different public transportation organisms. The European Commission has sponsored a series of recent projects which have succeeded in moving forward the state of the art in the provision of multimodal traveler information. Each project was built on the foundations of the projects before them, which include:

- ITISS (INTERREG IIIB) - developed the provision of real time information to travelers on the move through mobile devices (2003-2007);
- SIMBA 2 (FP7) - sought to increase road transport research cooperation between Europe and the emerging markets of Brazil, China, India, Russia and South Africa

by establishing a network of stakeholders in the field of Intelligent Transport Systems (ITS) (2006-2008);

- eMOTION (FP6) - was a study to investigate, specify and assess multi-modal, on-trip Traffic and Travel Information Services for European travellers (2006-2008);
- WISETRIP (FP7-SST) - developed a platform for the provision of public transport multi modal travel information between EU and Chinese partners (2008-2010);
- OPTI-TRANS (FP7) - developed a mobile platform for travellers to plan their journeys using public and private transport (2009-2010);
- IN-TIME (ICT-PSP) - focuses on the delivery of multimodal Real Time Traffic and Travel Information services to European travellers (2009-2011);
- START (INTERREG IVB) - developed a trans-European information portal to enable cities/regions to provide multi-lingual information to travellers, perform simple route planning from region to region, access detailed planning tools and Public Transportation operator's data (2006-2011).

Additionally the EU ITS Directive 2010 requires member states to deliver a number of systems according to the ITS Action Plan. These systems include provision of Multi Modal Traveler Information Systems by 2015.

2.6.2. EV Energy Consumption and Management

ICT and smart systems will facilitate the EV integration with the sustainable mobility initiatives under the motto “Smart Cities”, where the integration of information regarding the public transportation services will play an important role.

The application of ICT R&D in the large-scale deployment of the EV is a new challenging topic with a huge growing potential, and this study impact is an important task to prioritize and evaluate the diversity of options. The integration with renewable energy resources (Europe is leading this subject) could play an important role in this process and could be a key for Europe to recover some delay from Asia and North America in the EV areas.

The European Commission has sponsored a series of FP7 projects that contribute for the application of ICT in EV:

- EcoGem aims providing efficient ICT-based solutions to assist EV driver to increase range autonomy and energy efficiency through learning over time to

predict (and thus avoid) congested and energy consuming routes, based on experience that they gather. This learning process will render each EcoGem EV capable of autonomously classifying routes according to their degree of energy efficiency, enabling energy-driven route planning optimization and extending considerably EV efficiency and range of operation (2010-2013);

- OpEneR addresses the problem of range anxiety with a proposal range increase based on efficient energy management. A particular focus will be given to an optimal cooperation between the electric drivetrain and the regenerative braking system, supported by data from radar, video, satellite navigation, car-to-infrastructure and car-to-car systems (2012-2014);
- ELVIRE addresses the problem of range anxiety based on a collaborative platform between driver and charging infra-structure. Great emphasis is placed on the openness of the electricity service platform, granting access to multiple players and maintaining the customer's choice (2010-2012);
- P-MOB project aims to break the link between the growth in transportation capacity and increased facilities, congestions and pollution. The project proposes a novel concept of fully-electric personal mobility, addressing the needs of urban mobility whilst also encompassing characteristics suitable for extra urban mobility; reduced system complexity (a common car can have more than 50 processors, actuators and sensors), with a focus on the key essentials, and advanced systems integration, including: thin film solar cells (2010-2013);
- Several projects on charging and infrastructure interaction, such as: PowerUp (2011-2013), SMARTV2G (2011-2013).

2.7. Conclusions

In this Chapter it was researched and analyzed the state of the art of related topics. Due to the diversity of subjects' involved, electrical energy, electrical markets, transportation and information systems, a brief overview of those topics were performed. Main topics were covered, such as, EV types, smart cities, charging process, standardization, EV usage, electricity market participation (identification of potential interesting topics), and electrical distribution networks.

3. MOBI-SYSTEM: EV RELATED FUNCTIONS

This chapter introduces and discusses the central Mobi-System functions, related with the EV charging process. The main EV function modules are illustrated in Figure 3-1, and each of them is described in the following sections.




Figure 3-1: EV functions main modules.

3.1. Information Extraction from EV and Charging Device

The module “Information Extraction” is based on two equipment, with wired and wireless communications interfaces, allowing access information for two different scenarios/systems: EV and Home Charger Device. Providing relevant data from EV and charging spots to the platform, these devices integrate Charger Systems and EVs with the Mobi-System, enabling intelligent and opportunistic EV charging management, and providing useful information for each driver according to her/his needs. Main information extraction is the charging log file performed by charging devices, the information from EV and the commands to the charging device (Figure 3-2):




Figure 3-2: Main information to extract and commands to perform on charging device.

Analyses of transactions data can be useful information for future charging or discharging processes, taking into account a smart charging strategy to combine distribution network limitation and low prices. All this information is stored on the information repository on the central server.

If Internet communication is available, the driver can check remotely the home charging process, and interact with it if he wants to. Additional information in [Ferreira, 2012a].

3.1.1. Development of the OBU (On Board Unit)

The communication process consists in the development of an OBU (On Board Unit) working prototype, including hardware and software, to be installed on-board in the EV, providing telematics both locally (in the EV) and remotely (to the Mobi-System). The device is based on a microcontroller that integrates CAN, Bluetooth, GSM/GPRS (Global System for Mobile communications / General Packet Radio Service) and GPS (Global Positioning System). The implementation of CAN protocol allow requesting and receiving data from the car. With the available OBU wireless communications interfaces, it is

possible to report both locally and remotely the data being received from the EV through Bluetooth and/or GSM/GPRS technologies, respectively. Moreover, Bluetooth allows the OBU integration with mobile equipment, such as a mobile/smart phones. Additionally, and by having knowledge of the EV current coordinates (GPS receiver), the OBU is able to make the best decisions through the platform. GPRS allows the development and implementation of the OBU update over the air, increasing the easiness with which software updates are made. This work was performed by an ISEL (*Instituto Superior de Engenharia de Lisboa* – Lisbon Superior Institute of Engineering) partner company (Dailywork), in an ISEL electric car project (VEECO - Veículo Eléctrico Ecológico – Ecological Electric Vehicle). Due to confidentiality agreements signed in VEECO project, it is not possible to provide more detailed information. Also, this task was not easy to be performed due to missing information provided by the electric motor manufacturer company. This work was part of a student final year project in ISEL, where Figure 3-3 shows the main results achieved: the extraction and visualization in real time of VEECO information.




Figure 3-3: Visualization of VEECO extracted information in an external laptop [Gaeda, 2011].

3.1.2. Development of the RSU (Road Side Unit) Located on Charger System

Currently, a charger system is an equipment which only has in consideration the EV batteries charge level. This task aims to develop a RSU (Road Side Unit) which interacts with the different blocks that constitute the charger system to provide more information to the EV driver and to the Mobi-System. It can provide the SoC (State of Charge), the charge remaining time, the efficiency of charging, as well as other data.

In this task, it is developed the RSU, a prototype including hardware and software to be attached to the charger system, providing telematics, both locally and remotely. The RSU device integrates Bluetooth, GSM/GPRS and charger information. The available RSU wireless communications interfaces allow to report locally and remotely the charger system information data. As for the OBU, Bluetooth allows the integration of RSU with mobile equipment, such as a mobile/smart phone, and GPRS allows the development and implementation of the RSU update over the air, increasing the easiness of software updates.

3.2. Information Repository

The Central Information Repository stores EV related information, namely: (1) EV drivers profile; (2) electricity transactions of EV; (3) electricity prices; (4) weather information; (5) driving parameters; and (6) other EV related information. For detail information see corresponding Sections.

This Central Information Repository is based on XML files and a Mysql database implementation. Since our goal was the creation of a prototype, not a commercial application, this subject was not tuned for best system performance, but only for testing purposes.

3.3. Driver Profile

Initial driver profile is manually created by the driver, with the following information (Table 3-1):

Table 3-1: User Profile of an EV.

Propriety	Description
User login information	User name and password

Drivers information	Driver Name, birth date, sex
Home Address	GPS position of home address
Work Address	GPS position of Drivers work
Car Information	Model, Year, Battery type and power
Energy market behaviour	Minimum SoC level, price to sell and to buy
Trip information	Work days or weekend + holidays, start time, finish time, distance (km)

Driver is allowed to perform the following operations (Figure 3-4):




Figure 3-4: User Profile Operations.

This profile, later receives information about driver trip (time, duration and km travelled) from the tracking system. Also, home simulation module creates an electricity load profile (see Section 3.8) that is associated with this profile. A resume of EV parameters (speed, SoC level, travelled distance) is also stored and associated with this profile for later range prediction (see Section 3.10).

3.4. Public Charging Station

Public Charging Station (PCS) main module goal is the driver guidance towards nearest PCS, and the enable of on line advanced booking of charging spots. Due to missing standards communication formats, the system developed in Mobi-System uses KML²⁸ file

²⁸ **Keyhole Markup Language (KML)** is an XML schema for expressing geographic annotation and visualization within Internet-based two-dimensional maps and three-dimensional Earth browsers. KML was developed for use with Google Earth.

or compressed KMZ, to receive data from charging stations. In this file format EV position is defined, but in this work it is necessary additional information (see Figure 3-5):




Figure 3-5: Fields of KML file for information exchange with charging station.

The system developed for Mobi-System receives GPS coordinates of EV position and finds the nearest charging stations, showing the distances to them and giving guidance to the driver using Google Maps API (see used case in Chapter 6).

The booking slot process is complex, because batteries charging process takes more time than a usual gasoline deposit fill up, and a pre-reservation system should help on this process. So our proposal is a system for management of reserves (*Sistema para Gestão de Reservas* - SGR), that allows driver's mobile devices to communicate and performs reservations. To communicate with the SGR should be used a technology that allows synchronous communication. The Mobi-System is prepared to communicate with the SGR with a Webservice. The SGR responds to mobile device communication response with a reservation confirmation, or with a warning indicating the unavailability of slots. One of the issues that arise when proposing an SGR is the possibility of drivers failed to attend on time (or even didn't show) to a reserve performed. The SGR must implement mechanisms to minimize the impact of slots are being reserved, and then run out by failure of the driver. One possible solution is to implement a scoring system, which penalizes drivers with one point in their record when they fail to reserve a charging slot. When the driver reaches three

points, equivalent to three failures, the driver has to go to an operator and try to reactivate his/her access to the SGR.



Figure 3-6: Image of a Public charging infrastructure²⁹.

The diagram in Figure 3-7 illustrates how the SGR can be implemented with a system of penalty points. The information is centralized in the SGR, communicating with all operators, which also allows the exchange of information on penalty points, making the system more efficient. The SGR is prepared to follow a business model which is implemented with a slot reversion, failures penalties and a waiting of reservations of 5 minutes (administrator configurable time). The same approach and software module is used for parking places reservation. There are several issues related with PCS (Public Charging Station), which are not covered in this work: infrastructure creation, standardization, electrical energy network distribution (high power). In a PCS service, it is not used the previous module of smart charging, because should exist power limitation on charging process.

²⁹ Source image from <www.ekomiko.pl>. Available charging spots could be a problem since fast charging takes time (more less 10 to 30 minutes (it depends applied power and desirable SoC level)).




Figure 3-7: SGR penalty points to avoid user reservation failures.

3.5. Tracking System in ‘Offline’ Mode Drive

User profile plays an important role in the V2G or G2V process. Also to study drivers’ habits and profile update it has developed a tracking application to run in an offline mode (to avoid communication costs) in a mobile device with GPS device. The work was performed in a final year project at ISEL, described at [Sousa, 2010], and its high level vision is showed in Figure 3-8.

This tracking application mainly stores time, GPS coordinates and user identification. From the GPS coordinates it is easy to calculate travel distances. Using Google Maps API it is represented the driver route and it is obtained the travel distance.

From the travelled distance and EV efficiency it is estimated the remaining energy stored in the batteries of each EV (SoC – State of Charge level), as well as the community SoC level (sum of all individual community SoC levels). The studied population (from the city

of Lisbon area), with 50 cases, contains a mixture of university students and their parents, and takes into account the first EV introduced in Portugal, the Nissan Leaf, with a battery pack of 24 kWh and autonomy of 160 km (obtained with a careful driving).




Figure 3-8: Main module of driver's tracking system in a mobile device with GPS, and information created from drivers movements database.



Figure 3-9: Menu de Opções da Aplicação GPS Tracker.



The application of GPS Tracker allows to see the GPS data on its position, direction, and speed. This information is placed on the screen of the mobile device using the method `DisplayLocationInfo ()` in class GPS

Figure 3-10: Menu Principal da Aplicação GPS Tracker.

The system allows seeing statistics on the route taken, including: (1) travel duration time; (2) total distance traveled; (3) average speed; and (4) others that can be obtained by data manipulation (e.g., trip cost, price). The system can also provide all the above parameters for all the paths of the user, thus obtaining the total average values.

The presentation of statistical results for one route or for all the paths of the user is done via GPS ReportView running a personal computer system user. The purpose of this application is to allow viewing of all the statistical data corresponding to journeys made by the system user and owner of an EV, so that it is possible to graphically view each journey made. This application provides a list of all journeys performed by the driver with statistics related with all journeys (average speed, distance, time).

3.6. Weather Module

In the residential and commercial sectors, heating and cooling account for more than 40% of end-use energy demand [FERC, 2004]. As a result, energy consumption in those sectors can vary significantly from year to year, depending on yearly average temperatures³⁰. Several studies prove a relation between electricity consumption and temperature, especially for higher temperatures (most peak power consumption were reached on very hot days) [FERC, 2004]. Cooling is related with air conditioners (electricity powered) and

³⁰ Information taken from web site <<http://www.energy.eu/>>.

heating with central heating (gas powered), so peak electricity consumption occurs in hot summer days [FERC, 2004]. As indicated in Figure 3-11, there is a high correlation between the simple average daily temperature from the four sites selected and daily electricity demand in the CalISO region, which comprises most of the state of California, in the USA [Crowley, 2005]. This relation has been observed by several authors [Crowley, 2005], [Franco, 2007], and there is more or less 1% of electricity demand increase by 2°C of temperature rising. This Weather Module application was developed and is running, making possible to estimate this relation. A Web crawler (Web Content Extractor) was configured to take information from the main Portuguese weather site³¹. From the Web pages extracted with pre-defined forms it is taken information related with temperature, wind (direction and speed), rain and solar conditions (e.g., sunny, cloudy, etc). This crawler runs in a pre-defined periodicity and the information is stored on a database. In a near future the present work intends to add more information from different web sites and merge this information on the proposed database. When a failure occurs the previously available values are stored in the database. Temperature data is related with electricity consumption, and the other parameters are associated with renewable energy production: wind to Eolic, temperature and solar radiation to Photovoltaic, and rain to Hydropower production.




Figure 3-11: Electricity demand in the CalISO area as function of average daily temperatures: 2004 [Crowley, 2003].

³¹ <www.meteo.pt>.

The weather data is geo-referenced (several locations were considered) and is stored in an information repository correlated with:

- Temperature with average consumption. We apply K-Means algorithm to identify main groups. The first groups are: (1) below 0°C; (2) from 0°C to 8°C; (3) from 8°C to 18°C; (4) from 18°C to 26°C; (5) from 26°C to 31°C; (6) from 31°C to 35°C; and (7) above 35°C. From this centroids data (average consumption) it is calculated the percentage of consumption change due to group change.
- Wind speed and direction with Eolic production.
- Temperature and weather conditions with Solar Photovoltaic production.
- Rain in month's periods with Hydropower production capacity. We propose in a near future to try to identify which is the best time period to collect rain data.

Later in Section 4.3, it is explored this approach to estimate microgeneration production based on past data stored in a central repository. This weather information is used on range prediction process (see Section 3.10).

3.7. Geo-Reference Graph for the Electrical Distribution Network

One important approach introduced is the Geo-Reference Graph for the electrical distribution network. This allows computational data manipulation, such as distance calculation, identification of power limitation (Section 3.9) and identification of user communities (Section 4.2).

The area with the distribution of the electrical network is manually transformed in a graph (see Figure 3-12 and Figure 3-13), where it is added geographic information and power limitations between the nodes. This is a slow process where it is expected in a near future to introduce some automation. Assumptions on consumer's behavior are considered: (1) consumers define their house and family (number of house divisions, number of persons); (2) they define the number and type of electrical appliances from a pre-defined list; and (3) they define also their usual routine (arrival time, departure time). Tracking system data can tune arrival and departure times. Every consumer has its own behavior and changes or unexpected behavior are randomly generated at the beginning of the experiment, using an array of integers. Each consumer is represented by an agent who knows contractual power

limitation and also the limitations of the distribution network. Table 3.2 shows the configuration used for case study presented in the next section.




Figure 3-12: Electrical distribution network, transformed in a graph.




Figure 3-13: Geo-reference electrical distribution network with power limitations.

Table 3-2: Information about distribution network, used for our case study.

Node	Description	Type	Elevators (kVA)	Common Services (kVA)	Simultaneous Coefficient (kVA)	Power Available (kVA)
1	House 1	1x T4	0	0	1	13.8
2	House 2	1x T4	0	0	1	13.8
3	House 3	1x T4	0	0	1	13.8
4	House 4	1x T4	0	0	1	13.8
5	House 5	1x T4	0	0	1	13.8
6	House 6	1x T4	0	0	1	13.8
7	Building 1 3 Floors	6x T2	20.7	6.9	0.75 (6 installations)	48.3 (6 x 4.6 x 0.75) +6.9+20.7
8	Building 2 2 Floors	1xT4 1xT3	0	6.9	1	31.05 13.8+10.35+6.9

3.8. Home Consumption Simulation

An agent based simulation attempts to simulate an abstract model of a particular system. Computer simulations have become an useful part of mathematical modeling of many natural systems in Physics, Chemistry and Biology, and of human systems in Economics, Psychology, Social Sciences, and Engineering. Simulations can be used to explore and gain new insights into new technology, and to estimate the performance of systems too complex for analytical solutions. This approach already has been applied for electricity market [Figueiredo, 2010], [Zhao, 2007], [Pitt, 1999], creating a simulation environment for market prices determination based on consumers demand, and for production capacity of producers. Our main idea is to simulate consumers consumption taking also into account unexpected user behavior, using past experience (consumption log files), and then representing the information in an electrical distribution network graph.

There are several tools that can be used for this purpose, from which NetLogo tool has been chosen. NetLogo is a free agent-based simulation environment that uses a modified version of the Logo programming language, providing a graphical environment to create programs that control graphic “turtles” that reside in a world of “patches,” which is monitored by an “observer”. NetLogo also includes an innovative feature, called HubNet, which allows groups of people to interactively engage in simulation runs alongside of computational agents.

On the simulation tool (Netlog) it is followed a bottom-up approach where it is estimated consumption based on consumer profile and historical consumption data, described in Figure 3-14. Weather information (temperature) is used as a percentage increase factor on usual consumption. Each consumer is represented by an agent that is based on historical data, profile and temperature information, based on a random function for energy consumption, which is estimated at every 15 minutes (this time interval is configurable). Each agent has a utility function, but the agent is not optimizing it because this process is too expensive under many aspects: in terms of information retrieval cost, in terms of information processing costs from a computational point of view, and in terms of cognitive effort in searching alternatives. We decide to model each consumer as a node on a distribution network graph. Simulation takes into account house power limitation contract and electrical energy distribution limitations. Our simulation platform is: (1) Dynamic, updating each entity (agent) at each occurring event; (2) Stochastic, based on conditional probabilities; and (3) Discrete, with the changes in the state of the system occurring instantaneously at random points in time as a result of the occurrence of discrete events. Main output information is the visualization of electrical distribution network on a graph with the indication of power limits. Red color means above power capacity, which indicates that EV charging should be processed in an intelligent interactive process; green color means that it is possible to charge EV batteries on full power. It is estimated the consumption and this information is used for a smart EV charging, without measuring devices and real time information. The main application screen of the consumption simulation is illustrated in Figure 3-15.

Relatively to electricity market functions, it is aggregated energy production and consumption data, and based on this simulation, estimate prices and then determinate the best charging or discharging periods.




Figure 3-14: Simulation approach methodology.




Figure 3-15: Simulation application on Netlog.

3.8.1. Model for Collecting Consumption Data

Consumption patterns are studied based on two factors: (1) what equipment are used by consumers; (2) power used by these equipment; and (3) time interval in which they are used.

In order to know how much power each device consumes, it is used data available from ERSE (*Entidade Reguladora dos Serviços Energéticos* - Energy Services Regulatory Entity, from Portugal), and obtained the following tables of average values of maximum power per appliance. Since there are no devices installed in the homes of consumers that allow collecting the power consumption information instantaneously, the data collection was done manually. Were chosen representative consumers (around 50 families in Lisbon area were asked to report supposed daily use of equipment in their homes)³². Table 3-3 presents a table with a list of possible equipment used at homes, and it was asked to the representative consumers to fill this table with the equipment used and with the hours of utilization.

The study of consumer habits of each family is based on an analysis of the questionnaire performed, as Table 3-4 an example. The set of connected devices and related values of power per hour will provide the total consumption of electrical energy per hour per family. We combine the study of these three sets in order to get the following templates: (1) Template 1: Large Family; (2) Template 2: Medium Family; and (3) Template 3: Small Family.

From tracking system it is taken information about the time drivers arrive / leave home and the travelled distance taken. These values are stored and a mean value and a standard deviation are used to feed simulation environment on Netlog. Agents represent drivers and average time is used to start actions. A stochastic environment is created by random functions (changing start times) that can change mean values to maximum deviations, taking into account a probabilistic function. Also weather information is used to increase

³² Details of this survey can be found at <www.deetc.isel.ipl.pt/matematica/jf/inq_cons.pdf>.

or decrease overall energy consumption. This simulation process uses electrical distribution network information taken from the geo-reference graph.

Table 3-3: Power consumption of conventional home equipment. Data taken from [ESRE, 2010].

Home Appliances	Power (kWh)	Leisure	Power (kWh)
Washing Machine	2.00	TV (convencional)	0.09
Tumble Dryer	3.50	TV (plasma)	0.30
Dishwasher	2.00	Stereo sound	0.06
Oven	2.40	DVD	0.24
Cooktop	6.20	Computer	0.30
Microwave	0.90	Lighting	
Broiler	1.80	Incandescent Lights	0.06
Exhaust	0.14	Halogen Lights	0.04
Toaster	1.00	Fluorescent Lights	0.04
Aspirator	1.60	LFC (Economics lights)	0.01
Iron	1.60	Home Temperature	
Fridge	0.15	Air Conditioning	1.80
Freezer	0.25	Oil Radiator	2.00
Hairdryer	1.50	Heater	2.00
Fryer	1.90	Water Heater	1.50
		Heat accumulator	2.50
		W.C. Heater	1.20

Table 3-4: Questionnaire table to users about home energy consumption.

	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	
Home Appliances																									
Washing Machine																									
Tumble Dryer																									
Dishwasher																									
Oven																						1			
Cooktop																									
Microwave																					1				
Broiler																									
Exhaust																									
Toaster										1															
Aspirator																									
Iron																							1	1	
Fridge		1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
Freezer		1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
Hairdryer									1																
Fryer																									
Leisure																									
TV (convencional)		1	1																		1	1	1	1	
TV (plasma)																									
Stereo sound									1																
DVD																									
Computer		1																					1		
Lighting																									
Incandescent Lights																									
Halogen Lights																									
Fluorescent Lights									1																
LFC (Economics lights)		3	1	1					1													4	4	3	3
Home Temperature																									
Air Conditioning																									
Oil Radiator																									
Heater																									
Water Heater																									
Heat accumulator																									
W.C. Heater																									

3.9. Smart Charging Strategy

The strategy of the smart charging system is defined in order to achieve the goals identified in Figure 3-16, taking into consideration integrated home consumption, electrical distribution network limitations and availability of power for charging. This system is based on a central information repository that can store and manage historical data on electricity consumption and production. From this central repository it is possible the development of tools to extract knowledge from past electricity exchange log files, electricity market prices, renewable energy availability, home energy consumption (if EV is connected at home) and electrical distribution network constraints. Also, the weather information can be used for the forecast of energy production from renewable energy sources, and the EV users arrival and departure times from home (obtained from a tracking device) can be used for

consumption timing optimization (e.g., users can change their behavior, and thus historical data needs to be fitted). This central repository will be later, in a Smart Grid (SG) environment, a fundamental module to store all kind of SG data, and to solve problems of different data format diversity.

Main Output information is the visualization of electrical distribution network on a graph with the indication of power limits (Figure 3-15). The first step is to estimate the electrical power consumed per household, and given the contracted power, to determine the available electrical power for charging EVs. It was considered a power limit for the electrical distribution system of 80% of the nominal power of the transformer that feeds a set of consumers of each particular zone of the low voltage electrical network. So, depending on the percentage of existing EVs, we may have additional limitations.




Figure 3-16: Smart Charging approach and goals.

The main results obtained are showed in Figure 3-17 and Figure 3-18. For more details of these results see [Ramada, 2010] and [Ferreira, 2011e]. These studies were oriented to simulate domestic consumption and distances traveled, to determine the most appropriate forms of representing the power consumption of the families, also considering the EVs. In

order to determine the time of the day when there is more available power to use to recharge the EV batteries, we have compiled the values of power consumption per hour, and it was found that, during the week, the ideal intervals for charging the EV would be between one and six o'clock in the morning (range A), or between nine and the sixteen hours (range B). In the weekend, the ideal intervals for charging the EV would be between one and eight hours (range A) or between fourteen and sixteen hours (range B).




Figure 3-17: Power Consumption Distribution (all types of family).




Figure 3-18: Large family consumption simulation results.

Relatively to electricity market functions, it was aggregated energy production and consumption data, and based on this simulation estimate prices, and then determine the best periods for charging or discharging (returning energy to the electrical distribution network) the batteries of the EVs.

3.10. Range Prediction Functions

3.10.1. Range Prediction

Range prediction is the process of estimation of EV range based on three main dependency types (Figure 3-19):

- **The EV with its main variables:** the model of the vehicle (mainly its performance under different scenarios, speed, and acceleration), the chemical technology of the batteries (as lithium-iron-phosphate, lithium-titanate, or nickel-metal-hidride) the batteries characteristics (mainly, variation of SoC, lifespan, performance, specific power, specific energy, and safety), and the EV powertrain (electric motor and its power converter, as well as the other electric parts, as batteries charger, controllers, and power cables). This data is stored on an information repository, on a central server. All of these parts will influence the SoC and consequently the range prediction. The batteries SoC, and other relevant parameters, are provided to the main control system through CAN-bus communication, and then these information are stored in a data base (DB), in order to predict the available range.
- **The driver behavior:** speed and acceleration information are taken from EV through the CAN-bus communication, and the driver past behavior (e.g., SoC level versus travelled distance achieved), are stored in a DB. Weight is a manual input, and driving directions are acquired based on the GPS information.
- **Environment:** current location, traffic conditions (taken from a web service), road information (in a distance graph), weather information (wind and temperature, taken from a web service), and altitude, taken from GPS.




Figure 3-19: Main parameters for range prediction.

The range prediction procedure is in a first step based on the batteries SoC level, and using driving behavior (relation of SoC level versus travelled distance achieved, from past experience, stored in a central information repository). This distance is tuned based on weather information: if it is hot, a percentage of the energy stored in the batteries is taken for air-conditioning; if it is raining, a percentage of energy is taken for the window cleaning process. For night drive, also a percentage of energy is taken for light services. A web service brings traffic information, and based on past experience (e.g., information about driving times and traffic information), a driving range is predicted. Current driving behavior (e.g., driving speed and accelerations) are taking into account in this process. Once it is achieved an estimation of EV range, it is started the calculation of possible reachable points based on current position. Most of these estimation processes were performed based on simple heuristics, and a deep study is prepared (current MSc dissertation, started in 2011 in ISEL). For example, if the weight is above a configurable threshold, a percentage of reduction is applied on the range (this value should be tuned from past experience data and depending on EV parameters). Also altitude was taken into consideration, using Google maps to obtain the altimetry of the desirable path, again several levels were configured, and also is applied a percentage of reduction in the range, in function of the altitudes to overcome in the path. Temperature is an important parameter, because of the relation with air-conditioning. The temperature was divided in five classes range: (1) less than 5°C; (2) from 5°C to 15°C; (3) from 15°C to 25°C; (4) from 25°C to 30°C; and (5) above 30°C. For classes 1 and 5 it was assumed that all drivers use air-conditioning, for class 3 no usage is performed, and for classes 2 and 4 it is considered that a percentage of drivers use air-conditioning (initial profile parameter, but past data can tune this behavior). Traffic

information is used again as a parameter that can reduce range, because possible starts/stops on traffic jams increase consumption. More information available at [Ferreira, 2013d].

3.10.2. Range Representation

Once a range prediction is achieved, a topographical search starts with the current driver position, based in Figure 3-20. Main road nodes are used to check distances from current position and a polygon representation is achieved (see Figure 3-21, Figure 3-22 and Figure 3-23) based on Google API usage. A zone of uncertainty can be marked, based on the uncertainty parameters used to estimate the drive range (see Figure 3-24).

If SoC level is below 25 % (available range should be around 30 km-40 km) it is calculated every road option with guidance to the nearest charging point. Taking into account Figure 3-20, it was considered Lisbon as the starting point. Since the available range for the EV is around 160 km, the implemented process starts to look for main destinations in a radius of 130 km to 160 km. This distance calculation is based on GPS coordinates of correspondent places. For Lisbon as the starting point, the process identified the following cities (Figure 3-20, process (2)): Pombal, Leiria, Marinha Grande, Ourem, Tomar, Évora, Grandola, Santiago do Cacém and Sines. Then, the distances are calculated based on Google Maps query (Figure 3-20, process (3)), and the process identifies that Pombal are out of the EV range. The distances calculated to the other locations are within the available range of the EV. For example, the distance from Lisbon to Évora is 134 km, so the process (4) (Figure 3-20) looks nearby villas, and process (5) (Figure 3-20), identifies the ‘real’ distance. In the case of the present example (Figure 3-21) and using the city of Évora as destination, it is available more 26 km, which allows increasing the range representation around Évora with a radius of 20 km (see Figure 3-22). The output of this iterative process is represented in Figure 3-21. For every 5 km of EV movement this map is again calculated and represented. The Web range estimator represents range by the connection of main distances and putting the polygon together. To do so, our application uses Google maps API and shows the polygon on a mobile device display, as showed in Figure 3-21, Figure 3-22 and Figure 3-23.




Figure 3-20: Range representation process using Google Maps API.



Figure 3-21: Range estimation of a Lisbon trip to north. Four different cases are showed.

For charging process the range prediction and representation is performed in the same way. Based on the charging level (SoC information) the application predicts the range based on previous driving parameters (past relations of SoC levels and distances achieved stored in driver profile) and based on this information represents using Google Maps the regions that is possible to reach with that charging level. System is prepared to generate alerts about charging levels needed to reach a charging station (it is assumed that a charging process is always performed in a charging station, in the driver's home or in the work place). The range prediction process has several uncertainty factors that reflect driving behavior and external condition (e.g. traffic, road topology and weather). These factors showed in Figure 3-19 can be used to estimate a safe range (green shadow in Figure 3-24) and a maximum range. The red shadow in Figure 3-24 is a range that is possible to achieve but the driver needs to perform driving optimization (air condition off and avoid big accelerations). This could be helpful information because driver can customize his behavior function of the range it needs to achieve in their trip. This process is can be continue updated and when SoC level is low this uncertain gets low.



Figure 3-22: Representation of charging range for different SoC levels at a charging process.




Figure 3-23: Range estimation with a low SoC level.




Figure 3-24: Range estimation based on the uncertainty factors showed at Figure 3-19.

3.11. Recommendation Engine and System

Given the success of recommendation systems in automatically delivering the relevant information in numerous areas of usage, it can be applied in this scenario as well, with the objective of maximizing the relevance of the information presented to the driver, which should be the strictly needed for him/her to make decisions, filtering out the unnecessary one, [Ferreira, 2011b].

Based on the available information, the information repository of the Mobi-System, the recommendation system will choose (recommend) the ‘right’ information, based on user pre-defined preferences expressed in a profile. This system uses n dimensions to calculate utility function (information relevance measurement) for all input information: user $D1$, information $D2$ and context $D3$. A diversity of recommendations is displayed. So, a

recommended function has a new dimension d (means context), and is a three dimensional vector $u(\text{User, Item, Context})$ (Figure 3-25):




Figure 3-25: Recommender System.

Input Information: Is the available information and represents charging places and other information related to EV driver. A recommender engine information module selects and stores all related information.

Profile Information – Historical Data: Represents past user options in a three dimensional matrix based on selected information. In our implementation this field has only two values: value 1 represents a user choice, and value 0 signifies user disagreement.

Context Information: Is used to improve recommender system performance, based on the fact that user preferences change based on the context. For example, in a tourism recommender system, the year period changes the user’s preferences, among others. Several authors, [Gediminas, 2005] and [Tuzhilin, 2001], suggest that context information is used based on a bi-dimensional space, (User, Information), in a multidimensional matrix, u (utility):

$$u : D_1 \times \dots \times D_n \rightarrow \mathcal{R} \quad [\text{Equation 1}]$$

Each D dimension is represented by an information vector and the algorithm to find the best tuple (d_1, \dots, d_n) , that maximizes the utility function [Gediminas, 2005]. Our implementation uses as context information based on four main types: (1) function mode: “leisure” or “direct”; (2) day period: “morning”, “afternoon” or “night”; (3) destination: “home” or “work”; (4) trip status: “starting” “middle” or “ending”. This information is

stored on information repository and is obtained by interaction with the driver, (1) plus (3), and (2) plus (4), by the system based on pre-defined rules. So, day period is pre-defined on system, morning is until 12 am, afternoon from 12 am to 19 pm, and night in the remaining hours. Trip status is based on target distance, the first 25% km are considered starting and the last 25% km are considered ending.

Recommender Information: Generates new system output information, ordered by a utility function. In this pre-release phase our system takes care of the charging point.

Each information type is represented by a vector, with class values. The PCSs (Public Charging Stations) are based on:

- Charging Mode: Slow, Fast and Drop-off;
- Operator: “MOBILE”, “Better-Place”, “EDP”;
- Location Type: “Street”, “Small Station” and “Big Station”;
- Services: “Without Services”, “Reservation”, “Washing Services” and “Others”;
- Public Transportation Interface: “1”, “0”;
- Nearby Points of Interest (POI): “1”, “0” – only if operator mode is on travel mode.

3.11.1. Utility (u) Calculation

User recommendation is based on utility function (u), where only three items are showed to the user (this is a configurable parameter). After distance measure is introduced (Manhattan distance, others could be implemented), it is calculated the utility based on context information, for each piece of input information, item I_i :

$$I_i = \{I1_i, I2_i, I3_i, I4_i, C1_i, C2_i, C3_i\} \quad [\text{Equation 2}]$$

Where $\{I1_i, I2_i, I3_i, I4_i\}$ are the characteristics of input information I_i and $\{C1_i, C2_i, C3_i\}$ are the context characteristics. The utility function is based on the nearest neighbor algorithm, see Figure 3-26, where it includes context and distance function. For details see [Pereira, 2010].




Figure 3-26: Nearest Neighbour Algorithm used to calculate the function u .

3.12. Conclusions

In this Chapter Mobi-System main EV functions were identified, taking into account the defined objective.

An information system to support V2G (Vehicle-to-Grid) or G2V (Grid-to-Vehicle) processes was created to assist EV drivers. This system takes transactions information from charging devices and is able to give charging or discharging commands. Due to the diversity of charging equipment and the lack of standards, an approach of XML files to data exchange was considered. This approach has been successfully implemented in several problems of data exchange in the computer area.

Regarding driving assistance with useful information, the following topics were covered:

- **Address user range anxiety:** (1) display SoC (State of Charge) level, remaining km for next charging; (2) looking for the nearest charging station (with guidance);

- **Drivers useful functions:** (1) give remote charging or discharging commands; (2) define a smart charging strategy taking into account home consumptions and contracted power limitation; (3) report about electricity transactions with pricing information; (4) give POI (Points of Interest) and guidance; (5) enable online advanced booking of charging spots with a penalty algorithm to avoid users failures; and (6) EV news.

Also, this Chapter was the basis for the project submitted to FCT, “EV-Cockpit: Personal Mobile System for Electric Vehicle Control” (PTDC/SEN-TRA/118302/2010), with the following partners:

- GuIAA Group (Information Systems Group);
- Daily Work, main expertise in vehicle-to-vehicle communication and telematics;
- Department of Electrical Engineering and Automation, and the use of VEECO vehicle as a case study. VEECO (*Veículo Eléctrico ECOLógico*) is a QREN project where ISEL is a partner;
- CEIIA, as a OEM partner and a case study on MOBI.E;
- GSI in INESC-ID, on information systems and mobile devices;
- Centro Algoritmi of University of Minho, main expertise in charging devices and Power Electronics.

The main project goal was to create a commercial product from these Chapter ideas in a mobile device, and to explore the EV data extraction through the communication standard CAN (Controller–Area Network).

4. MOBI-SYSTEM: ELECTRICITY MARKET FUNCTIONS

This Chapter reflects the initial work performed with the EV Aggregations (Section 4.1), the Microgeneration and the Distributed Energy Resources (DER) (Section 4.2), and the Collaborative Aggregator Broker System for DER (Section 4.3), and it is dedicated to the participation of EV in the electricity market and the integration with local renewable energy resources.

4.1. EV Aggregations

EV behavior can be quantified in a user profile, like time of trip, travelled distance, daily hours connected to the grid and minimum energy stored. These profiles can be clustered in communities by a similarity measurement (taking into account the trips time), and also by the identification of the electrical distribution network mapped in a graph (see Section 3.7). This graph geo-reference points correspond to end users locations and low voltage distribution points. The biggest problem of this approach is the work involved in the identification of geo-reference of each of these points. Having collected this information any geographic database can easily handle the problem.

The basic idea behind such community is the aggregation of the EV (Figure 4.1) taking into account the electrical distribution network represented in a geo-reference graph, so that together they represent a load or a resource of a size appropriate to exploit economic opportunities in the electricity markets. The created community is a new player whose role is to collect the EV (profiles) by attracting and retaining them, so as to result in a megawatt capacity that can beneficially impact the grid. This impact is even bigger, because we take into account that the electrical distribution network minimizes losses of energy transmission and distribution. The size of the community is indeed a key to ensuring its effective role (100 EVs of 24 kWh can store 2.4 MWh, and around 300 EV of 24 kWh can reach 7.2 MWh). In terms of load, a community of EVs represents the total consumption of all vehicles, an amount in megawatts that constitutes a significant size, and allows each EV to benefit from the buying power of a large industrial/commercial customer. There are additional economic benefits that grow as a result of the economies of scale. The aggregated collection behaves as a single player that can undertake transactions with considerably lower transaction costs than would be incurred by the individual EV owners.

It is the role of the Aggregator to create and manage the community behavior by determining which EV to select to join the community, and by establishing the optimal deployment of the community. A single community may function either as a controllable load or as an energy resource. We first discuss the EV community utilization as a controllable load and then as a generation/storage device.




Figure 4-1: The EV community may act as a controllable load or as a generation/storage Device.

First, the larger scale of the aggregated V2G power resources commanded by the Aggregator, and the improved reliability of aggregated V2G resources connected in parallel, allows the electrical grid system operator to treat the Aggregator like a conventional ancillary services provider. This allows the Aggregator to utilize the same communication infrastructure for contracting and commanding signals that conventional ancillary services providers use, thus eliminating the concern of additional communications workload placed on the grid system operator.

In the longer term, the aggregation of V2G resources will allow them to be integrated more readily into the existing ancillary services command and contracting framework, since the grid system operator need only to communicate directly with the Aggregators. The communications infrastructure of the Aggregator (central server) and the vehicles is a standard communication system, using available technology (Wireless, GPRS, Wimax, among others). Since there are no standards defined among EV infrastructure, the data exchange was performed on the Internet standard XML. This approach allows picking and giving information from different proprietary systems, since they provide and interface

with XML data exchange. This Internet standard facilitates the application of data mining approaches to extract relevant information from the past experience (previous transactions performed).

User Profile is defined by: type of EV (this feature characterizes the battery size), minimum SoC allowed, time and date of trips (working days and weekends), geographic data, personal data and log files of energy received or dispatched, and time intervals of the grid connection. Most of this information can be acquired (without costs) if the drivers run a tracking application in an offline mode (only transmitting the information when a wireless communication is available) in a mobile device.

Aggregation is based on geographic distribution, taking into account the distribution of transportation lines and power stations, in a semi-automatic process. The system calculates the power available in a circular distance of a pre-defined point.

Aggregated EV has the potential to play a very important role in improving system operations both on the demand and on the supply-side. However, there is a huge variability in the behavior of the individual EV owner. This variability is a challenge for the Aggregator in order to assess the size of the resource available from the community EV. In order to study the impacts of such variability, we develop a modeling approach for the EV community.

A community of EVs can act as an effective distributed energy resource once it is interconnected with the distribution grid. However, we must keep in mind that the principal utility of EV is to provide clean and economic transportation to their owners rather than to generate electricity for grid operations. As a result, the aggregated EV may not always be plugged into the grid. Since EVs may travel different distances every day, they may have different levels of energy stored in their batteries any time they become interconnected to the grid. The community of many EV serves to smooth out such heterogeneity and to make the aggregated entity behave in a more homogeneous manner. The time dependence of EV travel may impact the level of participation of an individual EV to the load and the generation/storage device roles of the community. The variability in the contribution of each EV to the community creates considerable uncertainty in the capability of the community to act as a resource at any point in time.

Due to the personal preferences of each EV owner, the Aggregator cannot know with certainty the individual EV owner schedules and the amount of energy stored in each vehicle's batteries when the EV gets plugged in. Mobi-System analyzes the nature of this uncertainty and constructs an appropriate model under a set of reasonable assumptions. Mobi-System deploys this model to simulate the impacts of an EV community as a load and as a generation/storage device.

The principal sources of uncertainty for an Aggregator are: (1) the duration of the periods during which each EV in the community is connected to the grid; (2) the distances travelled by each EV; and (3) the SoC level of each EV at any point in time.

We propose an intelligent system based on agents' approach, to support the community and to achieve a predefined performance. To analyze the nature of the resulting uncertainty, we need to introduce assumptions to allow quantification of the resulting randomness. Specifically, we limit our analysis to the following set of assumptions:

- Losses in the EVs batteries are neglected, because the losses due to conversion efficiency in the charging stations, or in the EV batteries, or due to transmissions losses, are small – less than 10%;
- The storage capability of each EV battery remains unchanged during the study period, and it is a known quantity based on the car model;
- Parking lots have big capacities;
- EVs are always plugged in when they are parked;
- Charging stations and outlets at a particular location do not have any power limitation and are adequate for the EV which gets plugged in at this location.

4.1.1. Aggregator System Main Modules

The Aggregator System main modules are identified in Figure 4-2:

- **V2G System:** Is the system that controls the EV and PHEV connections to the power grid.
- **Users' Profile:** Is the module that interacts with the user, and is divided in the following modules: user registration module, user communication interface, and user profile. The user registration module is the responsible for detecting if the user is a registered user or not. If so, it shows its information, the number of credits that he/she has, allows him/her to change personal data and driver profile, making

suggestions, and also allows buying more credits. If it detects that the user is not a registered one, it asks for the registration. The user communication interface formats the information for the end-user device (e.g., PDA, mobile phone). The size of the information to be transmitted depends on the communication bandwidth and on the visualization capacities of the end-user device.

- **Aggregation:** Is the process of community creation by the selection of users. For the aggregative architecture, the Aggregator's ability to enter into contracts with the electrical grid system operator is independent of any individual vehicle's presence at the charging station. Because the Aggregator can vary the size of its power contract when fewer vehicles are present at charging stations, it is available to bid for ancillary services contracts at any time of day or night. This function identifies EVs in predefined areas (community areas) and identifies available distribution power in a week. Historical data is analyzed (basic statistics functions are applied to time values) to determine safety values for electrical energy markets contracts.
- **User Credits:** This module tries to measure the users' participation towards the common goal of the community.
- **Agent System:** The Aggregator system receives ancillary service requests from the grid system operator and issues power commands to contracted vehicles that are both available and willing to perform the required services. Under the data mining of available past data as community capacity aggregative architecture, the Aggregator can bid to perform ancillary services at any time. From the available power in community (based on plugged EVs) the Aggregator bids into the hourly ancillary services market, and compensate the vehicles under its control for each minute that they are available to perform V2G. As such, this aggregative architecture attempts to address the two primary problems with the direct, deterministic architecture. We need to determine a good distribution algorithm to extract electricity smoothly from all available EVs.
- **Transitions Record:** All transactions between EVs and the electrical power grid are stored in a database. This information would give a better insight into limits to charge/discharge which, in turn, would allow understanding the users' behavior. To keep user data privacy, the data is stored without a direct relation to the user.




Figure 4-2: Main modules and interfaces of the V2G Aggregation system.

Different communities should be established (when the number of EV increases), mainly in function of their geographic location, and created based on the electrical distribution networks, in order to avoid investments or charging overloads. This community should follow pre-defined rules implemented by the Central Grid Operator, Figure 4-3.




Figure 4-3: Aggregation hierarchy.

4.1.2. Managing User Behavior

Drivers express their behavior in a profile. Based on user's profile, the system calculates community aggregation efficiently based on individual data aggregation. However this pre-defined data will have changes due to unexpected situations, like failures, among others. Community goals are defined with a good failover gap, but system should manage the user behavior towards a common goal. For that, it is proposed in this work a novel approach based on the stock exchange metaphor, illustrated in Figure 4-4. This idea has been used in a collaborative system [Silva, 2007], [Ferreira, 2010]. The main idea is to promote a health environment, where users look for a common goal and this effort is converted in credits mechanism that can be converted in money. The system looks for users' data and transactions performed to identify critical hours (when less EVs are connected). This analysis divides time in several periods. In this work it was proposed 5 periods: (1) night

period, when more than 99% of EVs are plugged; (2) when 99% to 90% of EVs are plugged; (3) when 75% to 90% of EVs are plugged; (4) when 75% to 50% of EVs are plugged; (5) critical period, when less than 50% of EVs are plugged. The tracking system was used to associate time to these periods. Credits are based on the time intervals in which the EVs are connected, on the power available for the market, on the energy delivered back to the electrical grid, and on time criticality (in our case, based on the criteria described above) for community goals.




Figure 4-4: Proposed credits mechanisms.

Users' failures are measured by the unexpected changes on the time that EV should be plugged (defined by the user in their profile). These failures, if not reported to the Aggregator system before, are penalized with loss of credits. If the user replaces automatically his failure by other user, no penalty is applied. If the failure is not reported previously, the system penalizes heavily this behavior and forwards the failure report in order that the system finds a solution. An important research issue is how to implement the

right credits mechanism. This collaborative environment can be applied for charging processes of the EVs, where users help each other to find the cheaper price.

4.1.3. Collaboration Features

Users can also interact and collaborate among themselves to improve their knowledge, or by allowing them to express their needs and preferences. The features presented below are created to keep users informed, motivated and with intention to collaborate more frequently:

- **Punctual Changes on User's Plugging Time:** Users that identify in advance changes to their committed plug-in time can find a substitute among community members, avoiding system penalties.
- **Cooperation Area:** An area where users can ask questions or provide different kinds of knowledge to cooperate in EV related area. For example, one user that is good in dealing with information resource tools could provide prices and other helpful information to others, but if he knows nothing about the batteries or EV working processes, he can ask any user if they want to cooperate with him.
- **Helping Area:** An area where users can post questions and answers and some sort of help on any topic. This space could be accessed and viewed by any registered user. System gives credits to users that provide good helping answers to posted questions.
- **Abuses or Faults Reporting Area:** An area provided to report abuses of different kinds, like comments or bad use of the system. The system manager can penalize users for it. The reason for providing this area is essentially for discouraging users to commit abuses or faults.
- **Request:** An area where users can ask for specific questions. The system manager can use those requests to tune the community.
- **Awards:** Created in order to promote and recognize outstanding behavior (for example, no changes in the profile). The awarded users receive extra credits.
- **Community Newsletter:** The system manager publishes a digital newsletter with community information and EV related information.
- **Users Rankings:** Users rankings are created to represent the most valuable collaborators, calculated by adding all credits earned by each user.

- Alerts Subscription: Users can subscribe different kinds of alerts: notifications, comments, or other EV interactions.

4.1.4. Simulation Results Towards Aggregation of Available Electrical Power

To have some results regarding the proposal aggregation approach it was used data from tracking system (trips time and distances), and based on EV efficiency, it was estimated the remaining battery energy of each EV (SoC – State of Charge level). Based on these individual parameters it was achieved the community SoC level (sum of all individual community SoC levels). The studied population (from Lisbon area), with 50 cases, contains a mixture of ISEL (Lisbon Superior Institute of Engineering) students and their parents. In Portugal, the Nissan Leaf was introduced to the market with a 24 kWh battery pack and autonomy of 160 km (value considering a careful driving style). Once there is a diversity of EVs, with different energy storage capacity of the batteries, it was assumed that in average each EV has 15 kWh of energy available for the electrical energy market (each EV owner can choose the battery type of his vehicle from a pre-defined list, and define the value of energy to be available for the electrical market), and that during working hours only 75% of EVs are plugged.

From tracking data it was identified three main time intervals, with different profiles regarding energy consumption or availability: (1) From 19 h to 23 h (return home and home peak consumption hour). In this period test community have around 2 MW-h of available energy (the minimum community available energy is reached in this period). In this case it was assumed 1.5 MW-h as a safe value for the energy market. (2) From 23 h to 7 h (EV batteries charging period at home). Maximum community available energy is reached in this period, after the charging process of EVs is finished. (3) From 7 h to 19 h (Remaining hours – travel home-work, EVs plugged at work place, and travel work-home) Assuming that 75% of EVs are plugged, it has a community available energy ranging from 3 MW-h to 4 MW-h. These charging profiles were created through clustering data on a excel graph, presented in Figure 4-5. For more information see [Sousa, 2010], [Ferreira, 2010a].




Figure 4-5: Electrical power available during day for 500 EVs³³ of 15kWh of energy stored in batteries.

4.1.5. Power Market Community Revenues

Main power markets for EVs and PHEVs are Regulation and Spinning Reserve (SR). Regulation is contracted and paid for the available power capacity at any one hour, with a separate and typically much smaller payment for the amount of energy provided. This means a generator sitting idle with the ability to provide regulation is paid the same capacity payment as the generator that was called upon to provide regulation. SR is the generation capability that can provide power to the grid immediately, and reach full capacity within 10 minutes when called upon by the ISO/RTO (Independent System Operator / Regional Transmission Organization) [Kempton, 2009]. This power must be provided by equipment electrically synchronized with the electrical grid. Typically, requests for this generation to provide power are made around 20-50 times a year [Kempton, 2009].

Major economic advantages for EV and PHEV comes from Regulation, because prices in average are three times higher than those obtained with SR, and in addition, the cycling of the storage device is much more frequent for Regulation than for Spinning Reserve. Regulation is controlled automatically, by a direct command from the grid operator (thus the synonym “automatic generation control”). Compared to Spinning Reserves, it is called

³³ Taking into account the movements identified with the tracking system.

far more often (for instance, about 400 times per day), and requires a faster response (less than a minute), and is required to continue running for shorter durations (typically a few minutes at a time) [Kempton, 2005]. The actual energy dispatched for Regulation is some fraction regarding the total power available and contracted for, since the time in which power is delivered is very small. We shall show that this ratio is important to the economics of V2G (Vehicle-to-Grid), so it was defined the “dispatch to contract” ratio as:

$$R_{d-c} = E_{disp} / (P_{contr} \cdot t_{contr}) \quad [\text{Equation 3}]$$

Where R_{d-c} is the dispatch to contract ratio (dimensionless), E_{disp} is the total energy dispatched over the contract period (MW-h), P_{contr} is the contracted capacity (MW), and t_{contr} is the duration of the contract (hours). R_{d-c} is calculated separately for regulation up or down. Kempton, in [Kempton, 2005], uses a value of 0.1 for R_{d-c} . Based on previous studies of Kempton and Tomić [Tomić, 2007], and taking into account \$30 MW-h for Regulation services and \$10 MW-h for Spinning Services, it has the following revenues, presented in Table 4-1, for United State power markets. These values are calculated in an individual basis, but in a collective approach they should increase, mainly the SR values.

Table 4-1: Annual Revenue of EV and PHEV in the Electricity Market³⁴ [Tomić, 2007].

	Regulation	SR	Total
2 kW	400	100	500
6 kW	1200	300	1500
10 kW	2000	500	2500
15 kW	3000	700	3700

³⁴ Values are given in US\$, assuming that vehicles are plugged in 80% of the time around 7000 hours in a year.

4.2. Microgeneration and Distributed Energy Resources

Microgeneration study is out of this thesis scope, but due to a large synergy that can be established between microgeneration and EV, this Section is dedicated to this subject. Part of proposed approaches can be reused for this topic. This is part of a new reality of Distributed Energy Resources (DER), as part of intelligent power systems to construct a hybrid, fundamentally different architecture for an ICT-network, enabling the power grid to flexibly accommodate novel devices or clusters of devices. Several initiatives are taking place on this topic: (1) Intelligrid [Dolle, 2009], a program in the United States executed by EPRI; (2) Gridwise³⁵; CRISP project [Andrieu, 2005]; (3) European initiative under the program EU_DEEP-project³⁶ and the activities; and (4) IREDcluster³⁷. As described in various articles in literature [BenHabib 2006], [France, 1986], there are many implications for the grid when making a transition from centralized to decentralized control with merely some central coordination. When compared to hierarchically operated electricity grids, with power centrally generated at high voltage levels on a large scale, delivering electricity to consumers on lower voltage levels in the network, SG [Thanh, 2008] offer a number of challenges for technological research. Our work proposes the creation of a collaborative broker system to handle EV and microgeneration integration on electricity market, supported by users collaborative process, transaction data integration and central information repository knowledge, where it stores past experience to help on solving problems such as:

- The excess of energy produced by microgeneration should be distributed locally (to avoid transmission losses) to the EVs (that can act as storing devices) or to consumers, minimizing the use of the transmission and distribution networks. In this context, arise the Energy Storage Systems (ESS), which can store the excess of energy produced by microgeneration, and deliver this energy when it is necessary, and that includes the EVs. These ESSs are controlled by the broker.

³⁵ Information available at <<http://www.gridwise.org>>.

³⁶ Information available at <<http://www.eudeep.com>>.

³⁷ Information available at <<http://ired2.iset.uni-kassel.de>>.

- The price of the electricity should be determined taking into account the production capacity, because the microgeneration is based on renewable energy sources with different profiles of production.
- The interaction between the microgeneration and the consumers should be implemented taking into account a maximization strategy to the user. To obtain a good contribution of electrical energy to the electrical power grid by the microgeneration producers, the electricity market should implement attractive benefits to buy or to sell. The control of energy flow between microgeneration producers and the electrical grid, taking into account the electricity market, the consumers and the sellers, is coordinated by the broker.

The proposal central information repository can store and manage historical data on electricity consumption and production. From this central repository it is possible the development of tools to extract knowledge from past electricity exchange log files, electricity market prices, renewable energy availability and capability, consumed or delivered energy if EV is plugged at home, and electrical distribution network constraints. Also, the social networks are integrated as a tool to share and spread useful related information. This central repository will be later in a Smart Grid environment, a fundamental module to store all kinds of SG data and to solve the problems of different data format diversity.

4.2.1. Microgeneration and Micro Grids

Nowadays, the microgeneration emerges as a necessity to reduce the greenhouse effect caused by pollutant sources of energy. However, associated with the electricity market and the increasing in the technological development, the microgeneration of electrical energy has a great potential to the consumers, and to the distribution grid.

The main sources of energy in a microgeneration are the wind and the sun, and the electrical energy is obtained from micro wind turbines and solar photovoltaic panels. These sources of energy are the most common and the easier to implement in microgeneration facilities. Presently, this produced energy is provided to the electrical power grid without any concern about the electricity market or the electrical power grid capability to receive energy. In a Smart Grid context with Energy Store Systems (ESSs), like batteries, EVs, ultracapacitors

or flywheels, the energy produced in excess from the microgeneration can be stored in these systems. Posteriorly, this stored energy is used to help the electrical power grid, taking into account:

- **The energy produced by other sources of energy.** When it is required to provide a great amount of energy, as during EV fast charging, this energy can be delivered from the ESS. It is also important to provide energy to the electrical power grid in transitory moments, as during consumers' consumptions peaks.
- **The electricity market.** It is very important to the EV owners to buy or to sell electrical energy with the best price possible. EVs plugged in conjunction with microgeneration have the potential of charging the batteries when there is available energy from the microgeneration production, and of discharging part of the energy stored in the batteries, until a maximum value allowed, when the electrical grid demands energy (during a registered peak of consumption in the grid). This is why the Vehicle-to-Grid (V2G) has a fundamental role in a Smart Grid.

In this context, from the point of view of the electrical power grid, with the proximity between the microgeneration and the consumers, there are reduced flows of power along the transmission and distribution lines, and consequently, the losses are lower. With this proximity, encompassed in the microgeneration, the possibility of failures occurrence is reduced.

4.2.2. Distributed Energy Resources and the Energy Markets

Distributed Energy Resources (DER), small-scale power generating technologies close to energy loads, are expected to become an important part of the future power system. Microgeneration and EV will play an important role in this process, and nearby community will use the power made available by them, because the electrical distribution network allows it. Since distributed energy resources are installed near the loads, they are likely to be installed on low-voltage distribution systems. The distribution systems also account for the higher percentage of system losses compared with the higher voltage transmission systems, thus, local production of energy by EV and microgeneration causes an improvement on the overall efficiency of the system. DER has the problem of variability

(changes in production and consumption of energy), uncertainty (supply contingencies) and unpredictability (renewable generation depends on uncertain weather conditions).

Main important fact is that EV can store local microgeneration production excess and users' can tune their consumer behavior in part based on microgeneration production, i.e., they can develop a collaborative process based on energy production information, so that they can start/stop washing machines and other equipment that do not have an obligatory time constraint.

The energy market has historically been monopolized and governmentally regulated because of its utmost importance. Like water, energy is essential for life and firm grip on it was a logical choice of policy makers. With general globalization, such monopolized, nontransparent and market detached approach has become economically and politically unacceptable. To leave political influences aside, as they surpass the scope of this thesis, it is important to state that global economic development demanded a change. Despite the efforts to save energy and use it as rationally as possible, which are getting more serious every year, the energy consumption is inevitably growing. This is especially significant as the large part of the world is starting its development, and large countries, as China and India, are demanding their share of life standard. New stakeholders appear in this new open market: (1) A broker of electrical energy services is an entity or company that acts as a middleman in a marketplace in which those services are priced, purchased, and traded. A broker does not take title on available transactions, and does not generate, purchase, or sell electric energy but facilitates transactions between buyers and sellers. If a broker is interested in acquiring a title on electric energy transactions, then it is classified as a generator or a marketer. A broker may act as an agent between producers, or an aggregation of generating companies, and marketers; (2) An Aggregator is an entity or a company that combines customers into a buying group. The group buys large blocks of electrical energy and other services at cheaper prices. The Aggregator may act as an agent (broker) between customers and retailers. When an Aggregator purchases power and re-sells it to customers, it acts as a retailer and should initially qualify as a retailer. Our collaborative system has the function of these two entities.

4.3. Collaborative Aggregator Broker for DER

Our investigation proposal is to bring computer science work on software development, Web 2.0, geographic information systems, mobile computation and wireless communications, to create a system to support DER (Distributed Energy Resources) energy exchange, defining local prices and coordinating energy exchange from local community to big producers. The main modules of the proposed system, illustrated in Figure 4-6, are:

- Central Information Repository, that stores information about: (1) user energy consumption (amount and time); (2) energy production with available information of power; (3) energy supplier and source (e.g., hydropower, wind power, photovoltaic, etc); (4) energy prices; and (5) weather information (temperature, wind direction and speed, rain amount, solar radiation, etc). A proper interface is created for user profile, creation and manipulation. This information data is worked under data mining approach for consumption data analyses. We implemented a weather crawler, based on a web robot, to pick weather information from pre-defined sites and store this information on this information repository. Community creation is based on clustering available user profiles, based mainly on geographical position.
- Information Communication Tools (ICT), those mainly are: communication networks for information exchange; and high-speed digital monitoring, to take care of energy transactions.
- Smart meters, to measure local energy consumption and production, and Mobile Application, an application to run on a mobile device (like PDA or iPhone) to receive and send control information for charging the EV batteries and also for system interaction.
- Geo-reference graph based on electrical distribution network (a description of this is found in [Ramada, 2010]).
- A collaboration software tool, that has as goal to help people involved in a common task. It allows several independent computers working together, through an Internet connection. In a Smart Grid context it is very important to establish patterns related to the produced and consumed energy from microgeneration and the profiles of the consumers.
- Energy Market functions.

- Power Quality monitoring.




Figure 4-6: Main modules of the Collaborative Aggregator Broker system.

4.3.1. Repository of Information, Weather Information and Data Mining

A deterministic approach to forecast microgeneration production is complex, because wind power depends on the type of turbine, location (urban versus rural), height, orientation and wind speed. In solar photovoltaic generation the power generation depends on the environmental factors, mainly the irradiation and the cell temperature. Each case should be analyzed and this should raise a complex scenario. A renewable production prediction is achieved based on data mining approach, where past stored production data is used with weather forecast (e.g., wind speed and direction, temperature and weather condition) to predict microgeneration production. For this task a database is used to store all transactions data (EV charging and discharging and also microgeneration production), weather information and user profile information. Several approaches using data mining algorithms can be used for knowledge extraction: past transactions data can be used to try to identify, with clustering approaches, main periods of consumption and production, and trends with the identification of the main behavior. We implemented a weather crawler, based on a web robot to pick weather information from pre-defined sites (in our case, a Portuguese weather site). Details on this can be found at [Ramada, 2010], [Ferreira, 2010a] and in Figure 4-7, that shows examples of information for wind and temperature. Also by manipulating available data it is possible to create several reports, like: home energy consumptions,

weekly, monthly and annual energy expenses, price variation of electricity, and charging periods, among others.

Latitude: 40° 08' 30" N Longitude: 08° 52' 42" W Profundidade: 9 m

Data		Mar total (m)	Ond. (m)	Dir. ond.	Vaga (m)	Vento (nós)	Dir. vento	Sets	Temp.Água (°C)
2011-07-29 (6 ^a feira)	H00	1.1	0.5	→	1.0	15.6	↓		15.4
	H06	1.0	0.4	→	0.9	13.6	↓		15.4
	H12	0.9	0.3	→	0.8	9.7	↓		15.5
	H18	1.0	0.3	→	0.9	17.5	↓	*	14.5
2011-07-30 (sábado)	H00	1.1	0.3	→	1.0	19.4	↓	*	14.5
	H06	1.1	0.3	→	1.1	19.4	↓	*	14.5
	H12	1.1	0.3	→	1.0	17.5	↓	*	14.5
	H18	1.1	0.3	→	1.1	21.4	↓	*	14.5
2011-07-31 (domingo)	H00	1.2	0.3	→	1.1	21.4	↓	*	14.5
	H06	1.1	0.3	→	1.1	19.4	↓	*	14.5
	H12	1.0	0.3	→	1.0	15.6	↓	*	15.5
	H18	0.9	0.2	→	0.8	13.6	↘	*	15.5
2011-08-01 (2 ^a feira)	H00	0.8	0.2	→	0.8	15.6	↓		15.5
	H06	0.8	0.2	→	0.8	15.6	↓		15.5
	H12	0.7	0.2	→	0.7	11.7	↓		15.5
	H18	0.7	0.2	→	0.6	11.7	↓		15.5
2011-08-02 (3 ^a feira)	H00	0.7	0.2	→	0.7	13.6	↓		15.5
	H06	0.7	0.2	→	0.7	13.6	↘		15.5
	H12	0.6	0.2	→	0.6	7.8	↘		16.6

Figure 4-7: Wind effect and weather information³⁸.

A Naïve Bayes (NB) classifier can be used to relate consumption and microgeneration production to weather information (temperature, wind speed and direction, and also humidity, with raining information), and a small example is shown in Table 4-1. Production capacity is divided in n classes (a configurable number, gotten from clustering analyses of past data). In our implementation $n = 10$, and classes are defined based on percentage of production capacity: class 0 is zero production, class 1 is performed from 0 to 10% of production, and in class 10 it is reached maximum production (100%). Wind and temperature were also discretized in a pre-defined class. Time is also a discrete variable. In our example we simulate one day that have only one class (corresponding to all

³⁸ Data based on windy and temperature taken from a weather site <<https://www.ipma.pt>> for Lisbon (information in Portuguese language).

consumption and production in a day), but in a real case more classes should be added. In the literature several authors divide the hour in 20 to 10 minutes events, so the number of classes goes from $3 \times 24 = 72$ to $6 \times 24 = 144$. Wind speed and directions are correlated to pre-defined classes that characterize local Eolic production, and temperature is divided in interval classes. Wind production capacity was divided in 7 classes (0 to 6), (see Figure 4-7), and temperature in 5 classes (1 to 5). Renewable energy production from Eolic is more dependent on wind speed, than energy production from solar photovoltaic is dependent on solar radiation.

Since temperature and wind speed are continuous variables it was performed a discretization by the division of values into pre-defined classes. The number of classes introduced is a configurable parameter. Table 4-2 shows a small example on how a NB algorithm works, showing the occurrence probability of an event. In this case we want to know the expected production taking into account the forecast of sun and temperature and wind values in the range of pre-defined class 2. Based on historical data (in case 10 events) NB shows the probability for $p1$ to $p10$. For more details see [Ramada, 2010] and [Ferreira, 2013]. From this particular case of renewable energy production capacity based on current approach, $p3$ and $p4$ have highest probability. Assuming an installed capacity of 3 kW this means under these conditions that the renewable production is around 1 kW.

Table 4-2: NB (Naïve Bayes) classifier approach for a small example.

Day	Weather	Temperature	Wind	Production
1	Sun	2	3	3
2	Cloudy	1	5	4
3	Rain	4	1	2
4	Sun	5	4	9
5	Sun	3	2	4
6	Rain	1	2	1
7	Cloudy	3	2	2
8	Cloudy	4	6	5
9	Rain	3	3	3
10	Sun	3	2	4
11	Sun	2	2	???

$$P(\text{production}) = 0.1 \text{ (10 classes)}$$

$$P(\text{sun}|p3) = 1/2 \text{ (appears one in two examples of P3)}$$

$$P(\text{sun}|p4) = 2/3 \text{ (appears two in three examples of P4)}$$

...the same for the others examples

$$P(p1|\text{sun} + T2 + W2) = P(p1) \times P(\text{sun}|p1) \times P(T2|p1) \times P(W2|p1)$$

$$P(p2|\text{sun} + T2 + W2) = P(p2) \times P(\text{sun}|p2) \times P(T2|p2) \times P(W2|p2)$$

...

$$P(p10|\text{sun} + T2 + W2) = P(p10) \times P(\text{sun}|p10) \times P(T2|p10) \times P(W2|p10)$$

4.3.2. Energy Market and Smart Grid Integration

Energy market participation will require a detail control about electricity flow, and registered users would like to control charging or discharging processes, in association with the electricity prices. These prices are depending on the electrical energy supplier and time, and local broker picks from a pre-defined server on a standard XML file. Related to the microgeneration the main function is to manage the produced and consumed energy in conjunction with the needs of the consumers.

In this scenario, in Figure 4-8 is shown an electrical power grid with: solar photovoltaic panels (which only produce energy), micro wind turbines (which only produce energy), EVs (which can receive or provide energy), and energy storage systems (which, like the EVs, can receive or provide energy). Beyond the flow of energy between these parts, there is also the sharing of information, controlled by the collaborative broker. Also in this figure are shown the blocks of the Maximum Power Point Trackers (MPPTs) (for the solar photovoltaic panels and micro wind turbines), and the blocks of the AC-DC and DC-AC converters to adjust the levels of the voltages and current between the parts.




Figure 4-8: Integration of microgeneration, EVs and ESSs in an electrical distribution network controlled by a broker.

4.3.3. Collaboration Tool

This is a tool for the users, based in two main characteristics:

- The batteries of the EV: the technology of the batteries (if Lead-Acid, Nickel or Lithium), the energy storage capacity of batteries in kWh; the characteristics of the batteries for receiving and delivering energy, taking into account different rates of charging or discharging; and the SoC (State of Charge) and SoH (State of Health) of the batteries.
- The utilization of the EV: considering the profile of the user and of the community; important characteristics, like the data and the time of the travels, and the distance planned to be travelled, which is particularly important to define the energy that the EV owner can sell, or the energy needed to charge the batteries in fast charging mode.

How does a group of interested stakeholders collaborate to create real-world DER (Distributed Energy Resources) pilot programs that benefit multiple stakeholders? The following lines outline important questions to address and steps that can be taken towards

a common goal. In a Smart Grid scenario, there must be a collaborative process between electrical power grid, EVs, microgeneration and the Electricity Market. In this collaboration, the distribution network uses the shortest path (with less impedance) to deliver energy production excess, and EVs, if available, can store this local production excess. If the electrical grid does not have local EVs, the network can deliver to the nearest neighbor EVs, establishing a collaborative process. Also if EVs SoC (State of Charge) is above drivers' requirements, homes at neighborhood can take EVs energy. Non critical equipment (e.g., washing machines and others) can be started when there is a local production excess. Recording data can show periods of low consumption and the operation of these equipment can be scheduled these periods (in a Smart Grid it is possible to start the operation of equipment taking into account real time information). This collaboration is controlled by the central broker, for accounting purposes, and the price is established according to local production and local demand. The system will work always practicing better prices than the ones of big electrical energy distribution companies, and will always try to minimize energy transitions outside the community. The community is mainly defined by the electrical distribution network topology, that could be reached and controlled by a collaborative broker, and the energy can flow in different ways, as shown in Figure 4-9.

As previously said, the flow of energy is controlled by the central broker. This control is useful in many aspects, mainly when the users have capability to produce energy through microgeneration, but the electrical power grid does not need to receive energy. In this scenario, with the collaboration within the different parts in the Smart Grid, the energy produced by microgeneration can be distributed to EVs or to other home consumers. This distribution of energy should take into account the production and sale costs. Prices should change based on production capacity and energy needs. So the prices of electricity vary in time, but for that a measurement capability should be available at the consumer's side. These meter devices have as only inconvenience their high cost. If the price of electrical energy varies significantly during time periods of the day, customers can respond to this price variation structure with significant changes in energy use, reducing their electricity bills if they adjust the timing of their electricity usage to take advantage of lower-priced periods and/or avoid consuming electrical energy when prices are higher. Based on energy price, customers' load use modifications would be entirely voluntary. Market based

solutions also give solid background to develop new business opportunities, for example, to Aggregators. The main obstacle to introduce more price granularity at consumer's level is the cost of installing and monitoring the electrical energy meters that allow remote data acquisition.




Figure 4-9: Energy flux in an electrical distribution network with microgeneration, EVs and ESS.

4.4. Conclusions

In this Chapter Mobi-System main energy market functions were identified, taking into account the defined objectives. On electricity market functions, the main systems developed were: EV Aggregator, EV community creation, and the collaborative broker for DER.

EV Aggregator is the main contribution, where is proposed one system to create and manage the EV community, with a credit-based approach that can be converted into money to incentive user's participation. In the author's point of view, the use of this credit-base system, together with rankings, promotes an open and healthy competitive environment. Also, in the future, to increase the market share of EV and PHEV, there is a need of these

types of systems to explore the energy market potential of these types of vehicles. Also, renewable energy sources integration can benefit from a community coordination action, where users can capture renewable energy produced in excess at lower prices. This work was presented in the Conference EVS-25 (The 25th World Battery, Hybrid and Fuel Cell Electric Vehicle Symposium & Exhibition), in China, last November 2010, and the collaboration with the American company ElectronVault was initiated. This cooperation can be on a module of ElectronVault system for EV, where community identification and collaborative work could increase the package attractiveness.

5. MOBI-SYSTEM: SUSTAINABLE MOBILITY FUNCTIONS

In the European Union (EU), over 60% of the population lives in urban areas (information from Eurostat), and thus, air and noise pollution are getting worse each year. Urban traffic is responsible for 40% of CO₂ emissions, and 70% of emissions of other pollutants arises from road transport [Paper, 2007]. Increasing traffic in town and city centers is responsible for chronic congestion, with the many adverse consequences that this entails in terms of delays and pollution. Every year nearly 100 billion euros, or 1% of the EU's GDP [Paper, 2007], are spent by the European economy to deal with this phenomenon. Several solutions have been proposed to these problems, such as a diversity of intelligent transportation systems and solutions.

Transportation systems have witnessed significant advances in the past decade, such as, improved traffic monitoring and control systems, new vehicles with higher fuel efficiency, and on-board devices with navigation capability based on the Global Positioning System (GPS). These and other technologies have had a very direct and positive impact on human mobility, quality of life, trade, employment, global supply chains and territorial cohesion.

In most European cities, travelers can choose among different modes of transport, including private vehicles, taxis, railways, buses and other forms of public transportation. However, providers of transportation services operate independently, rather than collaborating in a holistic fashion. In such an uncoordinated setting, travelers are in charge of planning their own travel route and are typically unaware of the current conditions of the various transportation networks at a given time of day. In addition, travelers are often unaware of the exact monetary costs and of the environmental impact that a certain mobility option may incur. All of these factors add to the lack of attractiveness of public transport and risk of inefficiency in today's transportation systems.

EVs that are presented to the market nowadays have a reduced autonomy range when compared with traditional internal combustion engine vehicles, mainly due to the significant lower energy density of current batteries used on these types of applications. Vehicle designers and Original Equipment Manufacturers (OEM) must balance the size of the battery pack in the vehicle with its weight and its price, in order to get a final solution that the market may accept through a compromise of vehicle cost and available autonomy. In fact the battery pack is the main component that dictates the higher vehicle price and the

lower autonomy when compared with internal combustion engine vehicles. This lower autonomy and the significant higher time required to charge the vehicle batteries (in normal mode it takes usually from 6 to 8 hours, and in fast charging it usually takes about 30 minutes) limits the distance that each driver is able or is comfortable to drive, without reaching the battery end of charge. All this limitations and use constraints are reasons for EV to have a small acceptance in the market.

Mobi-System develops a solution that supports the driver with the appropriate and relevant information to decide and plan his/her journey using an EV, reducing the constraints related with the vehicle autonomy and allowing the driver to perform the journey with reduced anxiety about vehicle range. The proposed solution (Figure 5-1) integrates the data from the public transportation infrastructure, car and bike sharing systems, and carpooling, interacting with the driver through a mobile device that can be carried with the driver, in or out of the vehicle. This system is also able to, based on real traffic information, give decision for the best option taking into account pre-defined criteria (like fastest option, cheapest option, and also guidance), as Figure 5-1, suggests.

In the next Chapter sections are described briefly the systems: Real Time Information and Best Path, Car Pooling, Car Sharing, Bike Sharing, and Public Transportation Information Integration.




Figure 5-1: Main Sustainable Mobility System objectives and sub-systems.

5.1. Real Time Information and Best Path

Real time information is available from road concessionaries, but outside these organizations the access to this information is most of times denied. There are technical issues to solve because each organization has its own data format, and data integration is a real problem. During current research work several approaches were performed to have access to these data (with the Municipal Chambers of Lisbon and Loures, and with the company Brisa), but all the requests have been denied. We turned around this problem by the creation of a web crawler to pick traffic information from specialized sites by pre-defined heuristics, and a XML file with traffic information was created [Fontes, 2008]. The XML file is an approach of future data integration from different source providers. In Figure 5-2 is illustrated the process of XML file with road information oriented to a geo-reference graph.




Figure 5-2: Semi-automatic creation of a XML file with road information to be used for graph creation.

The Crawler (WebNews, version 1.0) was configured to pick traffic information from TVI web site³⁹ and also a Web service from Sapo⁴⁰ was implemented. Information about nodes were checked against a heuristic table, where a conversion factor (CVF) reduces the node speed traffic (if the road is blocked, with no traffic flow, the CVF is zero). Figure 5-3 illustrates this process. The result is stored in an adjacency matrix, where the number a_{ij} represents the cost of going from i to j . This process creates a graph representing the map, where the arcs represent roads and nodes represent intersections or traffic areas. To determine the best path between two points on a map an algorithm could be applied to this graph to find the path with less weight between the two desired points.

The weight of an arc is basically the average time in seconds that it needs to be traveled, for this it is used the formula $(L / V) * 3600$, where L represents the size of the graph in km and V is the top speed allowed. For all arcs there is a speed limit which serves as the basis for the weight of the cases in which there is no traffic information. When there is traffic information for a particular arc, the weight of this arc is affected because the traffic influences the speed. For example, if an arc with heavy traffic has a speed limit of 90km/h,

³⁹ <<http://www.tvi.iol.pt/transito.php>>.

⁴⁰ <<http://services.sapo.pt/Traffic/GeoRSS>>.

given the existing traffic, the reduction factor of the maximum speed has a value set between 0 and, based on current traffic information, causing the increase of the time required for this arc to be traversed, as much as its weight increases. If the transit is cut off, the factor of speed reduction assumes the value 0, and the maximum attainable speed is set to 0 km/h, what causes this arc to have an infinite weight.

If traffic is proceeding smoothly, without any problems, the factor of speed reduction has a value equal to 1, and the maximum attainable speed becomes equal to the speed limit, which makes this arc to assume the lowest weight possible. This weight can integrate also public transportation information and a price associated with CO₂ emission of private transportation. Users can choose the impact parameters based on their strategies, in order to save money, to satisfy conveniences, or even to save time. See Final Year Project at ISEL [Fontes, 2008] for a complete description of this process.




Figure 5-3: Graph node weight calculation based on traffic information from web sites (traffic information in Portuguese language).

Example: Path A1 (Alhandra – Alverca). Maximum speed allowed on this section: 120 km/h (motorway), but traffic information shows average speed is 84 km/h. Distance is 5km, so *arc weight* = (arc distance / average speed) x 3600 s = (5000/84000) x 3600 = 0,0595238 x 3600 ≈ 214 s.

Let's consider, in this example, that public transportation takes more or less twice the time spent with private transportation (by car), consisting in a time of 400 s. Transportation price is 1€ and car transportation is 2€, including the price for CO₂ emissions and fuel price. If drivers choose the same weight factor for time and price, then the arc weight for car transportation is $214 \times 2 = 428$, and the transportation arc weight is $400 \times 1 = 400$. In this case these values are approximately the same, but if the process takes care of parking price of the vehicle in the city, the system increases again the arc weight for private car, and then the system suggests the option of public transportation (PT), showing the next PT arriving to the nearest PT stop. System is able to provide orientation to the nearest PT stop.

To determine the best route or the quickest route was implemented a Dijkstra's algorithm, where its running time is proportional to N^2 , with N being the number of nodes in the graph. The graph to be used by this Dijkstra's algorithm is represented by an xml file. The best way to apprehend the quickest way is determined using the Dijkstra algorithm. In our web application there is a class called Dijkstra, which is where the algorithm is implemented. For a complete description method see [Fontes, 2008] and [Ferreira, 2013]. Information exchanges with external systems are based on XML files.

5.1.1. Case Study

In this Section, it is showed a small example of this application approach to go from Sacavém to Almada without traffic in Figure 5-4, the trip time is around 12 minutes. In Figure 5-5 is showed the same path with traffic information, now the trip time is around 20 minutes. In Figure 5-6, is showed again the same path with a traffic cut in the “25 de Abril” bridge. Now the best path is through the other bridge “Vasco da Gama” and the trip time is around 30 minutes. For more details see [Fontes, 2008]. In [Costa, 2011] master thesis it was used this approach for an integrated best path (with a transportation decision – e.g., private car versus public transportation). Pricing is also a decision factor where it integrates CO₂ emission prices.




Figure 5-4: Application of the best path taking into account no traffic information (trip estimation time is around 12 minutes).




Figure 5-5: Application of the best path taking into account traffic information (trip estimation time is around 20 minutes).




Figure 5-6: Application of the best path taking into account a serious traffic problem in 25 de Abril Bridge⁴¹.

⁴¹ Alternative path is showed as best path (trip estimation time is around 30 minutes).

5.2. Car Pooling System

Car pooling is the process of sharing daily trip with others with similar path and timing. This is important because the occupancy rate of private cars has reached a very low value of only 1.06 persons per car [Maniezzo, 2004]. It is clear that additional efforts are needed to utilize the free capacity in these vehicles. Against this background, is proposed a collaborative Car Pooling system, to raise vehicle occupancy based on a user collaborative environment motivated on a credits mechanism, which can be converted into parking licenses in facilities of big cities. The car pooling happens whenever at least two people ride the same car. Each person would have made the trip independently if the car pool had not been there. Driver and passengers know beforehand the trips in which they share the ride. This idea is not new and several initiatives have been tried in the past without considerable success:

- Dallastravel⁴²;
- Civitas⁴³;
- Carpoolworld⁴⁴;
- Ridesharingonline⁴⁵;
- Mitfahrerzentrale⁴⁶;
- Nctr⁴⁷.

Most of these systems allow convenient trip arrangements over the Internet, support trust building between registered users, and they implement billing systems to charge passengers and compensate drivers. Yet, these services have not become popular and did not significantly increase the average car occupancy. The main technical reason for this is that existing ride sharing services do not allow truly ad-hoc trip arrangements. Today's mobile computing with current advances on geographic location systems, mobile communications (e.g., GPRS, Wimax) new mobile devices (e.g., PDA, mobile phone), and navigations

⁴² Information available at <www.dallastravelsurvey.org/index.php?mod=3_carpool&side=none>.

⁴³ Information available at <www.civitas-initiative.org/measure_sheet.phtml?lan=en&id=282>.

⁴⁴ Information available at <www.carpoolworld.com>.

⁴⁵ Information available at <www.ridesharingonline.com>.

⁴⁶ Information available at <www.mitfahrerzentrale.de>.

⁴⁷ Information available at <www.nctr.usf.edu/clearinghouse/ridematching.htm>.

platforms overcame this limitation and enable for the first time truly ad-hoc ride sharing services. On top of this technology advances is proposed a new collaboration approach based on market share principals and on user profit, which is defined as credits that can be spent for advanced park booking and to reduce the payment fees in metropolitan areas.

5.2.1. System Concepts and Main Modules

Capturing requirements efficiently is crucial to the development of any system. It is proposed a software engineering requirement approach to try to identify patterns that can be later reused for similar systems developments. Based on these, follows a generic workflow of the several activities that compose the requirements, namely: (1) stakeholder analysis, where it is identified the main stakeholders that are likely to be affected by the activities and outcomes of the project, and are assessed how these stakeholders are likely to be impacted by the project and the relations between them; (2) problem domain analysis, it is performed in Lisbon Metropolitan Area (LMA) main transportation infrastructure (e.g., roads, parking places and public transportation); then it performs; (3) requirement elicitation; (4) requirement analysis; (5) requirement specification; and (6) requirement refinement. The main outputs of the system's specification, that meets user carpooling needs and the flow list of requirements, aiming to increase the average rate of car occupancy, are:

- Real time traffic information;
- Best route search based on traffic information, and based on dynamic route matching algorithms;
- Integration with public transportation information and parking facilities;
- Pre-booked parking place;
- Ad-hoc trip arrangements;
- Use of past-experience data to estimate time-to-pickup;
- User Profiles and credit mechanisms.

System main modules are illustrated in Figure 5-7. External information sources feed the system with public transportation time table and information, weather information, car parking facilities with available places, and road information (routes and traffic). Car Pool Driver profile, illustrated in Figure 5-8, and Car Passenger profile, showed in Figure 5-9, are used in a matching function to identify car pooling.

The car pooling design follows the use-case analyses (Figure 5-8 and Figure 5-9) for Car Pooling system with two main profiles: driver profile and passenger profile.

Driver profile is illustrated in Figure 5-8: user login, password, mail, cellular phone number, window travel time, start and ends points, credits, number of available seats, parking location, information to the system about delay on usual trip start time, parking number and parking timing slot wanted (date, start hour, end hour).




Figure 5-7: Car Pooling system main modules.




Figure 5-8: Use Case for car pooling driver profile.

The passenger profile is illustrated in Figure 5-9: user login, password, mail, cellular phone number, window travel time, start and ends points, credits, user results preference (like driving distance to picking point), waiting time, and if the passenger wants, a daily updated information or relay on pre-defined information. Results visualization can use a graph visualization tool or a map using Google Maps interface, and it can receive notifications about delays of scheduled ride based on driver starting hour delay (only possible if the driver alerts the system), or based on road traffic conditions.




Figure 5-9: Use Case for car pooling passenger profile.

Profile matching algorithm [Ferreira, 2009] is used to identify possible car poolers based on the matching of drivers and passengers profiles. First it is transformed the users routing plan in a nodes graph by defining the nearest node of GPS coordinates of start and end points. All node information comes from a GIS (Geographic Information System) application (GoogleMaps). Nodes distances are calculated based on node GPS coordinates. Then the system checks the travel time window based on matching nodes. If the user accepts public transportation the process adds graph information related with an alternative routing path. Return trip is independent and matching start with end points matching (user location car), time window and start point. A list of possibilities is always presented to the users based on pre-defined user's criteria chosen, like trip distance for picking point, waiting time and end point. Results can be shown in Google maps using public available API. Passenger's chosen trips are stored in a database associated to the user unless we ask for a new one.

The best routing path is based on graph optimization based on a Dijkstra algorithm (for detailed implementation see [Fontes, 2008]). Graph nodes correspond to road intersection or stop points and graph arc weight measures the time travel. This time is calculated based on node distance divided by road maximum speed. Traffic condition can perform a modification of road speed. When road information is available from sensors the system can use real information about the traffic speed. In the case study identifies a problem with heterogeneous data formats. When the information is missing our heuristics determines the traffic speed (for details see [Fontes, 2008]). To receive updated information in real time it is important to look for communications and end-users devices. End-users devices determine the communication interfaces and protocol. A user with mobile phone receives and sends SMS messages. If a user has a GPS and a GPRS (or even wireless) device communication (e.g., smart phone, PDA) the system is able to communicate and exchange information during the user ride.

5.2.2. Credits Mechanisms and Payments

The user does not pay his ride and can win credits giving alerts and feedback to the system about the way the driver steers. Credits can be mainly used in passenger ride or parking facilities, so it is necessary government incentives (for example, incentives given by municipalities) to cover some parking expenses related with credits. These costs can be compensated by less CO₂ emissions and less traffic during peak hours.

Users are handled by the following modules: user registration, user credits, user communication interface, and user profile. User registration module is the responsible for detecting if the user is a registered user or not. If so, it shows the user information, the number of credits that he has, allows him to change his personal data, driver profile, making suggestions, and allowing the user to buy more credits. If it detects that the user is not registered, it asks for the registration. User communication interface formats the information for the end-user device (e.g., PDA, mobile phone). User profile handles all issues related with the creation and change of driver or passenger profile.

Users Credits is an important research issue that addresses the system on how to determine the ride price (credit cost). In the current research is proposed a dynamic value determination, based on the stock exchange metaphor, following these listed main guidelines, for details see [Ferreira, 2009]:

- A new user in the registration process receives 50 credits.
- A recommend action to the system given by the user gives 5 credits.
- A given ride is equal to a predefined value. Trip expenses (km = 1€, plus toll and parking) are divided by the number of passengers. If it is assumed the number of four passengers in a trip of 25 km, with 5 € toll and 10 € parking, is converted in 10 credits. So, the driver wins 10 credits per passenger (or less if the trip is shorter) and the passenger spends only half of trip credits. Agent simulation tasks were used to optimize these credit values in order to maximize car occupancy.
- Feedback of updated information over the ride gives one credit.
- By the end of each month the average occupancy rate of each poll car is calculated. This number is multiplied by the number of rides performed by the car, giving additional credits.
- User feedback (e.g., rating driver punctuality and flexibility) can act over ride credits. A positive feedback is used to increase by 1% the ride credit, and a negative feedback is used to decrease by 1% the ride credit.
- Each hour in a parking place is one credit.

If a ride car is fully booked (i.e., number of passenger rider's equal car seats), and a user wants to take that trip, he can initiate a process of increase the ride credits until one of the booked riders give up. Also in a monthly basis, through ride statistics of car occupancy, the system can raise or decrease the ride credits by 5%. If average ride occupancy is smaller than 2.5 (the value of our target), then the system decreases in 5% de ride credits, but if it is bigger than 2.5, it has an increase of 5%.

Payments: the system uses a credits mechanism. Users can buy credits (1 credit is equal to one euro) through bank account transference. Based on monthly reports (from historical data) the system proposes ways to maximize the gains of credit, by increasing car occupancy or even by proposing more rides of the user as a driver. We are currently working in an optimization algorithm based on ride request (that uses mainly time window and location) that can give suggestions to the driver to make small changes in order to increase car occupancy. If user wants to participate only as passenger, perhaps he will need to buy credits that will be used to cover parking expenses.

5.2.3. Application Scenario

Lisbon is the largest city and the capital of Portugal. Being the capital, it contains the headquarters of the main companies, many universities (both public and private), and the main seaport and airport. This results in a concentration of most economic activities which creates a synergy without parallel in Portugal. On the north side of the river Tejo, close to Lisbon, there are 8 municipalities: Amadora, Azambuja, Cascais, Loures, Mafra, Oeiras, Sintra and Vila Franca de Xira. On the south side of the same river there are 9 municipalities: Almada, Alcochete, Barreiro, Moita, Montijo, Palmela, Seixal, Sesimbra and Setubal. Lisbon is not only the head of the Lisbon Metropolitan Area - LMA (there are only two metropolitan areas in Portugal), but also a district capital (comprising 15 municipalities). LMA, is the largest population concentration in Portugal. Preliminary data from the 2001 Portuguese census puts the population of the metropolitan area at 2,641,006 (about 1/4 of the Portuguese population), of which 20.8% lives in the city of Lisbon. About 27% of the population of continental Portugal lives in the 2,957.4 km² of LMA. Census 2001 (at the time this work was written no 2011 data was available), performed by INE⁴⁸ shows the following facts: average daily trip home to work is around 35 minutes and is distributed as shown in Figure 5-10. There is no official data regarding car pooling usage in Lisbon or Portugal. Only 5% of vehicles travels with more than one passenger, and this 5% value reflects mainly family trips (husband, wife and kids). Due to a bad transportation system outside the Lisbon area, a growing number of persons living outside the Lisbon city area, limited parking facilities in the Lisbon area, and the continuous increase of fuel prices, this system for car pooling has a great potential for a successful application.

⁴⁸ National Statistics Institute, <www.ine.pt>.




Figure 5-10: Lisbon Metropolitan Area (LMA) traffic distribution from 2001 census⁴⁹.

In Figure 5-11 it is possible to see the potential of car pooling system in LMA because there is a major movement into Lisbon city from distant places, without good transportation infrastructure supports. For instance, a person that lives in *Santa Cruz* (village in a cost at the north of Lisbon) at around 70 km distance, by car takes about 45 minutes (with costs of approximately 15-20€), but on public transportation the trip takes around 2 hours.

To minimize car cost or to avoid long trips in public transportation (like 4 hours, considering a round trip), several persons organize car pooling ride among neighbors or friends. Let's check the system behavior based on the following scenario shown in Figure 5-12. A user starts his daily journey from home to work. Starting point is near node A0. He takes 5 minutes to reach node A0, but our system assumes starting point in A0. By car the trip takes around 30 minutes (without traffic delays), however free parking place is always a nightmare, for which sometimes drivers wait more than 30 minutes without success. Pre-paid parking is cheaper, however daily prices are prohibitive (more than 10 € for an 8 hour time slot in Lisbon). Based on the drivers profile the system finds the driver's node routes within a waiting time previously defined (this case 5 minutes).

⁴⁹ Image source <www.ine.pt>.




Figure 5-11: Lisbon Metropolitan Area (LMA) people movements from 2001 census⁵⁰.

Also public transportation routes with starting time of pre-defined (5 minutes in this case). In our system, as shown in Figure 5-12, the information is in a graph visualization interface (it is possible to represent the same view in a map using Google Maps interface). Based on the system information the user chooses the color node option and stores this information. The system notifies the user and in this case the trip time takes only 2 more minutes than a trip taken with the own car of the user, but this time in average should be higher. Another advantage of this system is the parking booking. Credits can be converted in periods of parking, but the rate changes from park to park. Also relevant is a saving for this trip of 30 km, since the cost for using a motorway toll can reach an amount of 25€/day, which gives 600€/month and around 6600€/year.

The system also considers a delay report of user ride (for example 10 minutes), so that the system can advise users to take ride of drivers which start trip in C0 and catch public transportation at node A3. Also the driver that starts on node B0, can be considered in other day as a passenger, and catches a ride of driver A (starts in A0).

⁵⁰ Image source <www.ine.pt>.




Figure 5-12: User match ride, with user preferences on a graph tool visualization, in a java prototype.

5.3. Car Sharing System

Car sharing systems balance between private and public modes of transportation. They allow individuals to use a car when needed without having to buy one for their exclusive purpose. This, obviously, comes with some inconveniences, such as having to reserve the car for a predefined period, having to walk to the nearest parking lot, or needing to select another mode of transportation if no car is available. However, it also has a lot of advantages because it gives access to a private, flexible mode of transportation, without having the entire burden that comes with it. Hence, it is not that surprising to see that car sharing systems are becoming more and more popular and that people are willing to engage in this new mode of transportation.

Car sharing is not a new transportation mode. Years ago, when cars were luxurious goods, households were uniting to buy one. Its ownership and use were shared. It was for these households the only way to have access to an automobile. Nowadays, car sharing responds to new needs and is provided in an organized system. People want to benefit from the car's flexibility without supporting all its inherent costs: insurance, parking, maintenance, etc. Users are also attracted to car sharing because of its good environmental image [Steininger, 1996]. Figure 5-13 shows eleven car sharing parking locations in Lisbon, what represents a reasonable implementation of car sharing initiative. Car sharing services are managed by companies, like short term car rentals. Car Sharing Organizations (CSO) usually manages a fleet of vehicles dispatched in several predetermined parking lots. Members have access

to any vehicle at any time, given that they have made a reservation in advance. Car keys are usually located in a safe-deposit box located near the parking lot. Users can keep the vehicle during a fixed period of time that can vary from one hour to several days. At the end of the rental period, the vehicle has to be returned to a parking lot (usually the one where the car was taken). Traveled distances and rental durations are recorded and used for the billing of every user (fees depend on the total duration and mileage) [Barth, 2001].




Figure 5-13: Car Sharing parking places available in Lisbon, status July 2011.

Some studies have been conducted to estimate the potential of car sharing in urban transportation and changes in transportation behavior when a car sharing service is available [Shaheen, 2001], [Lee, 1998], [Cervero, 2002] and [Steininger, 1996]. Cervero et al. [Cervero, 2002] state that this mode could attract users towards individual car ownership for the San Francisco area. Other authors indicate that, on contrary, CSO helps to decrease car ownership because some users leave their individual car to enter the system. Positive impacts of car sharing on travel demand and on greenhouse gases (GHG) emissions were also reported by Morency [Morency, 2007]. Most of these studies are based on user surveys and can hardly characterized long run use of car sharing. Barth et al. demonstrated the potentialities of using individual data collected in a multi-station shared vehicle system [Barth, 2001]. On a pure economic basis, CSO can be both viable and profitable [Wright, 2001]. Several systems are running through the world, especially in Europe (UK, Germany,

Italy, Netherlands), in Canada (Toronto, Montreal, Quebec City) and in the United States (Seattle, Portland, San Francisco area).

The proposed system is similar to the reservation slots of a public charging station and it was developed in a Final Year Project at ISEL [Xavier, 2011]. Main system functionalities are described in Figure 5-14.




Figure 5-14: Use case for car sharing system.

5.4. Bike Sharing System

Bike share is an emerging urban transportation concept based on collective paid use of a distributed supply of public bicycles. It is similar in function and programming to car sharing initiatives that have been very successful in several places. In general, bike sharing consists of strategically distributed “stations” containing ten to twenty bikes on average, with a centralized payment/control kiosk. Customers—who range from one-time users to long term subscribers, “unlock” a bicycle with a credit card or smartcard, then ride to any other station in the city where they can deposit the bike, concluding their trip.

Bike share fills a number of key “niches” in the urban travel market and is particularly useful for relatively short-range travel beyond the length of comfortable walking distance. Its key advantage is that it gives virtually everyone access to what in the past had largely been viewed as a specialized form of urban transport, promising increased use of bikes for short-distance travel, helping to decrease pressure on traffic and transit systems.

Main functionalities of the proposed Bike Sharing system are defined in Figure 5-15 and for more details see master project at ISEL [Costa, 2010].




Figure 5-15: Main Bike Sharing system functionalities.

5.4.1. Weather

The extremes of weather affect bicycling more so than any other practical mode of transportation, on both short-term (day-by-day) basis and longer-term trends. Extreme heat, extreme cold, and heavy rainfall are the top weather phenomena leading to decreased numbers of cycling trips. User Profile can be used to define if the user wants to use a bike under certain weather conditions (rain, too cold or hot).

5.4.2. Topography

Like weather, topography has an impact on the willingness of people to use bicycles, although in this case it is often limited to certain trip patterns rather than affecting system usage as a whole. This is apparent in the evaluated European bike share cities, which

regularly exhibit shortages of bicycles at stations at the tops of hills or steep gradients, suggesting that many users are riding downhill but not back upwards.

The study of the slope is particularly important for cyclists and pedestrians. For the slope Google API allows the following operations:

- get the altitude of a particular point;
- get the altitude of n points in a straight line path, where n is the number of samples required;
- get the altitude of a set of points.

Figure 5-16 illustrates an invocation of Web service for calculating the profile of a set of points.



Figure 5-16: Google Web Service Elevation.

Figure 5-17 presents an application of this service, where appears the bike path and the elevation in meters.




Figure 5-17: Example of a bike path with the elevation in meters (top of figure).

5.5. Public Transportation Information Integration

There is difficulty in obtaining information about traveling to, from and within a region, even in the same city, due to the diversity of transportation operators. Most of these operators have their own system, so that they work and plan the routes and schedules independently of nearby operators. Also public transport systems differ from region to region. It is therefore understandable that when reaching a destination, even for the most traveled user, it becomes difficult to use local public transport due to poor organization of information, and especially due to language barriers, for those who do not speak the native language of the country. In this context, is denoted the scarcity of appropriate information systems to assist travelers in the region, including providing practical information, essential to understand the operation of the means of transportation.

The availability of the Internet and the current development of Information and Communication Technologies (ICT), became the best way to disseminate information, inspiring the development of strategies to support tourism and culture. Additionally, the mobile guides are increasingly seen as an asset to offer an experience more appealing of

visitation and interpretation to natural parks or historic sights. Technological advances allow higher processing in smaller devices, making possible the use of technologies such as GPS and Wi-Fi. In addition, the popularity of social networks, like Facebook, showed the willingness of users to share their experiences and be part of communities with similar interests.

Part of this research work was used in ISEL participation on the Seamless Travel across the Atlantic Regions using sustainable Transport (START) project. START Project is a European Commission's Transnational Territorial Cooperation Programme with 14 partners from the UK, France, Spain and Portugal. The main mission is the establishing of a transnational network of regional & local authorities to promote enhanced accessibility, giving tools to make easy to travel to, from, and around the Atlantic regions, using environmentally friendly, collective modes of transport, greater interconnectivity between transport systems, clearer information within regional gateways, airport hubs ports and rail interchanges. For more information see START web site⁵¹.

Main contribution of ISEL on this project was the data integration of multiple transportation sources [Costa, 2011], [Ferreira 2011f], [Ferreira, 2013b], and a system to support user on public transportation query data. The system should allow the interrogation of multiple sources of information through a single interface. The questions and answers to them should reflect a single data model. The existence of a single common data model takes the client applications with the difficult task of dealing with various technologies and their relational schemas different. Different public transportation systems can be added with total transparency to the end user. From START project different public transportation data and data base schemas were tested. Also this integration allows the creation of mobile systems oriented for tourism's purposes, other main goal of START project, where "low budget tourism" can be guided, to reach POI (Points of Interest) by public transportation.

This integration task is performed taking into account Figure 5-18, based on a domain ontology definition for public transportation, where a local public transportation data base is mapped.

⁵¹ <<http://www.start-project.eu>>.

5.5.1. Public Transportation Data Integration

In Figure 5-18 is illustrated the public transportation different sources data integration approach, where is possible data information integration from different operators of public transportation. This application output is a user Mobile Device, or Web Application SITP, that is described in Section 6.5. The data integration is based on a domain ontology (Ontology for Public Transportation - OPT), a wrapper that performs the mapping between different public transportation data base models and a mediator. If the public transportation operator data base is constructed under OPT the wrapper and the mapping definition are not needed. Wrapper is developed at each operator side based on operator information source and is a common interface for data access. In Figure 5-19 is presented the wrapper solution based on [Bizer, 2009]. D2RQ is a declarative language to describe mappings between relational database schemata and OWL/RDFS ontologies. The D2RQ Platform uses these mapping to enable applications to access a Resource Description Framework (RDF) view on a non-RDF database through the Jena and Sesame APIs, as well as over the Web via the SPARQL Protocol and as Linked Data.

SGBD Schema Publication is the mapping process between local data base and the vocabulary of the ontology (OPT) using R2RQ language. The Process is divided in the following steps: (1) entity definition; (2) adding of proprietaries to the entities; (3) connection of entities; and (4) definition of conditions and aggregations (when necessary).

Mediator is based on MediaSpaces Mapping Framework, where it is possible to perform SPARQL queries based on OPT.




Figure 5-18: Different sources of public transportation data integration approach.




Figure 5-19: Platform D2RQ used at wrapper components [Bizer, 2009].

5.6. Transportation Best Advice and Green Route Planer

The main idea is to build an integrated system, as showed in Figure 5-20, that based on traffic and weather information, can give the best advice in terms of a diversity of options: public transportation from several operators, car and bike sharing system, and car pooling. The system can be configured to give the faster option to go from point A to B. This could imply a mixture of options. Also best advice could be the cheapest option.

All public transportation data (to the Lisbon area) were exported to a graph, where the arc length is defined by the time that it takes to go from one node arc to the other. The same procedure is applied for car sharing, car pooling and bike sharing systems. With all information in a graph, the best path algorithm, described in Section 5.1, can be applied. The big issue is the matrix size that could increase a lot with a large diversity of options, and could generate computer memory problems on handling this matrix. Some heuristics were defined to speed up this process.



Figure 5-20: Mobi Transportation best advice.

The arc weight can be constructed from a diversity of options, time, price and CO₂ emissions. Next Sections explores this issue from a perspective of a green policy.

Also this integrated approach of a diversity of systems, with geographic information, could be important for transportation planners or to political decisions regarding transportation. Figure 5-21 shows the main systems and information involved in Mobi-System.

The main idea is to adapt arc weight to a combination of items that could reflect an environment policy. Arc node reflects time, price and CO₂ emission price and a good

investigation topic is to find the best combination between time, price and CO₂ emissions price, in order to define the ‘best’ weight of arc path. This weight could also include a parameter function of city traffic conditions (overload paths should be more penalized). The system has potential to work and deal with different source diversity. This idea is materialized in a final year project at ISEL [Marques, 2011].




Figure 5-21: Mobi-System transportation related system.

5.6.1. Green Route Planer: Case Study

Different approaches can be integrated in arc weight calculation: time, price, and a weight related with CO₂ emissions. Figure 5-22 shows a configurable application screen where the weights (from 0 to 500) can be defined and easily configured by a user.

Figure 5-22 shows a small example of the application usage to go from Chelas to Bairro Alto, in Lisbon, by walking and by metro. Weight configuration was based in the values showed at Figure 5-24. If the weights all equal the best path is based on the fastest option, see Figure 5-25 based on bus transportation.




Figure 5-22: Green Route application (application in Portuguese language).

Figure 5-22 shows a first path 200m (walking): $A_{walk} = 120s$ is the walking time (more or less 2 minutes). Then the metro with $A_{metro} = 900 + 600 = 1500s$, these values are taken from a standard time table. Last path is again walking 680m, then $A_{walk} = 408s$. Taking into account the weight for walking equal to 0.15 (see Figure 5-23, where table values are divided by 1000) and the weight for metro equal to 0.225, the A_{final} is:

$$A_{final} = 508 \times 0.15 + 1500 \times 0.225 = 414.$$

For other possibility, see Figure 5-25 with a total walking of 420m, which gives $A_{walk} = 252s$ and buses $A_{bus} = 1250s$. Taking into account a bus weight of 0.325 (Figure 3-24), the A_{final} is:

$$A_{final} = 252 \times 0.15 + 1250 \times 0.325 = 444.$$

In case of Figure 5-28 where the bus weight is changed to 0.225, then:

$$A_{final} = 252 \times 0.15 + 1250 \times 0.225 = 319.$$

So the second is the best option now.




Figure 5-23: Administration application menu: weight configuration (in Portuguese language).

	CO ₂ Emissions	Travel Time	Price	Weight
Pedestrian	0	150	0	150
Bike Sharing	0	125	1	200
Metro	50	75	2	225
Tram	50	100	2	300
Bus	75	100	2	325
Car Sharing	100	50	5	425
Taxi	100	50	15	400
Car	150	50	10	475

Figure 5-24: Weights used on current example.

The transportation networks system is based on several options (own car, car sharing, public transportation, walking and bike sharing). This system is viewed as a multimodal graph and each mode network is modelled by a monomodal sub graph. The mode network

structuring was used to speed up the computation of the multimodal shortest viable path and also to perform a new design for the multimodal path operator.




Figure 5-25: Green Route application results with all transportation weights equal (application in Portuguese language).

This study has examined sustainable mobility approaches towards a green environment policy. The proposed algorithm takes into account not only the expected travel time, but also additional constraints, such as: delays at mode and arc switching points, and CO₂ emissions. The transportation networks system is based on several options (own car, car sharing, public transportation, walking and bike sharing). This system is viewed as a multimodal graph and each mode network is modeled by a monomodal sub graph. The mode network structuring was used to speed up the computation of the multimodal shortest viable path, and also to perform a new design for the multimodal path operator.

5.6.2. CO₂ Emission Calculation

Also a CO₂ emission calculator was performed based on vehicle data, distance of current path and with estimation of the number of persons. An illustration of this calculator is

showed in Figure 5-26. This module assist policy maker on the definition of transportation weights used in green route application.




Figure 5-26: CO₂ emissions route calculation (application in Portuguese language).

5.7. Conclusions

From the guidelines that EVs change the way that drivers use vehicles, new realities and sustainable mobility in smart cities will increase the need of information systems to support a diversity of options and processes. Drivers need real time information about the diversity of transportation options, and the purpose of reducing the number of cars in the cities requires the integration of all diversity of transportation options, in order to present a good alternative transportation option to drivers, otherwise they will persist in using their own private transportation in the cities. This option could be interesting for EVs, due to autonomy purposes. A driver without range autonomy to go home-work-home could use this integration of information to stop in a parking place (with charging facility and nearby transportation options). In author opinion this approach (integration of public transportation information) will help the integration of EVs in future mobility concepts where the decrease of vehicles in the cities is a must towards the reduction of CO₂ emissions.

The focus on this work is aligned with the “Integra Concept”⁵², whose aim is to provide a single brand that links together and provides information on the different public transport operations across the Atlantic regions. So, the system should allow the query of multiple information sources through a unique interface. The queries and answers to them should reflect a single data model. The existence of this common data model takes the software applications with the difficult task of dealing with various technologies and their relational schemas. Different public transportation systems can be added from the end user point of view. Also, this integration allows the creation of mobile systems oriented for tourism purposes. Another main goal of Integra is to provide guidance to “low budget tourism”, helping tourists to reach POI (Points of Interest) by public transportation.

This Chapter introduces a new approach the “cooperative transportation infrastructure integration”, by providing the driver with a collaborative holistic approach of different public transportation infrastructure sources that can be combined with real traffic information, parking places and charging slots and current driver position, to support the driver decision making process.

⁵² See information on <<http://www.start-project.eu/en/Integra.aspx>>.

6. MOBI-SYSTEM: USER APPLICATION AND CASE STUDY

This Chapter is dedicated to the description of the applications developed not yet described and a case study. Figure 6-1 shows the main sub-systems developed for the Mobi-System application, grouped by main functionalities. In this Chapter our focus is the application for end-user (mainly the vehicle driver) in mobile devices (SiREV and IRecommendIt), the web application (V2G smart system and SITP system), and are presented some utilization results. Mobi-System is a central information system with two main mobile target platforms: (1) smartphones based on Windows mobile and android; and (2) vehicle dedicated system (to be considered by each manufacturer). All development was based on open source software. SiREV is the application developed for Android operating system and IRecommendIT the application for windows mobile.



Figure 6-1: Mobi-System main developed applications. In brackets are the Sections where the applications are described.

This chapter is divided in the following Sections: (1) V2G Smart System; (2) SiREV Application; (3) IRecommendit Application; (4) Mobile Application Usage Results (Case Study); (5) SITP Application; and (6) Conclusion.

6.1. V2G Smart System (Web Application)

V2G Smart System was developed under a final year project at ISEL in 2010 [Bento, 2010]. The main functionalities of this web application (V2G Smart System) are: (1) Registration: registration page form for new users; (2) Password Recover: form for password recovery; (3) Login: home page of the application; (4) Profile Creation: data creation related to driving habits, EV type; (5) Personalized Charge Profile: data related with EV usage, like minimum SoC (State of Charge) allowed for the EV batteries, electricity desirable prices to sell and to buy, desirable periods for charging and home charging limitations; (6) Statistics: home energy consumptions, weekly, monthly and annual energy expenses, price variation of electricity and charging periods, among others; and (7) Smart Charging taking into account the electrical distribution network and home power limitations.

V2G Smart System is divided into six main modules:

1. Interpreter of Downloaded Files: this module is responsible for reading and interpreting the charging files (e.g., files with electrical transactions or commands for charging device), giving the system a layer of abstraction over the file format of text issued by the charging station.
2. Smart Grid Interface: this module is responsible for the interaction with the electrical network, i.e., it controls the flow of energy from or to the electrical network, with the objectives of helping network stability and also, managing information on the variation of electricity prices, to optimize the possible profits obtained with the selling of electricity stored in the EV.
3. User Manager: module responsible for registering the users and their EV main characteristics (model, battery type), allowing the recording and editing of users data, as well as the removal of users (if defined rules are not accomplished by specific users). This module is also responsible for verification of user identity and ownership of registered vehicles (through the transmission of data received from the user to the authorities), and for performing regular cleaning from the database of users categorized as "spam".
4. Manager Charging Profiles: a user can set one or more load profiles for each of the vehicles registered by him. A common practice is, for example, the definition of profiles and needs of different charging to be carried out during the week (weekdays) and over the weekend.

5. Smart Charging Module (described in Section 3.9).
6. V2G Central Core: consists in the main module of the V2G Smart System, interacting with various modules mentioned above, and managing the distribution of system information (from other modules and database).

In relation to the technologies to be used in the development of these applications, it was decided that, the management system database, using MySQL Server. The development of Web applications is held in Java, and all graphical development is carried out using the *ZK Framework*, which facilitates the development of Web applications with Ajax, and has the advantage of being open source. The development of the environment, using the Eclipse Project, is integrated with the *ZK plugin*, with main modules: (1) *ZK Loader*, consists of a servlet (server side component that generates HTML and XML data to the presentation layer of a Web application) that processes the requests for resources zk; (2) *ZK Client Engine*, is processed on the client's browser and is responsible for monitoring the events page and realization of their requests to the server by Ajax technique. This engine is generated by *ZK Loader* when processing HTTP requests, and is sent in response to the client in the form of JavaScript code; (3) *ZK Asynchronous Update*, another servlet that serves asynchronously requests made by the *ZK Client Engine*. These requests are caused by interaction of the user with the various components of the page. The *ZK Asynchronous* processes the events triggered by the user, sending the response to the *ZK Client Engine*, encoded according to a protocol's own framework, which typically consists of changes to the page content; and (4) Index, home page of the application, from which the user can perform the login in the application or access the registration page if it is his first access. Figure 6-2 shows V2G Smart System main application menus: (1) Main menu with information of user definition, statistics, and virtual account; (2) User profile; (3) Electricity market prices, simulated with base on microgeneration production (see Section 4.3.1), based on installed capacity and weather information (wind direction and speed, rain percentage, temperature, solar radiation); (4) User account related with the electricity market; (5) Personalized menu links for user's fast access; (6) Application default menus; (7) EV and electricity market related news, created from personalized web search robot.




Figure 6-2: V2G Smart System Mobile Application (in Portuguese language).

Figure 6-3 describes the creation of a profile with pre-defined information, like EV type, and help tips to the user on this process.




Figure 6-3: V2G Smart System - menu for charging profile creation (in Portuguese language).

Figure 6-4 shows a user profile with the identification of travel periods and electricity prices to sell and buy.



Figure 6-4: Driver profile visualization (in Portuguese language).

Figure 6-5 shows the smart charging process, where is identified an electrical distribution zone, power limitations are considered and the EV identified, taking into account a small example. A complete description and a user manual is available in [Bento, 2010].




Figure 6-5: Small example of collective smart charging taking into account electrical distribution power limitation and user profile. At 3 am systems checks that user C needs more power, so V2G smart system limits user B charging.

6.2. SiREV Application

The SiREV system is based on three main layers, where SiREV is the designation for the mobile application for an Android phone. The SiREV main services are: (1) GPS position service; (2) Data storage service; (3) Internet connection service; (4) SMS service; (5) User notification service.

The SiREV system is based on three main layers, shown in Figure 6-6:

- SiREV Application for Android Operator System.
- Execution Services: The SiREV main services are: (1) GPS position service; (2) Data storage service; (3) Internet connection service; (4) SMS service; (5) User notification service.
- Mobile Application: These layers, as a group, form the Mobile Platform SiREV which the target is the mobile platform The Android platform is the platform for Google's mobile devices business; it is now one of the major operating systems used on smartphones, and the system that grew most in the market in 2009. The platform comprises an operating system, a middleware layer and a set of key applications. The development of applications for the Android platform is based on a well-documented Java API. For development of applications Google offers Android SDK that is a set of tools and documentation, integrated into the Eclipse development environment that allows the creation and test applications.




Figure 6-6: Main SiREV system platform layers.

The development of applications for the Android platform is based on a component-oriented architecture. A number of types of components that make up each application databases:

- *activitie*: an *activitie* presents a user interface and represents a specific activity of the user. An *activitie* may for instance be used to display a list of options to the user and capture the interaction that the user produces.
- *service*: a *service* has no user interface, runs in the background for an indefinite period of time. A *service* can be associated with one or more activities, which offer to the user the control of the application.
- *broadcast receiver* is a component used to receive advertisements transmitted by other components and may have different origins, such as low battery announcement, announcement of change in geographical position, announcement that a photography was taken or that the user has changed the language options of the equipment.
- *content provider* is used for data exchange with others applications. All data is stored in a SQLite database.
- *intents* are asynchronous messages that trigger activities, broadcast receivers and services and shows receptor component.

Each block in the Figure 6-7, extracted from [Pereira, 2010], represents a set of architectural components grouped by functionality, with the interfaces for communication with each other.




Figure 6-7: SiREV system architecture.

6.2.1. Components Model

Android architecture is based on a set of components. The system model SiREV uses these components as follows. In Figure 6-8 extracted from [Pereira, 2010], there are two layers of the application and external systems: (1) user interface and business logic; (2) integration; and (3) external systems. The colors represent the functional subsystems, which correspond to functional blocks of the model architecture. The six cubes in the bottom of the diagram represent the external systems with which it interacts. In the case of a system for a mobile device makes sense for 2-tier architecture that there is one layer for the user interface and business logic, and keeping separated the integration layer to allow greater modularity and flexibility in integration with external devices.




Figure 6-8: Components Models of SiREV application.

6.2.2. User's Interface

The SiREV system has one *activitie* for each screen functionality: (1) *ProfileChooser*, chooses the user and associated profile; (2) *ModeChooser*, chooses EV usage mode (travel or working); (3) *DestinationChooser*, chooses home, work or other specific address; (4) *MainScreen*, with context data, position and SoC, presented in Figure 6-9 (left side); and (5) *RecomendationChooser*, recommendation screen, showed in Figure 6-9 (right side).




Figure 6-9: Screens of SiREV Application.

6.2.3. Controller

The *Controller* is created when the application starts and the *Controller* checks application status, register the information in context and makes the connection between the presentation layer and the other *services* and *components*.

6.2.4. Integration Layer

The system interacts with different and heterogeneous external systems, which implement different integration patterns supported on various communication protocols. For each external system it identifies the most widely used standard, or in case there is no set standard or a universally accepted one, an adapter that abstracts of one possible implementation of a standard pattern. The interface with external systems offers a complete

abstraction of its implementation, with the purpose of isolating and decoupling the systems. The SiREV system is flexible to be integrated into any type of system, since the interface interaction is respected. The integration components are components Android-type *content providers*, and implement the standard architecture adapter [Pereira, 2010].

Smart Grid integration

Information on the charging points is received in XML files in KML format, which are obtained through the periodic synchronization with the smart grid. The synchronization is done via an Internet connection by going to an address configured on the system and using the classes in the API package `android.net android`. The component *SmartGridService* is a service to be launched to android who continues to run in the background, performing regular updating of the information file of the charging points. The service uses the component that is a component *SmartGridAdapter* android type of content provider. This component has the task to interface with external system that provides data on the charging points and makes the necessary changes to data in order to provide records that the service recognizes as *SmartGridService*.

Battery management system interface

The battery management system consists of the following components: (1) *BatteryDetails*: Android architecture that allows applications, or subsystems, sharing resources, including the user interfaces, activities. This facility allows, in this case, the set within the subsystem *activitie Management Battery*, because that is where it really fits, but that can invoke the main component of the system controller. The *activitie BatteryDetails* is a screen with information about the current state of the battery and the mode of operation, i.e., whether it is charging or running. By putting this in a different package *activitie* it allows the screen to be customized for different constructors or battery management systems, providing data specific to each; (2) *BatteryService*: Android service responsible for managing and monitoring the battery. It also has the function of periodically monitor the battery status and trigger messages such as autonomy *IntentBroadcast* lower than 50 km; (3) *ChargingDeviceAdapter*: Component responsible for integration with the system device. As explained above, implements the standard adapter that can be developed by a component of this type for any battery system of any manufacturer that has been duly specified. This component also has to deal with multiple physical interfaces to connect to

the battery system. The SiREV is designed to be implemented in both systems, integrated into the vehicle as smartphones. At that, it uses the API *ChargingDeviceAdapter* android to become fully achieved the physical connection to another system. It is possible to connect via USB or Ethernet, in the case of an integrated mechanism in the vehicle, or by Bluetooth or Wi-Fi, if the SiREV runs at a smartphone without physical connection to the vehicle. The platform provides all the necessary mechanisms to establish the physical connection, the application just needs to know the Uniform Resource Identifier (URI) that communicates.

Public transport interface

Information on public transport is available to the system in the form of an XML file that contains position information of the geographic locations of the transports stops. The recommendation system submits the items collection of items for the *PublicTransportService* that identifies each item to its proximity to an interface with public transport. If yes, the property *nearPublicTransport* item is placed with the value of one. The connection to an information system is made by public transport component *PublicTransportAdapter*.

Electricity Market Interface

The electricity market information is managed by *PriceService*, a service that periodically contact the information system of the electricity market in order to update the current price. The connection to the external system is the responsibility of the adapter *EnergyMarketAdapter*, which is a system that only returns a numeric value corresponding to the price of electricity.

Android Services are: Position system, Mapview, SMS Manager. For more details see this master project oriented at ISEL [Pereira, 2010].

6.3. IRecommndit: Windows Mobile Application

Similar application for windows mobile platform was developed by a final year project at ISEL [Borges, 2010]. Figure 6-10 extracted from [Borges, 2010], shows the different modules that compose the system architecture:

- Application for mobile devices, IRecommndIt Mobile App;

- Web Service *EVService*;
- Service Layer;
- Data Access Layer (DAL);
- SGBD1;
- SGBD2;
- Recommendation engine.




Figure 6-10: Main modules of IRecommendIt (Windows Mobile Application).

Starting at the end, right to left in Figure 6-10, the system has a subsystem, the recommendation engine system. The management is responsible for the calculation of recommendations of places of interest. The calculation of the recommendations i occupy large amount of resources is a task whose execution can compromise system performance and therefore must be isolated from the rest of the tasks of the system to not affect their performance. To isolate the calculation of the recommendations and give some scale to the system was based on two DBMSs, and SGBD1 SGBD2. The SGBD1 owns all of the data stored by the system IRecommendIt while the second part has SGBD2 SGBD1 data that are needed for the calculation of recommendations. The two DBMSs perform data replication, so that the calculation of the recommendations on data to be consistent and fair. The DAL performs the data management system IRecommendIt, it operates on the SGBD1 questions in the form of SQL (Structured Query Language). This provides a centralized access and ensures safety and consistency of the database (SGBD1). Interaction with the data access layer is done using DTOs. DTOs (Data Transfer Objects) is a design pattern used to transfer data between subsystems of a software application. The service layer (Service Layer) is the business layer IRecommendIt system, this is where the services are provided by the centralized system IRecommendIt. Among the many services are services on the charging points, as the research and booking of charging points. To expose the

system services IRecommendIt uses the Web Service *EVService*. Web Services are a solution used in systems integration and communication between different applications, enabling new applications to interact with existing ones. IRecommendIt Mobile App is an application for mobile devices whose operating system is based on the set of Windows CE components, such as Windows Mobile 6.0. This application accesses to system services through the Web Service *EVService*, using http requests (Hypertext Transfer Protocol).

The Services Layer is a layer that is intended to expose business logic as services and thus serve as an abstraction of business logic. This layer was created and designed so that a future Web application can take advantage of the functionality of the system. These are services that perform operations on the system being Mobi-System that the Web Service *EVService* uses this layer to perform the operations on the Mobi-System. The services do not show any relation between them, its functioning being independent of others and consists of: (1) Service charging points (*IRechargingPointsService*); (2) Service Sights (*ISightsService*); (3) Service Recommendations (*IRecommendationsService*); (4) Service Ratings (*IClassificationsService*); (5) Service Directorates (*IDriverDirectionsService*); (6) Map Service (*IMapsService*); (7) Service Users (*IUsersService*); (8) Service Roles (*IRolesService*); (9) Service Categories (*ICategoriesService*); (10) Geocoding Service (*IGeocodingService*); (11) Car and Bike sharing service (*ICarBikeService*); and (12) Public transportation service (*IPublicTransportationService*).

6.3.1. Creating Functionalities Based on Existing Services

The way that this solution has been developed is very simple to add services and functionalities to the system, since this solution was developed in modular and incremental form. Given the suggestion of a set of users, if it would be interesting to have information on the location and availability of parking places, it is functionality fairly easy to add, which allows users to obtain directions to car parks in town and to get information on the availability of parking places. Similarly, if the user can interact with the application managing a car park, it is possible to reserve parking places and get guidance until the car park. For this task it is necessary to: (1) Add the local authority car parks to the conceptual model of the database; (2) Utilize or even replicate (in large part) the service of charging points; (3) Provide Web Service operations in *EVService*; and (4) Add a set of screens for the car parks in the application for mobile devices. The same principles were used to develop the car and bike share systems, which are described at [Daniel, 2010].

6.4. Mobile Application Usage Results (Case Study)

A system is not useful if it does not have practical application in practical situations. Thus, in this work, in the proposed definition of a model of information system, it is important to demonstrate real-world scenarios in which the system applies and is useful and important for users. Electric vehicles create new paradigms to mobility due to its limited range and long recharging times, and inevitably have impact on the day-to-day of the drivers, who have to plan their journeys and stops for recharging.

These problems will tend to decrease with the technological advances that increase the autonomy of the vehicles, and with the development of a network of battery charging places, with an increasing number of alternative sites, as well as with a larger geographical dispersion.

Current work shows three scenarios that could be considered as representative for most types of electric vehicles in the near future. The scenarios described below project what might be the reality for drivers of electric vehicles in early 2012, based on the following assumptions:

Table 6-1: Data used in the case study of Section 6.4.

Characteristics	Values
EV Autonomy	150 km
Charging Points in Portugal	1,300
Slow Charging	6 Hours
Fast Charging	30 Minutes
Change Battery	10 Minutes

6.4.1. Scenario 1 - Day-to-Day Urban

This scenario shows the use of Electric Vehicle (EV) by a driver who lives on the outskirts of a big city, and uses the EV to go to the work. The driver takes the kids to school every day, and after the job, goes to a gym session before making the return trip. His typical driving day is:

- 07:30 - He leaves home with the EV fully charged, after charging during the night;
- 08:15 - He covers 30 km until reaches the school of the first son;
- 08:30 - He traverses 5 km to reach the school of the second child;
- 09:00 - He covers 10 km to come to his work place;
- 12:30 - He goes out for lunch in his EV covering a total of 10 km;
- 18:00 - He covers 10 km to the Gymnasium;
- 19:30 - He covers 10 km to the school of the child;
- 19:45 - He covers 5 km to the school of the other son;
- 20:30 - He covers 30 km in the way back home.

The driver returns home with 25% of the EV battery capacity.

This is the optimal scenario, appointed by opinion builders to justify the viability of EV, vehicles even with the current state of autonomy. However in this scenario an extra utilization of the EV cannot exist, as leaving home in the evening for dinner, or visiting friends. Besides, in this scenario all EV owners have to be able to charge their vehicles at home overnight. For the vast majority of the population that lives in metropolitan areas, it is not possible to charge the batteries of the vehicles during the night, since the vast majority of them live in buildings without parking or garage that make possible the overnight charging. For these cases the batteries charging must be carried out during the day, or in the middle of a travel, as with today's vehicles powered by fossil fuels.

Thus, maintaining the same schedule, but removing the batteries charging during the night, the driver will enter the vehicle with 25% of the battery capacity. Figure 6-11 shows the main screen of the application with the indication of charging and battery life management system received from the battery through the adapter.



Figure 6-11: SiREV- Charging indication (SoC); EV estimated autonomy⁵³ (in Portuguese language).

The SiREV asks for user login (driver identification), see Figure 6-12:



Figure 6-12: SiREV- Login menu with driver identification (in Portuguese language).

⁵³ A charging place identified (Better Place) at 20 km; and the Context Information (driver, mode, destination and day period).

Then the system asks for operation mode (Direct or Leisure), see Figure 6-13:



Figure 6-13: SiREV- Operation mode (in Portuguese language).

Then ask for destination identification (usual destination appears in the application screen, such as home and work), see Figure 6-14:



Figure 6-14: SiREV, destination identification, usually destinations are highlighted (in Portuguese language).

The vehicle's range is 40 km, however the trip will have a total of 45 km and it will be necessary to recharge the EV batteries to get to the destination.

The SiREV presents an alert indicating the need to recharge the batteries, and shows the alternatives identified by the recommendation system. Since this is a trip to work, the goal will be to arrive as quickly as possible, so the recommendation system presents three alternatives for fast charging, and set the route, given the previous choices. The first step is to submit a recommendation to select the candidate items for the SiREV, and then it uses the information gleaned from smartgrid to create a list of all the charging points that can be reached by the vehicle. In this scenery the vehicle is in Odivelas, outside Lisbon, so the number of charging points is high. It is created a list of 30 possible charging sites. Then the list is sent to the component that manages the public transport information to validate the proximity of interfaces with different means of public transport. The component validates each of the candidate items and returns the updated list.

The next step is the processing of the recommendation. At the entrance of the recommendation system there is a list of 30 candidate items distributed as follows:

- 15 Points of slow charging:
 - 5 of EDP;
 - 5 of Better Place;
 - 5 of Mobi.E.
- 10 Points of fast charging:
 - 4 of EDP;
 - 3 of Better Place;
 - 3 of Mobi.E.
- 5 Points of drop-off (in which the batteries are replaced):
 - 1 of EDP;
 - 3 of Better Place;
 - 1 of Mobi.E.

The driver of this studied case never chooses the drop-off sites, nor it is important for him to select locations near public transport. This driver has a clear preference for places of charging of EDP, followed by Better Place, and he never charges his EV at places of Mobi.E. The algorithm returns a recommendation to run the utility with more than three items after comparison with the history of the driver choices.

The following screen is displayed to the driver, Figure 6-15:



Figure 6-15: Showing recommendation, regarding charging points that fits drivers' choices (in Portuguese language).

The driver selects the first recommendation of SiREV and sends the data on the location of the Public Charging Station (PCS) for the navigation system. Reached the PCS the charging process starts and SiREV presents progress and an indication that the vehicle performs in charging state. It is possible to visualize in a map the distance that the EV can reach with that charge. The driver can perform a charge until the desirable distance is reached (if less than the maximum range).

After the driver leaves the two children at school, SiREV continues to put a notification in the notification area that the vehicle's range is below the limit. Upon reaching the destination the driver selects the notice and recommendation system introduces three new options for charging, this time the system knows that the vehicle is at its destination because it is less than 5 km from the site displayed as a destination, so presents options for charging along three car parks within walking distance (see Figure 6-16). The batteries will charge while the driver is on his job.

After 4 hours, the driver receives an SMS notification on his phone, indicating that the batteries are fully charged (with 100% of energy storage capacity). The driver rests, assured that he can keep his routine the rest of the day, and that 150 km of EV autonomy are available until the next working day.



Figure 6-16: Recommendation of charging places nearby (in Portuguese language).

6.4.2. Scenario 2 - Long Distance Between Home and Work

This scenario presents the situation of a driver who lives at a considerable distance from his work place. The driver lives in a distant city but works in downtown Lisbon. The trip from home to work is 100 km. The driver lives in a building with a garage, but without a charging point for electric vehicle. A typical daily schedule of this driver is:

- 08:00 - Departure from home;
- 09:30 - He covers 100 km to his place of work;
- 13:00 - Out to lunch, traveling a total of 5 km;
- 19:30 - Return back home, covering 100 km.

This daily driver travel is 205 km long. Using the system SiREV, and assuming that, as in the previous case, in the morning the EV has 25% of its energy storage capacity. Upon entering the EV and after selecting the profile and identifying the destination the driver is alerted to the fact that he must charge his EV in a radius of 30 km. The system immediately displays the recommendations taking into consideration that the driver goes to his work place (see Figure 6-17).

The three options presented are of fast charging type, and have in common the fact that they are service areas that have cafeteria service. Whenever the driver needs to recharge

the EV batteries in the morning, he chooses a service station with cafeteria service, because he takes the advantage of taking the breakfast as the car recharges. While having breakfast, the driver is alerted to the fact that the EV batteries are already charged. Back to the car, he follows his route to employment. Arriving at the entrance to Lisbon the battery pack is again with a low level of charge, with only 30% of stored energy, so that the driver is alerted to that fact.



Figure 6-17: Recommendation generated because SiREV detects that EV range is below 30% of initial range.

The driver remains far from his destination, thus he is presented to all the fast charging options, and to an option of slow charging, but he is also near an interface to public transport, enabling the driver to put the car in a park covered with charging service, and continuing his journey by public transport. The driver chooses to deposit the car in the park, let the EV to be charged, and use public transport to go to the work.

After 6 hours the driver is notified that the EV batteries are fully charged, and so, he knows that can return home with his EV, because the energy stored in the batteries will be enough to cover the 100 km back.

6.4.3. Scenario 3 - Car Ride at Weekend

In this scenario, the same driver of the second scenario leaves home on a Saturday morning for a ride with the family in the western coastal zone of Lisbon.

When entering the vehicle the driver identifies himself and indicates that he will shift into drive, with no predetermined destination.

After an hour of travel, the system notifies the driver that the autonomy of the vehicle reached the configured limit of 30 km, and displays an alert, as showed in Figure 6-18.

In this situation the recommendation system will consider the following context:

- Operating mode: leisure, see Figure 6-19;
- Time of day: morning;
- Destination: No destination.

The system has the following three charging station recommendations:



Figure 6-18: Recommendation, because SiREV detects that range is below the configured limit of 30 km.

All recommendations are slow and charging points have in common the fact that they are near centers of tourist interest, with places to visit. The full charge will take about six hours, so the driver and family can visit the Points of Interest (nearby), lunch in one of several restaurants. Just four hours after the driver decides to return home. The vehicle's range is 70%, and will not reach the destination.

After walking 50 km of new drivers are notified that you have to carry the load of the vehicle. In this situation the recommendation system will consider the following context:

- Mode of Operation: leisure, see Figure 6-19;
- Time of day: Afternoon;

- Destination: House.

By stating that the destination is home, the recommendation system provides fast charging points along the route (Figure 6-25), in this context because the driver always chooses this type of sites because they want to get home as soon as possible.



Figure 6-19: Recommendation for fast charging station.

6.4.4. Scenario 4 – Looking POI with Guidance

The driver of the EV can use the Mobi-System to: (1) get directions (2) locate charging points and reserve slots, (3) get recommendations on his journey with great information needs, as local battery charging, whose handicaps are known involving the charging time and its autonomy, local information satisfaction, public transport information in case of failure, etc; (4) Points of Interest (POI); (5) smart charging strategy; and (6) electricity market participation (sell, buy, profit maximization).

After user login (authentication), there is a menu where the driver selects which operation he wants to make; this is organized as Figure 6-20 (left side). If he wants to know possible interest places, from Recommendations tab Places, he has the screen shown in Figure 6-20 (right side). The user defines which region the system should consider introducing the geographic center and radius, which can be obtained using GPS or an address. Pressing the button Get recommendations are obtained, and in this case the user wants to know Points of Interest (POI) near Seixal, in Portugal, considering a radius of 2 km. At the bottom of the screen the user will find the recommendations identified by the name and address of the location of interest. The user can get more information about the location of interest selected by pressing the Info option from the menu.




Figure 6-20: Main application screen and search for POI (Points of Interest).

Figure 6-21 shows the screens to identify a POI. Information from a point of interest is constituted by its name, address, latitude, longitude, brief description, associated categories, hours of operation and a display picture. In the user classification menu option, the user can rate the point of interest in order to help future recommendations to himself and to other users.



Figure 6-21: Screen for POI (Points of Interest).

The screen lets you annotate/classify the site of interest, with a degree of satisfaction, such as "Good." The following Figure 6-22 (left side) represents the screen. If the user wants help geographically he can access it from Map menu to display the selected site of interest, as is visible in the Figure 6-22 (right side). The site contains an identifier of interest (in this case is A), and in this screen the user has the ability to navigate the map, as well as zoom

in and zoom out. In the menu he can change the map type view (Hybrid, Roadmap, and Satellite).



Figure 6-22: Visualization and classification of POI (Points of Interest).

If he does not like the recommendations generated, he can always get all the sites in a given area by accessing the item in the Places tab View. This screen is similar to the screen that lets the user get recommendations of sights, but this one shows all the sites in a given region with the possibility of filtering according to the categories of places of interest, as shown in Figure 6-23 (left side). After the user selects possible sites of interest to visit during the holidays, he needs to know which route to use in order to visit this place of interest. The screen is in the following Figure 6-23 (right side).




Figure 6-23: Get POI (Points of Interest) and get directions.

6.4.5. Scenario 5 – Reserve Charging Slots in a Public Charging Station

On this screen the user enters start and end place and current location is taken from GPS. After pressing the button Get Directions application are indicated possible routes and also are indicated the travel time and distance. For each route the user can see the steps needed to guide him during the journey in order to reach the target site. Optionally the user can observe this route on a geographical map. After he gets the recommendations and the routes he needs to go, he also needs to know where he can recharge the EV batteries (charging points), during or after the path followed. To access the screen the user chooses Book tab Recharging Stations. This screen is shown in Figure 6-24:



Figure 6-24: Availability and reservation of slots for charging stations.

Figure 6-25 shows a PCS (Public Charging Station) slot reservation.



Figure 6-25: Reverse and submission forms on Mobi-System.

Further usage possibility available in [Borges, 2010].

6.5. SITP Application

This Section is dedicated to the description of the SITP application developed for the public transportation data integration, using main ideas expressed in Section 5.5. In Figure 6-26, extracted from [Domingues, 2010] is illustrated a typical client operation from the client side: search for stops, search information of public transportation for a certain path, get price, schedules and best itineraries path options. From the operator are showed the registration and the registration of DB schema.



Figure 6-26: Use case for SITP application.

Two Web applications were developed:

- SITP, to support queries from users;
- SITP, for the management of information by the public transportation operators.

These applications were implemented in ASP.NET MVC platform. For more details see [Domingues, 2010].

The SITP was implemented to allow the user to search for routes, stops, query times and fares. Figure 6-27 illustrates the application menu to support these functionalities.




Figure 6-27: SITP - Web Client Application Menu.

The developed application has the basic structure of a Master Page with an application menu. The menu implemented allows navigation of the site as intended, with Multi-Language support and a link to access mobile devices (see Figure 6-28 and Figure 6-29).



Figure 6-28: SITP - available menu for users.



Figure 6-29: SITP - available menu for public transportation operators.

6.5.1. SITP Cases of Usage

In this Section are described several cases of usage of SITP application.

Case one: search for near public transportation (stops), using a pre-defined radius from current user position (see Figure 6-30). Taking into account current time the SIPT indicates also close public transportation to arrive on selected stops.



Figure 6-30: Search result of a user query for a PT stop in a radius of 50m from his current position in Lisbon (Cais do Sodré). Case two: getting public transportation prices for the desired journey. In Figure 6-31 is showed the price for the Portuguese company CP (a railway company).




Figure 6-31: Search result of a user price query for CP public transportation operator (description in Portuguese Language). In Figure 6-32 is showed the SITP application on a mobile device.



Figure 6-32: SITP mobile device interface.

In Figure 6-33 is showed the menu for a public transportation operator that introduces a stop on SITP system.

Insert Stop in existent Line
Select Service: Autocarro Select Line: Isel(carris) Praça do Chile(carris) Carreira 10
Insert: Begin Number of Stops: 1
Name: Chelas
Zone: 1
Latitude: 38.755314853913696
Longitude: -9.114224909862969
List Stops:
Isel(carris)
R. Luis Cristino Silva(carris)
Areeiro(carris)
Praça do Chile(carris)



Mapa
Lat= 38.755314853913696
Lng= -9.114224909862969
Insert

Figure 6-33: Menu for public transportation operator that introduces a stop on SITP system.

6.6. Conclusion

More tests and pilots should still be performed, but in this upcoming reality is difficult to find working situations to take in order to use their data. Simulation performs an important role to give data for the used case studies. Two main applications were developed for two main mobile operation systems, Android and Windows Mobile, and for two Web applications, V2G Smart System and SITP. User acceptance of this mobile application should come from questionnaires feedback after drivers' usage.

7. CONCLUSION

Mobi-System develops a solution that supports the driver with the appropriate and relevant information to decide and plan his journey using an EV (Electric Vehicle), reducing the constraints related with the vehicle autonomy and allowing the driver to perform his journey with reduced anxiety about vehicle range. This system is in the intersection of EV integration problems (e.g., new charging infrastructures are being prepared, and several problems have been raised due to limited range autonomy and the long time of the charging process) with the new paradigm of smart cities, where a cooperative approach is established among different transportation sources. ICT, with mobile communications and mobile information systems, play an important role in this process, in the integration and real time information access. The results bring new and increasing information needs for the drivers, because information forms a key part of the driver decision process. The success of EV penetration in the market will be in part due to this information availability at the drivers' side.

The main goal of this work was to bring ICT and Information System to an upcoming growing area of sustainable mobility process in smart cities, to help the EV driver on the charging process, and to minimize the range anxiety problem. To increase EV attractiveness electricity market participation is assisted through the creation and maintenance of EV community and an integration of local renewable energy resources. Figure 7-1 shows the main work research goals and the accomplished areas of work. The main result of this work is the development of driver relevant information on a mobile device, giving an integrated view of several areas as: charging process (at home and public station) in a EV, dealing with the driver range anxiety problem, creating a community of EVs for energy market participation, integration of local renewable resource and for a diversity of options towards mobility processes in smart cities: integration of bike and car sharing systems, car pooling, public transportation information integration, and best route taking into account a diversity of transportation and environmental policy options.




Figure 7-1: Mobi-System related areas and the achieved research goals.

Figure 7.2 shows developed functions and systems for:

- EV charging or discharging operation: a management system was proposed with a smart charging strategy taking into account distribution and consumers power limitation. Since there is no real environment for testing purposes, an agent-based simulation tool was developed. Based on this tool and taking into consideration real world information (from user questionnaire's inputs and information taken from tracking systems), a home consumption analysis was performed based on agents and using a stochastic process. Taking into account the limitations of the distribution network and the user's power contracts, a smart charging strategy was identified (basically this is an indication of the maximum power through time that the charging process can use). In the author's opinion more complexity could be introduced on this tool, such as microgeneration and discharging process (when EV batteries send part of the stored energy back to the electrical grid). The geo-reference in a graph, the electrical distribution network and a visualization tool were

also proposed, which can help the planning of new distribution infrastructures and the identification of regions of power constrains.

- Electricity Market participation: our main contribution was the definition of a conceptual system to create and manage the EV community. This is an innovative credit-based system that also involves a collaborative broker for DER (Distributed Energy Resources). Using this credit-base system, together with rankings, the users can profit from an open and healthy competitive environment. Also, in the future, to increase the market share of EVs, there will be a need of these types of systems to explore the energy market potential of these types of vehicles. Also, renewable energy sources integration and microgeneration can benefit from a community coordination action, where users can capture renewable energy produced in excess on local generation, at lower prices, avoiding electrical energy transportation loses.




Figure 7-2: Developed Functions and System for Mobi-System for EV related and electricity market related functions.

In this work it was proposed the integration of information from various areas that will for sure participate in the successful implementation of a mobility model for drivers of Electric Vehicles. However it was extremely difficult to find projects and technologies mature enough for the actual operating environment. There are prototypes from several players, mostly from universities or government projects. There are also some projects of companies

starting in this market business, but most of them are in the process of prototyping or market testing phase. Additionally, it is very difficult to find specifications and standards to be globally used and accepted for exchange of information, particularly with the smart grid systems, public transport systems, control systems for charging batteries, and the electricity market. The data exchange from a technical standpoint it was chosen to submit asynchronous communication modes based on open specifications (e.g., XML files). It was also necessary to ensure that the integration model is sufficiently generic and flexible to be adapted to different systems, having a low impact on the implementation of Mobi-System. The simulation platform could have a great impact on this startup phase, since there are few real cases to test.

In transportation a diversity of systems to reduce usage of own vehicles was created, reusing pieces of software code and approaches created for charging process and electricity market participation (credit mechanisms, charging spots reservation). The main contribution is the Public Transportation data integration and the diversity of systems (car sharing, bike sharing, car pooling) on a user single interface combined with the best path or decision to go from point A to point B. This integrated view is important for end-users, but also for government or public operators, because it gives a transparent overview, where it is easy to identify lack of services in certain areas. It is also important for areas where public offer is well dimensioned to introduce more severe penalties for the usage of own car. Besides, Green Router Planers can be adapted for local policies, where the arc cost between two nodes can be adjusted to local preferences or policies.

This work benefits from author's background in Computer Science, from his automobile work experience, and also from his position as Professor at ISEL, where during the last three years he has supervised four master projects and nine final year projects in the Informatics Department.

7.1. Future Work

Electric Vehicles (EV) will open new business opportunities, because this type of vehicles needs more user interactions and systems to support its operating processes. OEMs (Original Equipment Manufacturers) will need to open access to vehicle information and a standardization process will play an important role. In this sense Telematics and Communications are good businesses opportunities. Traditional and new EV OEMs are betting heavy on Telematics: Renault Nissan, PSA, REVA, Th!nk, GM, and Ford, among others, are all gearing up with value-added Telematics features. This reality, added to Electricity Market participation, and Sustainable Mobility policies towards CO₂ emissions reductions, will raise this tendency and opens new opportunities, especially in giving right and important information to drivers through mobile devices.

To finalize, the author is aware that an alternative to the use of a mobile device (development option in this work) is the use of the navigation system device of the own Electric Vehicle, but the sustainable mobility function (described in Chapter 5) will always benefit from a mobile device option, because a mobile device can go with the user to everywhere, becoming the user's communication device. One future possibility is that these mobile devices could be mirrored in the Electric Vehicle (in the navigation system or in other equivalent device).

It is possible to follow MDD (Model-driven engineering) approach to model Mobi-System and the creation of specific metamodel for EV mobile system, follow an approach performed in XIS-Mobile [Ribeiro, 2014].

7.2. Expected Impacts of Current Work

Mobi-System provides to the drivers relevant information about public transportation, parking, car sharing system and charging stations. The creation of communities also provides conditions for electrical market participation, and consequently may provide the means to use the available spare power capacity (also allowing renewable energy integration) in each parked vehicle, avoiding the need of maintaining the excess of conventional electricity generation capacity currently required to provide regulation, spinning reserves and power peaks.

V2G model may have the potential to transform both energy and transport systems in profound ways, by promoting the deployment of alternative vehicle technologies, reducing inefficient investment in conventional generation, and supporting the installation of renewable electrical energy sources, including microgeneration.

Part of this work was submitted to the recent FCT call [FCT, 2010] with the project here described:

- Proposal Title: EV-Cockpit: Personal Mobile System for Electric Vehicle Control (PTDC/SEN-TRA/118302/2010).
- Abstract: *Project will create a mobile device application to assist EV drivers, receiving EV related information and created a diversity useful EV related information. Main project purpose is to get expertise from different group areas, such as information systems, mobile devices, communications, telematics and power electronics area to create a new product application: Mobile application with EV related information. Regarding the current problem (e.g. Drivers access EV related information) three main approaches could come out: (1) integrated system on EV, developed by OEM; (2) web application on desktop; and (3) mobile application. This problem could be similar to orientation devices (GPS) for vehicles, where there is two main consumers approaches: (1) taking solutions from OEM, full integrated in the vehicle; and (2) external devices for vehicle integration. This second solution is most chosen by the drivers because the price, most of the times are ten to twenty times cheaper. So we think that in future the EV mobile application will be a growing market with the possibility of drivers integrated several vehicles in the same mobile.*

Part of this work in collaboration with INTELI was submitted to a tender call to FP7 in May 2011 [Tender, 2011]: SMART 2011/0065 "The impact of ICT R&D in the large scale deployment of the electric vehicle", where an impact study will be focus on relevant problems and drivers of the ICT R&D in the large-scale deployment of the electric vehicle. This proposal identifies the present course of action of the UE for EV smart system and infrastructures and identifies its path dependence.

Also current work was the basis for a Portuguese FP7 project submission under the call GC-ICT-2011.6.8f - Integration of the FEV in the Cooperative Transport Infrastructure:

- Proposal Title: Electro-Mobility Cockpit Systems and Applications for FEV Range Optimisation and Seamless Integration in the Cooperative Transport Infrastructure (MOBI.Cockpit).
- Abstract: *Full electric vehicles (FEV) are being introduced in the market, but batteries reduced energy storage capacity and the lack of a high density charging infrastructure limit their autonomy range. In order to overcome this limitation, we propose developing a new solution enabling drivers to drive longer distances. This will be achieved by integrating some components of the cooperative transport infrastructure (charging system, public transport system and the vehicle), thus increasing driving autonomy through energy consumption reduction and driving efficiency. Integration with the charging infrastructure allows the driver to plan his journey considering charging points position, booking a charging point for a time period to perform battery charging, increasing the distance he can drive comfortably without fearing running-out the battery. Integration of FEV with public transport system allows extension of driving autonomy beyond the storing capacity of vehicle's battery. Supplying information on availability, schedule and price of public transport allows the driver to plan the journey using FEV and public transportation in a complementary way, using functions as car parking booking (and charging) and ticket buying. Energy consumption reduction on-board is the third approach to be addressed as one of the main ways to increase the autonomy of the vehicle. The adoption of new driving patterns and the possibility of automation of some of vehicle functions such as air-conditioning and speed limit, brings less energy consumption and increase autonomy. The outcome of this Project is the MOBI.Cockpit System (MCS) that includes three users' interfaces: mobile device application, infotainment and web application, supporting users in taking efficient decisions. MCS has the mission of supporting EV drivers on range optimization using intelligent route planning (taking into account public transportation information), charging management and energy efficiency, fostering electric vehicles adoption.*

Also, this work is part of the current participation of ISEL in the “Seamless Travel across the Atlantic Regions using sustainable Transport” (START) project. This PhD research

contributes for the START project with best path algorithm, a proposal for public transportation information integration and an ontology for public transportation.

ANNEX

A.1 Ontology for Public Transportation (OPT)

OPT is built on top of Resource Description Framework (RDF), thus it inherits its concepts: resource, propriety, datatype and class. Figure 5-23 shows the hierarchy of OPT concepts: (1) Resource is one of the bases of RDF. It represents all things described and is the root construction. It is an instance of MOF classes. (2) Property defines the relation between subjects and object resources, and is used to represent relationships between concepts. Ontology class attributes or associations are represented through proprieties. (3) Ontology is a concept that aggregates other concepts (classes, properties, etc). It groups instances of other concepts that represent similar or related knowledge. (4) Classifier is the base class of concepts that are used for classification and is divided in: (i) datatype, a mechanism for grouping primitive data; (ii) abstract class; and (5) Instance that is the base class and is divided in individuals and data values.

Property: is a relation between a subject resource and an object resource. There are two types of properties: (1) object property, that may additionally be: transitive, symmetric, functional and inverse functional; (2) datatype. Users can relate properties by using two types of axioms: (1) property subsumptions, which specify the extension of a property and are subset of the related property; (2) property equivalence, which defines extensional equivalence.

Classifier: class that represents a concept for grouping resources with similar characteristics. It is similar to the concept of classes defined in Unified Modeling Language (UML) but with an orientation to object programming languages, and they are set theoretic. Classdescription is defined as a subclass of class to solve the problem of dynamic classifier. The class can be defined in the following four ways: (1) AllDifferent states that all of its instances have different identity; (2) restriction; (3) enumeration of individuals that form the instance of a class; (4) logical class of all individuals that could have the following attributes: (i) union; (ii) complement; (iii) intersection.

This is a work developed at ISEL under a Final Year Project integrated in the START project (for more details see [Domingues, 2010]). From several public transportation data

base of consortium partners and standard specification, such as SIRI⁵⁴ (Service Interface for Real Time Information) and IFOPT⁵⁵ (Identification of Fixed Objects in Public Transport), as well as information provided by public transport operators, a procedure to design the ontology schema was created. Figure A-1, extracted from [Domingues, 2010] shows the main entities of the domain model. OPT is built on top of RDF using OWL (Ontology Web Language).

Also in Figure A-1 is represented the relationship between the entities Operator, Service and Contact. Public transport operators are represented by the entity Operator. This entity is associated with the entity that represents the Service(s) provided by a particular operator. For example, indicates the case that the operator Carris offers two services: bus and tram. The relationship with the entity Contact is due to the need that exists to represent the contacts provided by operators of public transport.




Figure A-1: Entities in the main domain model.

The Contracting Service, Figure A-2 extracted from [Domingues, 2010], represents the services provided by an operator of public transport that can be, e.g., rail, road, air or water (sea, river or lake). Each service is linked to a type, represented by the entity Type, which

⁵⁴ <www.siri.org.uk>.

⁵⁵ <www.ifopt.org.uk>.

represents the categories within each mode, e.g., rail, bus, plane or ship. Within these types may still exist variants: Variant entity.




Figure A-2: Transportation service hierarchy.

The Contact entity, Figure A-3, represents the contact types, such as: electronic mail (e-mail), telephone, address and website. This authority is shared by all entities, Operator and POI (Points of Interest), because both the transport operator and POI have similar types of contact. POI entity are divided into categories that highlight, for example, Academic (Academic), Rest (Restoration), Monument (Museums), and others.




Figure A-3: Contact hierarchy.

Also Figure A-4 illustrates the relationship between the entities Schedule, Stop, POI, Interface and Contact. Stop entity include the attributes: name of the stop, geographical coordinates (Latitude, Longitude) zone (taking the subway, as an example, it verifies the existence of two areas, one inside the city limits and another in the vicinity).




Figure A-4: POI hierarchy.

The relationship between Stop and Schedule is justified with the representation of a schedule (see Figure A-5). A detailed description can be found at [Domingues, 2010].




Figure A-5: Stop Hierarchy, [Domingues, 2010].

A.2 Search Public Transportation Routes

To search for Public Transportation routes were considered several criteria's: The first is based on the selection of operators connected with the research. The second considers the number of transfers and price of the desired trip; and the last based on the trip duration using best path algorithm. In Figure A-6 is described in a sequence diagram the search process. The first's steps are the operator registration, where it receives an ID and publish the DB schema.




Figure A-6: Sequence Diagram of user search of Public Transportation stops and best path in different operators, [Domingues, 2010].

A.3 Best Path Implementation

To calculate the paths it was considered two phases. At first it is checked whether the stations of departure and arrival belong to the same line. So when the departure and arrival stations belong to the same line *IsSameLine* the field is marked as true, otherwise it is marked as false. Where *IsSameLine* be true is executed the first phase of the research journey thus obtaining the data required to design the course. These data highlight the coordinates of the stations, the price of the trip, points of interest that are near the station of arrival and other information such as schedules and features. If *IsSameLine* is false then runs the second phase. In the second phase, the stations of departure and arrival are not on the same line. It is therefore necessary to find a path or paths considering the available interfaces on the lines corresponding to the stations of departure and arrival. This research takes advantage of the method *getAllInterfacesBetween*. This method was implemented in a recursive manner to allow the taking of all possible paths between two stations. To obtain the pathways analysis was carried out taking into account the interfaces of the line of the station that is being verified. In each interface is checked if the line matches the line of the arrival station guarding the path and if so, otherwise, it uses recursion repeating the analysis to find a route. A sample calculation (s) route (s) is illustrated in Figure A-7. Figure A-7 shows the paths generated between the starting point Odivelas (metro line) and the arrival point for Oriente (metro line). The first route uses only one interface (Saldanha (interface metro line)) to reach the destination while the second route uses two interfaces (Campo Grande (interface metro line) and Alameda (interface metro line)) to reach the same destination. In the case of route X as there is no interface that the route reaches the destination is not valid.

The method *getAllInterfacesBetween* to be implemented recursively have to take care to avoid cycles. To prevent cycling was implemented *VerifyCicleInPath* method that checks if the route has passed or not by a given interface. If so this path is excluded. The route shows to the user by taking advantage of Google Maps API. Information relating to the route is via steps with possibility to download the route to a text file.




Figure A-7: Path Search using interfaces.

A.4 Calculate the Price of the Trip

To calculate the price of the trip was defined *InfoServiceZone* the class containing the service identifier and zone. This class is used in the method *ObtainArrayTickets* to get a list of services and areas used on a trip, or a list in which each position corresponds to an instance of *InfoServiceZone*. This represents an instance of *InfoServiceZone* stage of the journey. After obtaining the list of stages of the method is invoked *CalcPrice*. This method evaluates the list of steps in order to return the price of the journey. Analysis of the list of steps highlight the fact that the next step is to compare with the previous order to ascertain whether there was an exchange zone or service. This comparison can then calculate the price given the exchange area or service over the route.




Figure A-8: Price calculation taking into account the zone information.

As mentioned before a route is divided into stages. Figure A-8 shows that the route is only done by a service ($IdService = 1$), so the price calculation takes into account the zones (Zone) of the steps. Once the trail starts in Area 2 the price to be added is € 1.10. When you perform the initial exchange of steps, from Step 1 to Step 2, it is verified that the area is below the Step 2 from Step 1. The fact that this happens will not affect the current price. If the area of Phase 2 was superior to that of Step 1 then the price would be the sum of the pricing zone subtracted from Step 2 to the pricing of the zone in Step 1. In return for the second stage, from Step 2 to Step 3 is to be noted that the pricing is the same zone is not changed. Please note that these calculations are made for services where the services allow transfers in your network. If the services do not allow transfers in calculating the price is the sum of the prices of each step. Assuming that the service ($IdService = 1$) does not provide the transfer on your network with a single ticket is the price of 2.70 € ($1.10 € + 0.80 € + 0.80 €$). The search page provides the user stops the ability to search stops in a certain radius. To implement this research used the Google Maps API, where the user can select a point on the map to determine if there are stops and a certain radius around that point. The radius is chosen by the user through a DropDown available for this purpose. If there are stations within the radius desired markers are placed with the operator logo on the coordinates where they are. The user can view station information by interacting with the markers. The information provided is related to service characteristics with the characteristics of the station, as well as information on upcoming departures of service. It is also available to the user the possibility to observe the line where the station is located. This was implemented in AJAX with ActionResult Controllers, for details see [Domingues, 2010]. Thus, whenever a request is made, the Controller responsible for the care of returns information about the form of a JsonResult which is treated in the Client (JavaScript). Client-side (JavaScript) is methods that deal with the response and put the information available to the user. To determine the stations that lie within the perimeter defined by the user, the method *GetAllStopsInArea*. To find the two stations are set intervals by adding and subtracting the radius of latitude and longitude of the point chosen. Once these intervals a search is performed to determine the geographic coordinates of the stations that lie within these.

Regarding the Rates page is provided information on the tickets of a particular operator such as area, price and description. This information is represented whereas the seasons,

although the same line, may belong to different zones with different price lists. Thus, the user gets the price depending on the area from where or where it goes. As an example, the journey from Campo Grande station (metro line) station Odivelas (metro line). In this case, the patient away from a station belonging to a zone must purchase a ticket for zone 2 since it moves to a station that belongs to zone 2. The same happens in reverse.

BIBLIOGRAPHY AND REFERENCES

Adrian T., M. L., (2009). Active Management of Distributed Energy Resources Using Standardized Communications and Modern Information Technologies. *IEEE Trans. Ind. Electron.*, pp. 4029-4037.

Aggassi S., (2009) World without oil, better place builds a future for electric vehicles. Available at: <<http://www.mitpressjournals.org/doi/pdf/10.1162/itgg.2009.4.4.125>>, last accessed on October 2013.

Almeida H., (2008). Portugal, Spain Sign Green Car Partnership. Available at <<http://technology4life.wordpress.com/2008/01/22/spain-and-portugal-sign-green-car-partnership>>, last accessed on October 2013.

Almeida J., Ferreira J., (2013). BUS Public Transportation System Fuel Efficiency Patterns in proceedings of the 2nd International Conference on Machine Learning and Computer Science (IMLCS'2013) 24-25 August, Malaysia.

American Trade Initiatives, (2001). Sustainable transportation practices in Europe. R.N.F.P., Federal. Washington, DC., Federal Highway Administration. Available at <<http://international.fhwa.dot.gov>>, last accessed on December 2011.

Andrieu C., et al., (2005). Distributed Network Architectures D1.7. Available at <<http://www.crisp.ecn.nl/deliverables/D1.7.pdf>>, last accessed on October 2013.

Argone, (2009). Climate change. Available at <<http://buildecu.wordpress.com/2009/05>>, last accessed on October 2013.

Barkenbus J. N., (2010). Eco-driving: An overlooked climate change initiative, *Energy Policy*, 38, issue 2, p. 762-769.

Barth M. J. H., Todd, M., (2001). Performance evaluation of a multi-station shared vehicle system. *IEEE Intelligent Transportation Systems Proceedings*, Oakland, CA.

Belchior A. I., Silva A.R., (2011), eXcitingTrails/Events: Events for Touristic Scenarios, in *Anais do VI Congresso Ibero-americano de Telemática (CITA 2011)*, *Cadernos de Informática*, v.6, n.1, 2011, UFRGS.

BenHabib, M.C., et al., (2006). Power Electronic System and ICT-requirements for novel electricity distribution grids. *Flexible Electricity Grids*.

Bento C. R. N., (2010). V2G SMART SYSTEM: Sistema inteligente para gestão de carregamentos de veículos eléctricos. Final Year Project at ADEETC – ISEL, Lisbon.

Bizer C. P., (2009). The D2RQ Platform - Treating Non-RDF Databases as Virtual RDF Graphs. Available at <<http://www4.wiwiss.fu-berlin.de/bizer/d2rq>>, last accessed on October 2013.

Black W. R., (2002). *Social Change and Sustainable Transport*. Indiana University press.

Borges L. B., (2010). IRecommendIt: Sistema de recomendação para veículos eléctricos. ADEETC, Lisbon, ISEL. Final Year Project.

Brady J., (2010). *Electric Car Cultures: An ethnography of the everyday use of electric vehicles in the UK*. Masters thesis, Durham University. Available at <<http://etheses.dur.ac.uk/690>>, last accessed on December 2011.

Brooks A., (2001). Integration of electric drive vehicles with the electric power grid—a new value stream, in *18th International Electric Vehicle Symposium and Exhibition, Berlin*. Available at <http://www.acpropulsion.com/EVS18/ACP_V2G_EVS18.pdf>, last accessed on December 2011.

Brooks A., (2002). **Vehicle-to-grid demonstration project: Grid regulation ancillary service with a battery electric vehicle.** AC Propulsion. Available at <<http://www.udel.edu/V2G/docs/V2G-Demo-Brooks-02-R5.pdf>>, last accessed on October 2013.

Caiso, (2004). **California ISO Annual Report. C. I. S. Operator.** Available at <<http://www.caiso.com/2777/27778a322d0f0.pdf>>, last accessed on December 2011.

California Independent System Operator, Washington, DC: **Federal Energy Regulatory Commission.** . (2004). **Federal Energy Regulatory Commission.** Available at <<http://www.ferc.gov/docs-filing/eforms/form-714/data/2004/WECC.zip>>, last accessed on December 2011.

Caragliu A. D. B., Nijkamp C. P., (2009). **Smart cities in Europe. Serie Research Memoranda 0048, VU University Amsterdam.** Available at <http://www.im.ethz.ch/education/FS11/iot_2011_slides/08_SmartCities_OliverHaubensak.pdf>, last accessed on December 2011.

Carb, (2000). **Staff Report for the 2000 Zero Emission Vehicle Program Biennial Review. C. A. R. Board. Sacramento, California.** Available at <http://www.ppic.org/content/pubs/cep/EP_907LBEP.pdf>, last accessed on December 2011.

Casals M., (2009). **Topological Complexity of the Electricity Transmission Network PhD thesis.** Universidade Politecnica de Catalunya.

CENELEC, (2011). **Final report of the CEN/CENELEC/ETSI Joint Working Group on Standards for Smart Grids.**

Cervero R. C., et al., (2002). **Assessment of Short-Term Travel-Behavior Impacts. City CarShare. I. o. U. R. Development. San Francisco.** Available at <<http://escholarship.org/uc/item/7fn8966c>>, last accessed on December 2011.

Chau C. C. C., (2001). **Modern Electric Vehicle Technology. Oxford - UK, Oxford Science Publications.**

Cochran J. L. B., (2012). **Integrating Variable Renewable Energy in Electric Power Markets: Best Practices from International Experience. NREL - National laboratory of the U.S. Department of Energy.**

COM, (2007). **“Results of the review of the Community Strategy to reduce CO2 emissions from passenger cars and light-commercial vehicles”, Brussels, 7.2.2007.** Available at <http://eur-lex.europa.eu/LexUriServ/site/en/com/2007/com2007_0019en01.pdf>, last accessed on October 2013.

Costa D., (2010). **Bike and Car Sharing System. MSc dissertation – ADEETC – ISEL, Lisbon.**

Crowley C. and Joutz F., (2003). **Hourly electricity loads: Temperature elasticities and climate change. In 23rd U.S. Association of Energy Economics North American Conference.**

Dasgupta S., S. N., (2012). **A Plug and Play Operational Approach for Implementation of an Autonomous-Micro-Grid System. IEEE Trans. Ind. Inform., pp. 615-629.**

DOC, (1999). **The Effect on the National Security of Imports of Crude Oil and Refined Petroleum Products, Bureau of Exports Administration, US Department of Commerce.** Available at <<http://www.bis.doc.gov/defenseindustrialbaseprograms/osies/defmarketresearchrpts/effectofcrudeoilandrefinedpetroleumnationalsecurity1989final.pdf>>, last accessed on December 2011.

Dolle D. V., (2009). **Intelligrid Architecture, EPRI.** Available at <<http://intelligrid.epri.com>>, last accessed on December 2011.

Domingues D., (2010). **SITP – Sistema de Informação sobre Transportes Públicos. Final Year Project at ADEETC – ISEL, Lisbon.**

Dowds J., et al., (2009). A Review of Results from Plug-in Hybrid Electric Vehicle Impact Studies, University of Vermont (VT). Available at <http://www.cems.uvm.edu/~phines/publications/2009/dowds_2009_phevs.pdf>, last accessed on December 2011.

EC, (2001). Towards an European Strategy for the Security of Energy Supply. Brussels, Green Paper of the European Commission. Available at <http://www.em.gov.lv/images/modules/items/ae_2.pdf>, last accessed on October 2013.

EC, (2009). DIRECTIVE 2009/28/EC of the European Parliament and the Council, Brussels, 23.4.2009.

EC, (2011). Transport: White paper 2011 - European commission. Available at <http://ec.europa.eu/transport/strategies/2011_white_paper_en.htm>, last accessed on October 2013.

Elektromobilität, (2010). Vorschriften im Bereich Kraftfahrzeugtechnik und Gefahrguttransporte (Electromobility regulations in automotive technology and the transport of dangerous goods); Report of the team “Vorschriftenentwicklung” in Working Group 4 (Normung, Standardisierung, Zertifizierung) of the German National Platform for Electromobility (NPE).

ENE, (2009). Cabinet Resolution n° 29/2010, of 15th April - ENE2020, Portugal. Available at <www.ren.pt/SiteCollectionDocuments/Investidor/RelatóriosAnuais/2010/en/Legislationin2010andGlossary/Electricity.html>, last accessed on October 2013.

Energycs, (2005). 2004-2006 MY Plug in Hybrid Electric Vehicle (PHEV) Toyota Prius with Valence Saphion battery pack. Available at <<http://www.iiasa.ac.at/Admin/PUB/Documents/IR-06-025.pdf>>, last accessed on December 2011.

Epri, (2001). Comparing the benefits and impacts of hybrid electric vehicle options. Palo Alto, California, Electronic Power Research Institute. Available at <http://ourenergypolicy.org/docs/9/Comparing_Hybrid_Electric_Vehicle_Options.pdf>, last accessed on December 2011.

ERSE, (2009). Available at <<http://www.erse.pt/pt/electricidade/mibel/construcaoesenvolvimento/Paginas/2009.aspx>>, last accessed on December 2011.

Eurostat, (2009). Statistics. Available at <http://epp.eurostat.ec.europa.eu/portal/page/portal/statistics/search_database>, last accessed on December 2011.

EWEA, (2008). PurePower—Wind energy scenarios up to 2030, European Wind Energy Association. Available at <http://www.ewea.org/fileadmin/ewea_documents/documents/publications/reports/purepower.pdf>, last accessed on October 2013.

EWEA, (2009). EWEA Offshore Report 2009. Available at <http://www.ewea.org/fileadmin/ewea_documents/documents/publications/reports/Offshore_Report_2009.pdf>, last accessed on October 2013.

EWEA, (2012). Wind in power: 2011 European statistics. Available at <<http://www.ewea.org/statistics/european-statistics>>, last accessed on October 2013.

EWEA, (2013). Wind in power: 2012 European statistics. Available at <http://www.ewea.org/fileadmin/files/library/publications/statistics/Wind_in_power_annual_statistics_2012.pdf>, last accessed on October 2013.

F. Benzi, N. A., (2011). Electricity smart meters interfacing the households. IEEE Trans. Ind. Informat., pp. 4487-4494.

FCT, (2011). “EV-Cockpit: Personal Mobile System for Electric Vehicle Control” (PTDC/SEN-TRA/118302/2010).

FERC, (2004). Form 714, California Independent System Operator, Washington, DC: Federal Energy Regulatory Commission, 2004. Available at <<http://www.ferc.gov/docsfiling/eforms/form-14/data/2004/WECC.zip>>, last accessed on December 2011.

Ferreira J., Paulo T., Porfírio F., (2009). Collaborative Car Pooling System. Proceedings of International Conference on Sustainable Urban Transport and Environment. Paris.

Ferreira J., Afonso J.L., (2010). A Conceptual V2G Aggregation Platform. EVS-25 -The 25th World Battery, Hybrid and Fuel Cell Electric Vehicle Symposium & Exhibition. Shenzhen, China.

Ferreira J., Trigo P, Silva, Coelho H., Monteiro V., Afonso J.L., (2010a). Simulation of Electrical Distributed Energy Resources for Electrical Vehicles Charging Process Strategy. Proceedings of the Second Brazilian Workshop on Social Simulation (BWSS-2010), pp.82-89, IEEE Computer Society, 2010.

Ferreira J., Afonso J.L., (2011a). Towards a Collective Knowledge for a Smart Electric Vehicle Charging Strategy. International Conference on Industrial and Intelligent Information (ICIII 2011) Bali - Indonesia.

Ferreira J., Pereira P., Porfírio F., Afonso, J. L., (2011b). Recommender System for Drivers of Electric Vehicles. International Conference on Network and Computer Science (ICNCS 2011). Kanyakumari India.

Ferreira J., Silva A.R., Monteiro V., Afonso J.L., (2011c). Agent based approaches for Smart charging strategy for Electric Vehicle. Proceedings of EVTEC 11, 1st International Electric Vehicle Technology Conference (Japan-Yokohama, 17-19 May 2011).

Ferreira J., Silva A.R., Monteiro V., Afonso J.L., (2011d). EV_Cockpit-Mobile Personal Travel Assistance for Electric Vehicles. Proceedings of AMAA 2011, 15th Int. Forum on Advanced Microsystems for Automotive Applications “Smart Systems for Electric, Safe and Networked Mobility”, (Germany-Berlin, 29-30 June 2011).

Ferreira J., Silva A.R., Monteiro V., Afonso J.L., (2011e). Smart Electric Vehicle Charging System. Proceedings of IV 2011, IEEE Intelligent Vehicles Symposium (Germany, Baden-Baden, June 5-9, 2011).

Ferreira J., Filipe P., Silva A.R., (2011f). Multi-Modal Transportation Advisor System. Proceedings of IEEE FISTS Forum (Austria-Vienna, June 29 - July 1, 2011).

Ferreira J., Silva A.R., Monteiro V., Afonso J.L., (2011g) Collaborative Broker for Distributed Energy Resources. Proceedings of International Symposium on Computational Intelligence for Engineering Systems (ISCIES 2011) (Portugal, Coimbra, Nov. 16 to 18, 2011).

Ferreira J., Silva A.R., Monteiro V., Afonso J.L., (2012). Electric Vehicle Route Recommender System, 1st International Conference on Smart Greens, Porto-Portugal, April 2012.

Ferreira J., Silva A.R., Monteiro V., Afonso J.L., (2012a). Real Time Information Extraction of an Electric Vehicle. Proceedings of the Annual Seminar on Automation, Industrial Electronics and Instrumentation (SAAEI'12), in its nineteenth edition, will be held at the Escola de Engenharia of the Universidade do Minho, in Guimarães, Portugal, in the days 11, 12 and 13 of July of 2012.

Ferreira J., Silva A.R., Monteiro V., Afonso J.L., (2013). Collaborative Broker for Distributed Energy Resources. Computational Intelligence and Decision Making - Trends and Applications, ISBN 978-94-007-4722-7, Springer, 2013.

Ferreira J., (2013a). Green Route Planner. Nonlinear Maps and their Applications, Selected Contributions from the NOMA 2011 International Workshop. Series: Springer Proceedings in Mathematics & Statistics, Vol. 71. Grácio, C.; Fournier-Prunaret, D.; Ueta, T.; Nishio, Y. (Eds.), ISBN 978-1-4614-9160-6, December 2013.

Ferreira J., Filipe P., Martins P., (2013b). Cooperative Transportation Infrastructure in proceedings of the International Conference on IT and Intelligent Systems (ICITIS'2013), 28 - 29 August, Malaysia.

Ferreira J., Silva A.R., Monteiro V., Afonso J.L. (2013c). Moby.Cockpit Project for EV Seamless Integration in the Cooperative Transport Infrastructure. Proceedings of the International Conference on IT and Intelligent Systems (ICITIS'2013), 28 - 29 August, Malaysia.

Ferreira J., Silva A.R., Monteiro V., Afonso J.L., (2013d). Dynamic Range Prediction for an Electric Vehicle. Proceedings of the 27th Electric Vehicle Symposium (EVS27), 17 -20 de November in Barcelona.

Ferreira J., Silva A.R., Monteiro V., Afonso J.L., (2013e). Vehicle-to-Anything Application (V2Anything App) for Electric Vehicles. Industrial Informatics, IEEE Transactions on Volume: PP, Issue: 99. Digital Object Identifier: 10.1109/TII.2013.2291321, Publication Year: 2013 , Page(s): 1

Figueiredo V., et al., (2010). An Electric Energy Consumer Characterization Framework based on Data Mining Techniques; IEEE Transactions on Power Systems; Vol. 20, n.2, pp. 596-602.

Fontes T. F., (2008). Determinação do melhor caminho em sistemas de transporte terrestre (BPath – Best Path). Final Year Project at ADEETC – ISEL, Lisbon.

France E. d., (1986). Le Micro Réseau : 30 ans d'activité Direction des Etudes et Recherches. Power and Energy Society General Meeting, ISBN: 978-1-4244-6549-1.

Franco G., Sanstad A., (2008). Climate change and electricity demand in California. Climatic Change 87:139–151.

Gartner, (2010). Gartner Says Worldwide Mobile Phone Sales Grew 17 Per Cent in First Quarter 2010. Available at <<http://www.gartner.com/it/page.jsp?id=1372013>>, last accessed on October 2013.

Geada M. and Nunes R., (2011). SGI-VE: Sistema para Gestão de Informação num Veículo Eléctrico. Final Year Project at ADEETC – ISEL, Lisbon.

Gediminas A., (2005). Toward the Next Generation of Recommender Systems: A Survey of the State-of-the-Art and Possible Extensions, IEEE Transactions on Knowledge and Data Engineering, Vol. 17, N°. 6, June 2005.

Gini C., (1921). Measurement of inequality of income. Economy Jornal V31: 124-125.

GroupI, (2001). IPCC, Climate change 2001: the scientific basis. Third Assessment Report of the Intergovernmental Panel on Climate Change, Geneva. Available at <<http://www.ipcc.ch/ipccreports/ar4-wg1.htm>>, last accessed on December 2011.

Guerreiro R., (2011). Sistema de Apoio à Criminologia, MSc dissertation, ADEETC – ISEL, Lisbon.

Guille C., Gross G., (2009). A conceptual framework for the vehicle-to-grid (V2G) implementation. Energy Policy, vol. 37, no. 11, pp.4379 -4390.

Gungor, V. B. L., (2010). Opportunities and challenges of wireless sensor networks in smart grid. IEEE Trans. Ind. Inform., vol.57, pp. 3557-3564.

Gungor, V. D. S., (2011). Smart grid technologies: Communications technologies and standards. IEEE Trans. Ind. Inform., pp. 529-539.

Gungor, V. D. S., (2013). A Survey on Smart Grid Potential Applications and Communication Requirements. IEEE Trans. Ind. Inform., pp. 28-42.

Hagbhin, S. L., (2013). Grid-Connected Integrated Battery Chargers in Vehicle Applications: Review and New Solution. IEEE Trans. Ind. Electron, pp. 459-473.

Hajimiragha, A. H., C. A., (2010). Optimal transition to plug-in hybrid electric vehicles in Ontario, Canada, considering the electricity-grid limitations, *IEEE Trans. Ind. Electron.*, pp. 690-701.

Hawkins D., (2001). Vehicle-to-grid: a control area operators perspective. EVAA Electric Transportation Industry Conference. Sacramento, CA.

Hirst E., Kirby B., (1998). Technical and market issues for operating reserves. Tennessee, Consulting in Electric-Industry Restructuring.

IEA, (2013). Global EV outlook -Understanding the Electric Vehicle Landscape to 2020. Available at <http://www.iea.org/topics/transport/electricvehiclesinitiative/EVI_GEO_2013_FullReport.pdf>, last accessed on October 2013.

Jana K. (1998). Electric Vehicle Application Handbook For Genesis Sealed-Lead Battery, report available at <www.evdl.org/docs/hawker4e.pdf>, last accessed on October 2013.

Jones A. E., et al., (2010). Incentives for Microgeneration Development in the U.S. and Europe. IECON 2010-36th Annual Conference on IEEE Industrial Electronics Society, Glendale, AZ, USA, 2010.

Kassatly S, (2010). The Lithium-Ion Battery Industry For Electric Vehicles. MIT.

Kempton W., (1997). Electric vehicles as a new power source for electric utilities. *Trans. Res. D* 2(3): 157–175.

Kempton W., (2000). Electric-drive vehicles for peak power in Japan. *Energy Policy* 28: 9–18.

Kempton W., et al., (2009). A Test of Vehicle-to-Grid (V2G) for Energy Storage and Frequency Regulation in the PJM System. Mid-Atlantic Grid Interactive Cars Consortium Jan. 2009. Available at <<http://www.magicconsortium.org/Media/test-v2g-in-pjm-jan09.pdf>>, last accessed on October 2013.

Kempton W., Kubo T., (2000). Electric-drive vehicles for peak power in Japan. *Energy Policy* 28: 9-18.

Kempton W., Letendre, S., (1997). Electric Vehicles as a new power source for electric utilities. *Transportation Research Part D*, 2.

Kempton W., Tomić J., (2005). Vehicle-to-grid power fundamentals: Calculating capacity and net revenue. *Journal of Power Sources* 144: 268-279.

Kempton W., Tomić J., Letendre S., Brooks A., Lipman A., (2001). Vehicle-to-Grid Power: Battery, Hybrid and Fuel Cell Vehicles as Resources for Distributed Electric Power in California. Davis, CA, Institute of Transportation Studies Report # IUCD-ITS-RR 01-03, 77+xiv pages.

Kennel F., D. G., (2012). Energy Management for Smart Grids with Electric Vehicles based on Hierarchical MPC. *IEEE Trans. Ind. Inform.*, pp. 1528-1537.

Kirby B., Hirst E., (1996). Ancillary services. American Power Conference. Chicago, Illinois.

Kirby B., Hirst E., (2003). Technical Issues Related To Retail-Load Provision of Ancillary Services: Background Issues Discussion, Report for New England Demand Response Initiative. Available at <<http://citeseerx.ist.psu.edu/viewdoc/summary?doi=10.1.1.194.7296>>, last accessed on October 2013.

Lee A. T., (1998). Impact of the Car Sharing Scheme on mode choice. *Proceedings of the 1998 Conference on Traffic and Transportation Studies - ICTTS*. A. R. V. USA. Beijing, China: 508-517.

Lewin K., (1946). Action research and minority problems. *J Soc. Issues* 2(4), pp 34-46.

Little A. D., (2002). Guidance for transportation technologies: fuel choice for fuel cell vehicles (Phase II Final Deliverable to DOE). Cambridge, Massachusetts, Arthur D. Little, Inc.

Maniezzo R. W., (2004). A distributed geographic information system for the daily car pooling problem. *Computers and Operations Research archive* 31(13).

Marques M., (2011). Green Route-Assistente ‘verde’ em viagens na cidade. Student Miguel Marques nº 24676, Final Year Project, ADEETC-ISEL, Lisbon.

Masser I., Sviden O., Wegener M., (1992). From growth to equity and sustainability—paradigm shift in transport planning futures.

MBizon, (2010). Electricity Grid Schematic English. Available at: <http://en.wikipedia.org/wiki/File:Electricity_Grid_Schematic_English.svg>, last accessed on October 2013.

Miketa A., (2004). Technical description on the growth study datasets. International Institute for Applied Systems Analysis (IIASA). E. C. E. S. Program. Luxemburg, Austria.

Milkovits M., Huang, E., Antoniou C., Ben-Akiva M., Lopes J.A., (2010). DynaMIT 2.0: The Next Generation Real-Time Dynamic Traffic Assignment System, *Advances in System Simulation (SIMUL)*, 2010 Second International Conference on , vol., no., pp.45-51, 22-27 Aug. 2010.

Mobieuropa, (2011). Information available at project website, <<http://www.mobieurope.eu/the-project/ongoing-initiatives/mobi-e>>, last accessed on October 2013.

Monteiro V., Ferreira J. C., Pinto G., Pedrosa D., Afonso J. L., (2010). iV2G Charging Platform. *IEEE-ITSC, 13th International IEEE Conference on Intelligent Transportation Systems*. Funchal - Madeira, IEEE Catalog Number: CFP10ITS-CDR: 337.

Monteiro V., Gonçalves H., Ferreira J., Afonso, J., (2012). Batteries Charging Systems for Electric and Plug-In Hybrid Electric Vehicles, in *Automotive Engineering*, João Paulo Carmo, InTech. 2012. ISBN 979-953-307-838-9.

Monteiro V., Ferreira J. C., Meléndez A., Afonso J. L., (2012a). Electric Vehicles On-Board Battery Charger for the Future Smart Grids, L.M. Camarinha-Matos, S. Tomic, and P. Graça (Eds.): *DoCEIS 2013, IFIP AICT 394*, pp. 351–358, 2013

Morency C., et al., (2007). Car sharing system: what transaction datasets can tell us regarding the user behaviors, *The 10th International IEEE Conference on Intelligent Transportation Systems - ITSC 2007*, Seattle, Washington, USA, Sept. 30-Oct. 3, 2007.

Moreno-Muñoz A., et al., (2013). Embedding Synchronized Measurement Technology for Smart Grid Development. *IEEE Trans. Ind. Inform.*, pp. 52-61.

Morrow K., Karner D., (2008). Plug-in Hybrid Electric Vehicle Charging Infrastructure Review, Final report Battelle Energy Alliance, US Department of Energy Vehicle Technologies Platform – Advanced Testing Activity.

Nagata T. K., (2005). Economic analysis of electric-drive vehicles as distributed power resources in California. *22nd Annual North American Conference of the USAEE/IAEE*.

Nijkamp P. E., (1999). Sustainable transport: new research and policy challenge for the next millennium. *European Review* 7 (4): 551–677.

Nilsson M., (2011). Electric vehicles. The phenomenon of range anxiety. Elvire FP7 project, available at <http://www.elvire.eu/IMG/pdf/The_phenomenon_of_range_anxiety_ELVIRE.pdf>, last accessed on October 2013.

Palensky, P. D. D., (2011). Demand Side Management: Demand Response, Intelligent Energy Systems, and Smart Loads. *IEEE Trans. Ind. Inform.*, pp. 381-388.

Paper G., (2007). Towards a new culture for urban mobility. Available at <http://ec.europa.eu/transport/clean/green_paper_urban_transport/doc/2007_09_25_gp_urban_mobility_working_doc_en.pdf>, last accessed on October 2013.

Pereira P., (2010). Sistema de Recomendação para Condutores de Veículos Eléctricos. MSc dissertation - ADEETC- ISEL, Lisbon.

Philip A., Wiederer R., (2010) Policy opinions for electric vehicle charging infrastructure in C40cities. Technical report, Harvard Kennedy School. Available at: <<http://www.innovations.harvard.edu/cache/documents/11089/1108934.pdf>>, last accessed on October 2013.

Pikeresearch, (2010). Electric Vehicle Geographic Forecasts. Available at <<http://www.pikeresearch.com/research/electric-vehicle-geographic-forecasts>>, last accessed on October 2013.

Pinho, (2008). Energias Renováveis em Portugal - Ministério da Economia e da Inovação. Available at <http://www.min-economia.pt/document/Energias_Renov_PT.pdf>, last accessed on December 2011.

Pitfield N. T. F., (2000). Economic and operational evaluation of urban car-sharing. Transportation Research, Part D: Transport and Environment 5: 1-10.

Pitt B. D., Kitschen D. S., (1999). Application of data mining techniques to load profiling. IEEE International Conference on Power Industry Computer Applications, pp. 131-136, May 1999.

Ramada A., (2010). V2G - Modelo de simulação. Final Year Project at ADEETC – ISEL, Lisbon.

Ribeiro A., Silva A.R., (2012). Survey on Cross-Platforms and Languages for Mobile Apps, in Proceedings of QUATIC'2012 Conference, IEEE Computer Society.

Ribeiro A., Silva A.R., (2014). XIS-Mobile: A DSL for Mobile Applications, Proceedings of ACM SAC'2014 Conference, ACM, 2014

Rosmarino T., (2009). A Self-Funding Enterprise Solution to Reduce Power. Available at <<http://www.nysfirm.org/documents/html/2007/execcommittee/may/enterprisepow>>, last accessed on December 2011.

Saber, A. Y., (2011). Plug-in vehicles and renewable energy sources for cost and emission reductions. IEEE Trans. Ind. Electron., pp. 1229-1238.

Sahin D., T. K., (2012). Smart Grid and Smart Homes: Key Players and Pilot Projects. IEEE Ind. Electron, pp. 18-34.

Sanna L., (2005). Driving the solution - the Plug-in Hybrid vehicle. EPRI Journal. David Dietrich ed.

Santos J. S. P., (2010). MyTracking: Sistema de Tracking de Movimentos de Condutores de Veículos em modo “off-line”. ADEETC. Lisbon, ISEL. Final Year Project.

Schott B., (2009). Range Anxiety. The New York Times. Retrieved 26 June 2010. Available at <<http://schott.blogs.nytimes.com/2009/01/15/range-anxiety>>, last accessed on December 2011.

Shahidepour M., (2002). Market Operations in Electric Power Systems Forecasting, Scheduling, and Risk Management. Wiley-IEEE Press.

Silva R., (2008). Bolsa de Objectos Digitais. MSc dissertation – ADEETC- ISEL, Lisbon.

Smartgrid, (2009). Smart Grid | Department of Energy. Available at <<http://energy.gov/oe/technology-development/smart-grid>>, last accessed on October 2013.

Sousa P., (2009). Visualização de dados geográficos em dispositivos móveis. MSc dissertation- ADEETC- ISEL, Lisbon.

Steininger K. W., (1996). Car-sharing organizations - The size of the market segment and revealed change in mobility behavior. *Transport Policy* 3.

Stephen S., Pond E., Campbell C., (2008). Low-carbon attractive, resilient communities: New imperatives for sustainable redevelopment. *Conference Reader, Background Papers and Excerpts Selected Conference Papers, Climate Change and Urban Design Council for European Urbanism* (2008), 42-58.

Stern N., (2006). *Stern Review on The Economics of Climate Change* (pre-publication edition). Executive Summary". HM Treasury, London. Archived from the original on 2010-01-31. Retrieved 2010-01-31.

Tate E. D., et al., (2008) *The Electrification of the Automobile: From Conventional Hybrid, to Plug-in Hybrids, to Extended-Range Electric Vehicles*. SAE technical paper series 2008 World Congress. Reprinted From: *Advanced Hybrid Vehicle Powertrain*, 2008. Detroit, Michigan, April 14-17, 2008.

Tender, (2011). FP7 tender call (May 2011): SMART 2011/0065 - The impact of ICT R&D in the large scale deployment of the electric vehicle.

Thanh L. R. C., et al., (2008). High Level Specification of the Functionality for novel electricity distribution grids.

Timbus A., et al., (2009). Active Management of Distributed Energy Resources Using Standardized Communications and Modern Information Technologies, *IEEE Trans. Ind. Electron.*, vol.56, no.10, pp.4029-4037, Oct. 2009.

Tomić J., Kemptom W., (2007). Using fleets of electric-drive vehicles for grid support. *J. Power Sources*, vol. 168, no. 2, pp.459 -468 2007

Toyota, (2007). *Hybrid Synergy*. <<http://www.motores24h.pt/toyota-prius-hybrid-synergy-drive-hsd-high-pack-carro-276691.html>>, last accessed on December 2011.

Tuttle, R. B., (2012). The Evolution of Plug-In Electric Vehicle-Grid Interactions. *IEEE Trans. Smart Grid*, pp. 500-505.

Tuzhilin A., Gediminas A., (2001). *Multidimensional Recommender Systems: A Data Warehousing Approach*, Springer Berlin/Heidelberg, 2001.

UN, (2004). *World Population to 2300*. New York, Population Division, Department of Economic and Social Affairs, United Nations. Available at <<http://www.un.org/esa/population/publications/longrange2/WorldPop2300final.pdf>> last accessed on October 2013.

WBCSD, (2004). *Mobility 2030: meeting the challenges to sustainability. The Sustainable Mobility Project* World Business Council for Sustainable Development. Available at <<http://www.wbcsd.org/web/publications/mobility/mobility-full.pdf>>, last accessed on October 2013.

Weiwei X., (2009). Optimal energy management for a series-parallel hybrid electric bus. *Energy Conversion and Management* 50 (7).

Wellings T., Binnersley J., Robertson D., Khan T., (2011) *Human machine interfaces in low carbon vehicles: Market trends and user issues*. Dokument No. HMI 2.1. Low carbon vehicle technology project: workstream 13. Available at: <http://www2.warwick.ac.uk/fac/sci/wmg/research/low_carbon/automotive/levtpevents/ws13_hmi_in_levs_market_analysis_and_user_issues_v2_1.pdf>, last accessed on October 2013.

Wencong Su, (2012). A Survey on the Electrification of Transportation in a Smart Grid Environment. *IEEE Trans. Ind. Inform.*, pp. 1-10.

Wright, (2001). The Carlink II pilot program: Testing A commuter-based carsharing model. IEEE Intelligent Transportation Systems Proceedings, Oakland, CA.

Wynn T., Leafeur S., (2009) A free market perspective on electrical vehicles. Technical Report, Cascade Policy Institute.

Xavier A., Lourenço N., (2011). CarSharing. Final Year Project, ADEETC-ISEL, Lisbon.

Yamane H., (2002). Cycle performance in each state-of-charge in LiMn₂O₄. Journal of the Electrochemical Society: vol. 149, no. 2, pp. A1514-A1520. Available at <<http://cat.inist.fr/?aModele=afficheN&cpsidt=14454228>>, last accessed on October 2013.

Zhao J.H., Dong Z.Y., Li X., Wong, K.P., (2007). A framework for electricity price spike analysis with advanced data mining methods, Power Systems, IEEE Transactions on Issue Date, vol 22, Issue 1, Feb. 2007, pp: 376 – 385.